

Printing date 08/15/2022 Version number 83 Reviewed on 08/15/2022

1 Identification

- · Product identifier
 - · Product number PF5K18
 - · Trade name: SPRAY STAIN WENGE'
 - · Application of the substance / the mixture For professional use
- · Details of the supplier of the safety data sheet
 - · Manufacturer/Supplier:

IVM Chemicals Srl

Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture

Flammable Liquids 2 H225 Highly flammable liquid and vapor.

H315 Causes skin irritation. Skin Irrititation 2

Eve Irritation 2A H319 Causes serious eye irritation.

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Carcinogenicity 2 H351 Suspected of causing cancer.

Specific Target Organ Toxicity - Single Exposure 3H336 May cause drowsiness or dizziness.

Specific Target Organ Toxicity - Repeated

Exposure 2

H373 May cause damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Oral, Inhalation.

Aquatic Acute 3 H402 Harmful to aquatic life.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting

effects.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







· Signal word Danger

· Hazard-determining components of labeling:

1-methoxy-2-propanol

C.I. ACID BLACK 194

xylene

C.I. Acid Yellow 151

hydrogenbis[2-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]benzoato(2-)] chromate(1-)

· Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

(Contd. on page 2)



Printing date 08/15/2022 Version number 83 Reviewed on 08/15/2022

Product number PF5K18

Trade name: SPRAY STAIN WENGE'

(Contd. of page 1)

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Oral, Inhalation.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 3

Reactivity = 0

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

· Dangerou	is components:	
107-98-2	1-methoxy-2-propanol	20-24.99%
	Flammable Liquids 3, H226Specific Target Organ Toxicity - Single Exposure 3, H336	
123-86-4	n-butyl acetate	15-19.99%
	Flammable Liquids 3, H226Specific Target Organ Toxicity - Single Exposure 3, H336	
67-64-1	acetone	10-12.49%
	Flammable Liquids 2, H225 Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	
	· ·	(Contd. on nogo

(Contd. on page 3)



Printing date 08/15/2022

Version number 83

Reviewed on 08/15/2022

Product number PF5K18

Trade name: SPRAY STAIN WENGE'

400.05.0		Contd. of page
108-65-6	2-methoxy-1-methylethyl acetate	10-12.49%
	Flammable Liquids 3, H226 Specific Target Organ Toxicity - Single Exposure 3, H336	
4220.20.7	¥	F 0 000/
1330-20-7	xylene	5-9.99%
	 Flammable Liquids 3, H226 Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304 	
	Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irrititation 2, H315; Eye Irritation 2A, H319; Specific Target	
	Organ Toxicity - Single Exposure 3, H335 Aquatic Acute 3, H402; Aquatic Chronic 3, H412	
111-76-2	2-butoxyethanol	5-9.99%
	Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irrititation 2, H315; Eye Irritation 2A, H319 Flammable Liquids 4, H227	
67-63-0	propan-2-ol	2.5-4.99%
	Flammable Liquids 2, H225 Flammable Liquids 2, H225 Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	
57693-14-8	C.I. ACID BLACK 194	2.5-4.99%
	Aquatic Chronic 2, H411 Eye Irritation 2A, H319; Sensitization - Skin 1, H317 Aquatic Acute 2, H401	
72496-88-9	C.I. Acid Yellow 151	1-2.49%
	 Carcinogenicity 2, H351 Sensitization - Skin 1B, H317 Aguatic Acute 3, H402; Aguatic Chronic 3, H412 	
100-41-4	ethylbenzene	1-2.49%
100 41 4	 Flammable Liquids 2, H225 Carcinogenicity 2, H351; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304 Acute Toxicity - Inhalation 4, H332 Aquatic Chronic 3, H412 	7 2.40%
34590-94-8	(2-methoxymethylethoxy)propanol	1-<5%
	Flammable Liquids 4, H227	
5601-29-6	hydrogenbis[2-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl) azo]benzoato(2-)]chromate(1-)	≥0.1-<0.5%
	Eye Irritation 2A, H319; Sensitization - Skin 1A, H317 Aquatic Acute 3, H402; Aquatic Chronic 3, H412	

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 4)



Printing date 08/15/2022 Version number 83 Reviewed on 08/15/2022

Product number PF5K18

Trade name: SPRAY STAIN WENGE'

(Contd. of page 3)

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary). Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
 - · Most important symptoms and effects, both acute and delayed Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
 - · Suitable extinguishing agents:

Alcohol resistant foam

Alcohol resistant foam, CO, powder, water spray/mist.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

(Contd. on page 5)



Printing date 08/15/2022

Version number 83

Reviewed on 08/15/2022

Product number PF5K18

Trade name: SPRAY STAIN WENGE'

(Contd. of page 4)

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:	1-methoxy-2-propanol		100 ppm
	• • •		
	n-butyl acetate		5 ppm
	acetone		200 ppm
	2-methoxy-1-methylethyl acetate		50 ppm
1330-20-7			130 ppm
	2-butoxyethanol		60 ppm
	propan-2-ol		400 ppn
	ethylbenzene		33 ppm
34590-94-8	(2-methoxymethylethoxy)propanol		150 ppn
· PAC-2:			
107-98-2	1-methoxy-2-propanol		160 ppm
123-86-4	n-butyl acetate		200 ppm
67-64-1	acetone		3200* ppn
108-65-6	2-methoxy-1-methylethyl acetate		1,000 ppm
1330-20-7	20-7 xylene		920* ppm
111-76-2	2-butoxyethanol		120 ppm
67-63-0	propan-2-ol		2000* ppn
100-41-4	ethylbenzene ethylbenzene		1100* ppn
34590-94-8	(2-methoxymethylethoxy)propanol		1700* ppn
· PAC-3:			
107-98-2	1-methoxy-2-propanol	6	60 ppm
123-86-4	n-butyl acetate	3	000* ppm
67-64-1	1 acetone		700* ppm
108-65-6	6 2-methoxy-1-methylethyl acetate		000* ppm
1330-20-7			500* ppm
111-76-2			00 ppm
67-63-0	propan-2-ol	12	2000** ppn
100-41-4	ethylbenzene	10	800* ppm
34590-94-8	(2-methoxymethylethoxy)propanol	9	900** ppm

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Protect against electrostatic charges.

Keep respiratory protective device available.

Use explosion-proof apparatus / fittings and spark-proof tools.

(Contd. on page 6)



Printing date 08/15/2022 Version number 83 Reviewed on 08/15/2022

Product number PF5K18

Trade name: SPRAY STAIN WENGE'

(Contd. of page 5)

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

- · Storage:
 - · Requirements to be met by storerooms and receptacles:

Store in a cool, well-ventilated area, away from heat and sources of ignition

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
 - · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

, , , ,	and time, the other conditions have no known expectate innite.
107-98	3-2 1-methoxy-2-propanol
REL	Short-term value: 540 mg/m³, 150 ppm Long-term value: 360 mg/m³, 100 ppm
TLV	Short-term value: 100 ppm Long-term value: 50 ppm A4
123-86	6-4 n-butyl acetate
PEL	Long-term value: 710 mg/m³, 150 ppm
REL	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm
67-64-	1 acetone
PEL	Long-term value: 2400 mg/m³, 1000 ppm
REL	Long-term value: 590 mg/m³, 250 ppm
TLV	Short-term value: 500 ppm Long-term value: 250 ppm A4, BEI
108-6	-6 2-methoxy-1-methylethyl acetate
WEEL	Long-term value: 50 ppm



Printing date 08/15/2022 Version number 83 Reviewed on 08/15/2022

Product number PF5K18

Trade name: SPRAY STAIN WENGE'

-20-7 xylene		(Contd. of p
	lue: 435 mg/m³, 100 ppm	
_	nlue: 655 mg/m³, 150 ppm	
Long-term va	lue: 435 mg/m³, 100 ppm	
	alue: (150) ppm	
BEI, A4	lue: (100) NIC-20 ppm	
76-2 2-butoxye	hanol	
Long-term va Skin	lue: 240 mg/m³, 50 ppm	
Long-term va Skin	lue: 24 mg/m³, 5 ppm	
Long-term va BEI, A3	lue: 20 ppm	
3-0 propan-2-o		
Long-term va	lue: 980 mg/m³, 400 ppm	
	alue: 1225 mg/m³, 500 ppm lue: 980 mg/m³, 400 ppm	
Short-term va Long-term va BEI, A4	alue: 400 ppm lue: 200 ppm	
41-4 ethylbenze	ne	
Long-term va	lue: 435 mg/m³, 100 ppm	
	alue: 545 mg/m³, 125 ppm lue: 435 mg/m³, 100 ppm	
	lue: 20 NIC-20 ppm OTO, BEI, A3	
0-94-8 (2-meth	oxymethylethoxy)propanol	
Long-term va Skin	lue: 600 mg/m³, 100 ppm	
	alue: 900 mg/m³, 150 ppm	
Long-term va Skin	lue: 600 mg/m³, 100 ppm	
Long-term va (Skin)	lue: NIC-50 ppm	
· Ingredients	with biological limit values:	
4-1 acetone		
25 mg/L		
Medium: urine Time: end of sh	ft	
	rone (nonspecific)	
-20-7 xylene		
1.5 g/g creatinir	е	
Medium: urine		
Time: end of sh		
	nylhippuric acids	(Cont



Printing date 08/15/2022 Version

Version number 83

Reviewed on 08/15/2022

Product number PF5K18

Trade name: SPRAY STAIN WENGE'

(Contd. of page 7)

111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

67-63-0 propan-2-ol

BEI 40 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: Acetone (background, nonspecific)

100-41-4 ethylbenzene

BEI 0.15 g/g creatinine

Medium: urine

Time: end of shift at end of workweek

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
 - · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

Short term filter device:

Filter AX



Suitable respiratory protective device recommended.

· Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 9)



Printing date 08/15/2022 Version number 83 Reviewed on 08/15/2022

Product number PF5K18

Trade name: SPRAY STAIN WENGE'

(Contd. of page 8)

· Eye protection:



Tightly sealed goggles

Information on basic physical and o	chemical properties
· General Information	
· Appearance: · Form:	Fluid
· Form: · Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Mixture is non-polar/aprotic.
· Change in condition	<u> </u>
Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	56 °C (132.8 °F)
· Flash point:	-17 °C (1.4 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	270 °C (518 °F)
· Decomposition temperature:	Not determined.
	Product is not selfigniting.
· Auto igniting:	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
· Lower:	1 Vol %
· Upper:	~20 Vol %
· Vapor pressure at 20 °C (68 °F):	233 hPa (174.8 mm Hg)
· Density (+/- 0,03) at 20 °C (68 °F):	0.923 g/cm³ (7.702 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Not determined.
· Partition coefficient (n-octanol/water): Not determined.
· Viscosity:	
· Dynamic:	Not determined.
· Kinematic at 20 °C (68 °F):	29 s (ISO 3 mm)
· Oxidising properties:	N.A.
· Solvent content:	
· VOC content:	76.41 %
	705.3 g/l / 5.89 lb/gal
· Solids content:	12.6 %



Printing date 08/15/2022

Version number 83

Reviewed on 08/15/2022

Product number PF5K18

Trade name: SPRAY STAIN WENGE'

(Contd. of page 9)

· Other information (HAPS)			
1330-20-7	xylene		5-9.99%
100-41-4	ethylbenzene		1-2.49%
112-34-5	2-(2-butoxyethoxy)ethanol <0.01%		<0.01%
Other information No further relevant information available.			

10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
- · Chemical stability The product is stable in normal conditions of storage and use recommended
 - · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

Possibility of hazardous reactions

Reacts with oxidizing agents.

Vapours may form explosive mixtures with air

- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Acids, alkalis and oxidizing agents
- Hazardous decomposition products:

in case of possible formation of combustion:

Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
 - · Acute toxicity:

· Acute to	oxichy:	
· LD/LC50 values that are relevant for classification:		
ATE (Acute Toxicity Estimate)		
Oral	LD50	22,642 mg/kg
Dermal	LD50	9,027 mg/kg
Inhalative	LC50/4 h	83.2 mg/l (mouse)
107-98-2	1-methoxy	r-2-propanol
Oral	LD50	4,016 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 h	5,001 mg/l (mouse)
123-86-4	n-butyl ac	etate
Oral	LD50	10,760 mg/kg (mouse)
Dermal	LD50	14,000 mg/kg (rabbit)
Inhalative	LC50/4 h	21.1 mg/l (mouse)
67-64-1 ad	cetone	
Oral	LD50	5,800 mg/kg (mouse)
Dermal	LD50	20,000 mg/kg (rabbit)
Inhalative	LC50/4 h	76 mg/l (mouse)
108-65-6	2-methoxy	r-1-methylethyl acetate
Oral	LD50	8,532 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
		(Contd. on page



Printing date 08/15/2022

Version number 83

Reviewed on 08/15/2022

Product number PF5K18

Trade name: SPRAY STAIN WENGE'

		(Contd. of page
Inhalative		35.7 mg/l (mouse)
1330-20-7	xylene	
Oral	LD50.	3,523 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rabbit) (ATE value)
	LD50.	12,126 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (mouse) (ATE value)
	LC50/4h.	27.571 mg/l (mouse)
111-76-2	2-butoxye	thanol
Oral	LD50	1,200 mg/kg (ATE)
		1,480 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rab)
Inhalative	LC50/4 h	11 mg/l (mouse)
67-63-0 pi	ropan-2-o	
Oral	LD50	4,710 mg/kg (mouse)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	72.6 mg/l (mouse)
72496-88-	9 C.I. Acid	Yellow 151
Oral	LD50	5,001 mg/kg (mouse)
100-41-4	ethylbenze	ene
Oral	LD50	3,500 mg/kg (mouse)
Dermal	LD50	15,486 mg/kg (rabbit)
Inhalative	LC50/4 h	17.2 mg/l (mouse)
34590-94-	8 (2-meth	oxymethylethoxy)propanol
Oral	LD50	5,135 mg/kg (mouse)
Dermal	LD50	19,020 mg/kg (rabbit)
5601-29-6		nbis[2-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo (2-)]chromate(1-)
Oral	LD50	8,290 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (_)

- · Primary irritant effect:
 - · on the skin: Irritant to skin and mucous membranes.
 - · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

Irritant

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of causing cancer.

May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Oral. Inhalation.

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

· Carcinogenic categories

Ethylbenzene

From IARC MONOGRAPHS VOLUME 77/2000

Human carcinogenicity data

Two studies of workers potentially exposed to ethylbenzene in a production plant and a

(Contd. on page 12)



Printing date 08/15/2022

Version number 83

Reviewed on 08/15/2022

Product number PF5K18

Trade name: SPRAY STAIN WENGE'

(Contd. of page 11)

styrene polymerization plant were available. In the first study, no excess of cancer incidence was found but the description of methods was insufficient to allow proper evaluation of this finding. In the second study, no cancer mortality excess was observed during the follow-up of 15 years.

Evaluation

There is inadequate evidence in humans for the carcinogenicity of ethylbenzene. There is sufficient evidence in experimental animals for the carcinogenicity ofethylbenzene.

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)		
72496-88-9	C.I. Acid Yellow 151	2B
100-41-4	ethylbenzene	2B
· NTP (National Toxicology Program)		
None of the ingredients is listed.		
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

12 Ecological information

· Toxicity Harmful to aquatic life with long lasting effects.

· Aquatic t	toxicity:
107-98-2 1-	methoxy-2-propanol
EC50	21,100 mg/l (daphnia) (48 h)
LC50 (96h)	6,812 mg/l (Fish)
123-86-4 n-	butyl acetate
EC50	397 mg/l (algae) (72 h)
	44 mg/l (daphnia) (48 h)
LC50 (96h)	18 mg/l (Fish)
67-64-1 ace	etone
EC50	8,800 mg/l (daphnia)
LC50 (96h)	5,540 mg/l (Fish)
108-65-6 2-	methoxy-1-methylethyl acetate
EC50	1,001 mg/l (algae) (72 h)
	501 mg/l (daphnia) (48 h)
LC50 (96h)	134 mg/l (Fish)
ל 1330-20-7	kylene
EC50	2.2 mg/l (algae)
LC50 48h	1 mg/l (daphnia)
LC50 (96h)	2.6 mg/l (Fish)
111-76-2 2-	butoxyethanol
EC50	101 mg/l (daphnia) (24 h)
LC50 (96h)	101 mg/l (Fish)
67-63-0 pro	ppan-2-ol
EC50	1,001 mg/l (algae) (72 h)
	10,000 mg/l (daphnia) (24 h)
LC50 (96h)	9,640 mg/l (Fish)
	(Contd. on page 1



Printing date 08/15/2022 Version number 83 Reviewed on 08/15/2022

Product number PF5K18

Trade name: SPRAY STAIN WENGE'

	(Contd. of page 12)
100-41-4 et	hylbenzene
EC50	438 mg/l (algae) (72h)
	1.8 mg/l (daphnia) (48 h)
LC50 (96h)	12.1 mg/l (Fish)
34590-94-8	(2-methoxymethylethoxy)propanol
EC50	970 mg/l (algae) (72 h)
	1,919 mg/l (daphnia) (48 h)
LC50 (96h)	1,001 mg/l (Fish)
	nydrogenbis[2-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo] penzoato(2-)]chromate(1-)
LC50 48h	75 mg/l (daphnia)
	Sodium bis[2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-methyl-2-phenyl-3H-pyrazol-3-onato(2-)]chromate(1-)
LC50 48h	24.1 mg/l (daphnia)
LC50 (96h)	3.7 mg/l (Fish)

· Persistence and degradability No further relevant information available.

· Substances Easily biodegradable		
107-98-2	1-methoxy-2-propanol	
123-86-4	n-butyl acetate	
67-64-1	acetone	
108-65-6	2-methoxy-1-methylethyl acetate	
1330-20-7	xylene	
111-76-2	2-butoxyethanol	
67-63-0	propan-2-ol	
100-41-4	ethylbenzene	
34590-94-8	(2-methoxymethylethoxy)propanol	

· Behavior in environmental systems:

- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
 - · Remark: Harmful to fish
- · Additional ecological information:
 - · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

(Contd. on page 14)



Printing date 08/15/2022 Version number 83 Reviewed on 08/15/2022

Product number PF5K18

Trade name: SPRAY STAIN WENGE'

(Contd. of page 13)

- · Uncleaned packagings:
 - · Recommendation: Disposal must be made according to official regulations.
 - · Recommended cleansing agent: Water, if necessary with cleansing agents.

Transport information	
UN-Number	
· DOT	NA1263
· IMDG, IATA	UN1263
· Note	Check viscosity and flash point at section 9
UN proper shipping name	
· DOT	Paint PAINT
· IMDG, IATA	PAIIVI
Transport hazard class(es)	
\cdot DOT	
FLAMMABLE LIQUID	
3	
· Class	3 Flammable liquids
· Label	3
· Class · Label	3 Flammable liquids 3
	3
· IMDG, IATA	
3	
· Class	3 Flammable liquids
· Label	3
Packing group	
· DOT, IMDG, IATA	II .
Environmental hazards:	A/-
· Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
· Hazard identification number (· EMS Number:	Kemler code): 33 F-E, <u>S-E</u>
· Stowage Category	Р- <u>-</u> <u>, 5</u> В
Transport in bulk according to Ar	nnex II of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information.	* *
· IMDG	
· Limited quantities (LQ)	1L



Printing date 08/15/2022

Version number 83

Reviewed on 08/15/2022

Product number PF5K18

Trade name: SPRAY STAIN WENGE'

(Contd. of page 14)

· Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30

ml

Maximum net quantity per outer packaging:

500 ml

· UN "Model Regulation": UN 1263 PAINT, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

- · Various regulations
 - · SARA

· SAKA			
· Se	ction 355 (extremely hazardous substances):		
None of the	ingredients is listed.		
· Se	ction 313 (Specific toxic chemical listings) :		
1330-20-7	xylene	5-9.99%	
111-76-2	2-butoxyethanol	5-9.99%	
67-63-0	propan-2-ol	2.5-4.99%	
72496-88-9	C.I. Acid Yellow 151	1-2.49%	
100-41-4	ethylbenzene	1-2.49%	
110-82-7	cyclohexane	<0.025%	
112-34-5	2-(2-butoxyethoxy)ethanol	<0.01%	
· TSCA	· TSCA (Toxic Substances Control Act):		
All components have the value ACTIVE.			
· Hazardous Air Pollutants			
1330-20-7	xylene		
72496-88-9	C.I. Acid Yellow 151		

· Proposition 65

100-41-4 ethylbenzene

· Chemicals known to cause cancer:	
100-41-4 ethylbenzene	* 1-2.49%
· Chemicals known to cause reproductive toxicity for females:	
1589-47-5 2-methoxypropanol	<0.1%
70657-70-4 2-methoxypropyl acetate	<0.1%

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

. 1	EPA (Environmental Protection Agency)		
67-64-1	acetone	I	10-12.49%
1330-20-7	xylene	1	5-9.99%
		(Cc	ontd. on page 16)



Printing date 08/15/2022 Version number 83 Reviewed on 08/15/2022

Product number PF5K18

SPRAY STAIN WENGE' Trade name:

			ontd. of page 15
111-76-2	2-butoxyethanol	NL	5-9.99%
100-41-4	ethylbenzene	D	1-2.49%
110-82-7	cyclohexane	1	<0.025%
· T	· TLV (Threshold Limit Value)		
67-64-1	acetone		A4
1330-20-7	xylene		A4
111-76-2	2-butoxyethanol		A3
67-63-0	propan-2-ol		A4
100-41-4	ethylbenzene		A3
· N	IOSH-Ca (National Institute for Occupational Safety and Health)		
None of the	e ingredients is listed.		

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
 - · Date of preparation / last revision 08/15/2022 / 82
 - · Abbreviations and acronvms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids - Category 2

Flammable Liquids 3: Flammable liquids – Category 3

Flammable Liquids 4: Flammable liquids - Category 4

Acute Toxicity - Dermal 4: Acute toxicity - Category 4 Skin Irrititation 2: Skin corrosion/irritation - Category 2

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Sensitization - Skin 1: Skin sensitisation - Category 1

Sensitization - Skin 1A: Skin sensitisation - Category 1A

Sensitization - Skin 1B: Skin sensitisation - Category 1B

Carcinogenicity 2: Carcinogenicity - Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3
Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2

Aspiration Hazard 1: Aspiration hazard – Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard - Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

(Contd. on page 17)



Printing date 08/15/2022

Version number 83

Reviewed on 08/15/2022

Product number PF5K18

Trade name: SPRAY STAIN WENGE'

(Contd. of page 16)

·Sources

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site INRS Fiche Toxicologique IARC International agency for research on cancer

* Data compared to the previous version altered.

US