

1 Identification

- **Product identifier**

- *Product number* TG1323
- *Trade name:* **PE CLEAR SEALER**
- *Application of the substance / the mixture* For professional use

- **Details of the supplier of the safety data sheet**

- *Manufacturer/Supplier:*
IVM Chemicals Srl
Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441

1.3.2 Importer

Name I.C.& S. DISTRIBUTING CO.
 Address P.O.BOX 10845
 LANCASTER. PA
 USA
 E-Mail: nelson@ics-company.com

- *Information department:*

Environmental Health and safety office
 hseoffice@ivmchemicals.com

- *Emergency telephone number:*

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.
 001 813-248-0585

2 Hazard(s) identification

- **Classification of the substance or mixture**

Flammable Liquids 2	H225	Highly flammable liquid and vapor.
Skin Irritation 2	H315	Causes skin irritation.
Eye Irritation 2A	H319	Causes serious eye irritation.
Sensitization - Skin 1	H317	May cause an allergic skin reaction.
Carcinogenicity 1B	H350	May cause cancer.
Toxic to Reproduction 2	H361	Suspected of damaging fertility or the unborn child.
Specific Target Organ Toxicity - Repeated Exposure 1	H372-H373	Causes damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalation. May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

- **Label elements**

- *GHS label elements*

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Product number TG1323
Trade name: PE CLEAR SEALER

(Contd. of page 1)

· **Hazard pictograms**



· **Signal word** Danger

· **Hazard-determining components of labeling:**

styrene
maleic anhydride
toluene

· **Hazard statements**

H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H350 May cause cancer.
H361 Suspected of damaging fertility or the unborn child.
H372-H373 Causes damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalation. May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral.
H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



3 Composition/information on ingredients



















· **Chemical characterization: Mixtures**

· **Description:** Mixture: consisting of the following components.

(Contd. on page 3)

Product number TG1323**Trade name: PE CLEAR SEALER**

(Contd. of page 2)

· Dangerous components:		
100-42-5	styrene  Flammable Liquids 3, H226  Carcinogenicity 1B, H350; Toxic to Reproduction 2, H361; Specific Target Organ Toxicity - Repeated Exposure 1, H372  Acute Toxicity - Inhalation 4, H332; Skin Irritation 2, H315; Eye Irritation 2A, H319 Aquatic Chronic 3, H412	30-39.99%
108-88-3	toluene  Flammable Liquids 2, H225  Toxic to Reproduction 2, H361; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304  Skin Irritation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H336 Aquatic Chronic 3, H412	2.5-4.99%
67-64-1	acetone  Flammable Liquids 2, H225  Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	1-2.49%
110-19-0	isobutyl acetate  Flammable Liquids 2, H225  Specific Target Organ Toxicity - Single Exposure 3, H336	0.5-1%
141-78-6	ethyl acetate  Flammable Liquids 2, H225  Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	0.5-1%
57-55-6	propane-1,2-diol	<0.5%
67-56-1	methanol  Flammable Liquids 2, H225  Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331  Specific Target Organ Toxicity - Single Exposure 1, H370	<0.5%
108-31-6	maleic anhydride  Sensitization - Respiratory 1, H334  Skin Corrosion 1B, H314  Acute Toxicity - Oral 4, H302; Sensitization - Skin 1, H317	≥0.001-<0.1%

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary).

Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

(Contd. on page 4)

Product number TG1323**Trade name: PE CLEAR SEALER**

(Contd. of page 3)

- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; immediately call for medical help.
- **Information for doctor:**
 - **Most important symptoms and effects, both acute and delayed**
Allergic reactions
For symptoms and effects caused by substances, refer to Section 11.
 - **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
 - **Suitable extinguishing agents:**
Alcohol resistant foam
Alcohol resistant foam, CO, powder, water spray/mist.
 - **For safety reasons unsuitable extinguishing agents:**
Do not use a jet water stream as it may scatter and spread fire.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
In case of fire, the following can be released:
Nitrogen oxides (NO_x)
Carbon monoxide (CO)
- **Advice for firefighters**
Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.
 - **Protective equipment:**
Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to Section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. on page 5)

US

Product number TG1323
Trade name: PE CLEAR SEALER

(Contd. of page 4)

· Protective Action Criteria for Chemicals

· PAC-1:		
100-42-5	styrene	20 ppm
108-88-3	toluene	67 ppm
67-64-1	acetone	200 ppm
110-19-0	isobutyl acetate	450 ppm
141-78-6	ethyl acetate	1,200 ppm
57-55-6	propane-1,2-diol	30 mg/m
67-56-1	methanol	530 ppm
· PAC-2:		
100-42-5	styrene	130 ppm
108-88-3	toluene	560 ppm
67-64-1	acetone	3200* ppm
110-19-0	isobutyl acetate	1300* ppm
141-78-6	ethyl acetate	1,700 ppm
57-55-6	propane-1,2-diol	1,300 mg/m
67-56-1	methanol	2,100 ppm
· PAC-3:		
100-42-5	styrene	1100* ppm
108-88-3	toluene	3700* ppm
67-64-1	acetone	5700* ppm
110-19-0	isobutyl acetate	7500** ppm
141-78-6	ethyl acetate	10000** ppm
57-55-6	propane-1,2-diol	7,900 mg/m
67-56-1	methanol	7200* ppm

7 Handling and storage

· Handling:
· Precautions for safe handling

- Ensure good ventilation/exhaustion at the workplace.
- Open and handle receptacle with care.
- Prevent formation of aerosols.
- Protect against electrostatic charges.
- Keep respiratory protective device available.
- Use explosion-proof apparatus / fittings and spark-proof tools.

· Information about protection against explosions and fires:

- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities
· Storage:
· Requirements to be met by storerooms and receptacles:

- Store in a cool, well-ventilated area, away from heat and sources of ignition
- Provide solvent resistant, sealed floor.
- Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.
- In cases where there is no reported expiration date, it means that the product must be used within 8 months.

(Contd. on page 6)

Product number TG1323
Trade name: PE CLEAR SEALER

(Contd. of page 5)

- *Information about storage in one common storage facility: Not required.*
- *Further information about storage conditions:*
 Keep receptacle tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· *Components with limit values that require monitoring at the workplace:*

100-42-5 styrene

PEL	Long-term value: 100 ppm Ceiling limit value: 200; 600* ppm *5-min peak in any 3 hrs
REL	Short-term value: 425 mg/m , 100 ppm Long-term value: 215 mg/m , 50 ppm
TLV	Short-term value: 20 ppm Long-term value: 10 ppm BEI, OTO, A3

108-88-3 toluene

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m , 150 ppm Long-term value: 375 mg/m , 100 ppm
TLV	Long-term value: 20 ppm BEI, OTO, A4

67-64-1 acetone

PEL	Long-term value: 2400 mg/m , 1000 ppm
REL	Long-term value: 590 mg/m , 250 ppm
TLV	Short-term value: 500 ppm Long-term value: 250 ppm A4, BEI

110-19-0 isobutyl acetate

PEL	Long-term value: 700 mg/m , 150 ppm
REL	Long-term value: 700 mg/m , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

141-78-6 ethyl acetate

PEL	Long-term value: 1400 mg/m , 400 ppm
REL	Long-term value: 1400 mg/m , 400 ppm
TLV	Long-term value: 400 ppm

57-55-6 propane-1,2-diol

WEEL	Long-term value: 10 mg/m
------	--------------------------

(Contd. on page 7)

Product number TG1323**Trade name: PE CLEAR SEALER**

(Contd. of page 6)

67-56-1 methanol

PEL	Long-term value: 260 mg/m , 200 ppm
REL	Short-term value: 325 mg/m , 250 ppm
	Long-term value: 260 mg/m , 200 ppm
	Skin
TLV	Short-term value: 250 ppm
	Long-term value: 200 ppm
	Skin; BEI

108-31-6 maleic anhydride

PEL	Long-term value: 1 mg/m , 0.25 ppm
REL	Long-term value: 1 mg/m , 0.25 ppm
TLV	Long-term value: 0.01* mg/m
	DSEN, RSEN; *inh. fraction + vapor, A4

· *Ingredients with biological limit values:*

100-42-5 styrene

BEI	400 mg/g creatinine
	Medium: urine
	Time: end of shift
	Parameter: Mandelic acid plus phenylglyoxylic acid (nonspecific)
	40 g/L
	Medium: urine
	Time: end of shift
	Parameter: Styrene

108-88-3 toluene

BEI	0.02 mg/L
	Medium: blood
	Time: prior to last shift of workweek
	Parameter: Toluene
	0.03 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Toluene
	0.3 mg/g creatinine
	Medium: urine
	Time: end of shift
	Parameter: o-Cresol with hydrolysis (background)

67-64-1 acetone

BEI	25 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Acetone (nonspecific)

67-56-1 methanol

BEI	15 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Methanol (background, nonspecific)

· *Additional information:* The lists that were valid during the creation were used as basis.

(Contd. on page 8)

Product number TG1323
Trade name: PE CLEAR SEALER

(Contd. of page 7)

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.
- Pregnant women should strictly avoid inhalation or skin contact.

· Breathing equipment:

- Short term filter device:
- Filter AX



Suitable respiratory protective device recommended.

· Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

- Form:** Fluid
- Color:** According to product specification
- Odor:** Characteristic
- Odor threshold:** Not determined.

· pH-value: Mixture is non-polar/aprotic.

· Change in condition

- Melting point/Melting range:** Undetermined.

(Contd. on page 9)

Product number TG1323
Trade name: PE CLEAR SEALER

(Contd. of page 8)

· Boiling point/Boiling range:	56 °C (132.8 °F)	
· Flash point:	-17 °C (1.4 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	>370 °C (>698 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.	
· Explosion limits:		
· Lower:	1.2 Vol %	
· Upper:	30 Vol %	
· Vapor pressure at 20 °C (68 °F):	233 hPa (174.8 mm Hg)	
· Density (+/- 0,03) at 20 °C (68 °F):	1.016 g/cm (8.479 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water):	Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
· Kinematic at 20 °C (68 °F):	40 s (ISO 4 mm)	
· Oxidising properties:	N.A.	
· Solvent content:		
· Water:	0.0 %	
· VOC content:	38.12 % 387.3 g/l / 3.23 lb/gal	
· Solids content:	92.0 %	
· Other information (HAPS)		
100-42-5	styrene	30-39.99%
108-88-3	toluene	2.5-4.99%
67-56-1	methanol	<0.5%
108-31-6	maleic anhydride	≥0.001-<0.1%
· Other information	No further relevant information available.	

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents

(Contd. on page 10)

-US

Product number TG1323
Trade name: PE CLEAR SEALER

(Contd. of page 9)

· **Hazardous decomposition products:**

in case of possible formation of combustion:
 Carbon monoxide and carbon dioxide

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	401,437 mg/kg (mouse)
Inhalative	LC50/4 h	35.9 mg/l (mouse)

100-42-5 styrene

Oral	LD50	5,000 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (mouse)
Inhalative	LC50/4 h	11.8 mg/l (mouse)

108-88-3 toluene

Oral	LD50	5,000 mg/kg (mouse)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	25.7 mg/l (mouse)

67-64-1 acetone

Oral	LD50	5,800 mg/kg (mouse)
Dermal	LD50	20,000 mg/kg (rabbit)
Inhalative	LC50/4 h	76 mg/l (mouse)

110-19-0 isobutyl acetate

Oral	LD50	13,400 mg/kg (mouse)
Dermal	LD50	17,401 mg/kg (rabbit)
Inhalative	LC50/4 h	31 mg/l (mouse)

141-78-6 ethyl acetate

Oral	LD50	4,934 mg/kg (rabbit)
Dermal	LD50	20,001 mg/kg (rabbit)
Inhalative	LC50/4 h	1,600 mg/l (mouse)
	LC0	22.6 ppm (mouse)

57-55-6 propane-1,2-diol

Oral	LD50	20,000 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (mouse)

67-56-1 methanol

Oral	LD50	1,187 mg/kg (mouse)
Dermal	LD50	17,000 mg/kg (rabbit)
Inhalative	LC50/4 h	128.2 mg/l (mouse)

128601-23-0 Hydrocarbons, C9, aromatics

Oral	LD50	3,492 mg/kg (mouse)
Dermal	LD50	3,161 mg/kg (rabbit)
Inhalative	LC50/4 h	6,194 mg/l (mouse)

(Contd. on page 11)

Product number TG1323
Trade name: PE CLEAR SEALER

(Contd. of page 10)

68551-17-7 Alkanes, C10-13-iso-

Oral	LD50	15,900 mg/kg (mouse)
------	------	----------------------

108-31-6 maleic anhydride

Oral	LD50	1,090 mg/kg (mouse)
Dermal	LD50	2,620 mg/kg (rabbit)

· **Primary irritant effect:**· *on the skin:* Irritant to skin and mucous membranes.· *on the eye:* Irritating effect.· **Sensitization:** Sensitization possible through skin contact.· **Additional toxicological information:**

Irritant

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause cancer.

Suspected of damaging fertility or the unborn child.

Causes damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalation.

May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral.

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

· **Carcinogenic categories**

Styrene

An increased incidence of lung tumors was observed in mice from an inhalation study on styrene. The relevance of this finding to humans is uncertain since data from mode of action investigations of mouse lung tumors coupled with other long-term animal studies and epidemiology studies of workers

exposed to styrene do not provide a basis to conclude that styrene is carcinogenic.

· **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

100-42-5	styrene	2A
----------	---------	----

· **NTP (National Toxicology Program)**

100-42-5	styrene	30-39.99%
----------	---------	-----------

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information· **Toxicity** Harmful to aquatic life with long lasting effects.· **Aquatic toxicity:****100-42-5 styrene**

EC50	4.9 mg/l (algae) (72 h)
	4.7 mg/l (daphnia) (48 h)
LC50 (96h)	4.02 mg/l (Fish)

108-88-3 toluene

EC50	134 mg/l (algae) (96 h)
	3.78 mg/l (daphnia) (48 h)
LC50 (96h)	5.5 mg/l (Fish)

(Contd. on page 12)

Product number TG1323
Trade name: PE CLEAR SEALER

(Contd. of page 11)

67-64-1 acetone

EC50 8,800 mg/l (daphnia)

LC50 (96h) 5,540 mg/l (Fish)

110-19-0 isobutyl acetate

EC50 370 mg/l (algae) (72 h)

25 mg/l (daphnia)

LC50 (96h) 17 mg/l (Fish)

141-78-6 ethyl acetate

EC50 165 mg/l (daphnia) (48 h)

LC50 (96h) 230 mg/l (Fish)

57-55-6 propane-1,2-diol

EC50 19,000 mg/l (algae) (48 h)

18,340 mg/l (daphnia) (48 h)

LC50 (96h) 40,613 mg/l (Fish)

67-56-1 methanol

EC50 8,000 mg/l (algae) (72 h)

24,500 mg/l (daphnia) (48 h)

LC50 (96h) 15,400 mg/l (Fish)

128601-23-0 Hydrocarbons, C9, aromatics

EC50 2.9 mg/l (algae) (72 h)

3.2 mg/l (daphnia) (48 h)

LC50 (96h) 9.2 mg/l (Fish)

108-31-6 maleic anhydride

EC50 29 mg/l (algae) (72 h)

42.8 mg/l (daphnia) (48 h)

LC50 (96h) 75 mg/l (Fish)

· **Persistence and degradability** No further relevant information available.

· **Substances Easily biodegradable**

100-42-5 styrene .

108-88-3 toluene .

67-64-1 acetone .

110-19-0 isobutyl acetate .

141-78-6 ethyl acetate .

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Ecotoxicological effects:**

· **Remark:** Harmful to fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

(Contd. on page 13)

US

Product number TG1323
Trade name: PE CLEAR SEALER

(Contd. of page 12)

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· DOT, IMDG, IATA

UN1263

· Note

Check viscosity and flash point at section 9

· **UN proper shipping name**

· DOT

Paint

· IMDG, IATA

PAINT

· **Transport hazard class(es)**

· DOT



· Class

3 Flammable liquids

· Label

3

· Class

3 Flammable liquids

· Label

3

· IMDG, IATA



· Class

3 Flammable liquids

· Label

3

· **Packing group**

· DOT, IMDG, IATA

II

· **Environmental hazards:**

· Marine pollutant:

No

· **Special precautions for user**

Warning: Flammable liquids

· Hazard identification number (Kemler code):

33

· EMS Number:

F-E, S-E

· Stowage Category

B

(Contd. on page 14)

Product number TG1323
Trade name: PE CLEAR SEALER

(Contd. of page 13)

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **IMDG**

· **Limited quantities (LQ)** 5L
 · **Excepted quantities (EQ)** Code: E2
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":** UN 1263 PAINT, 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
 Requirements of Federal Register

· **Various regulations**
 · SARA

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings) :**

100-42-5	styrene	30-39.99%
108-88-3	toluene	2.5-4.99%
67-56-1	methanol	<0.5%
108-31-6	maleic anhydride	≥0.001-<0.1%
1338-02-9	Naphthenic acids, copper salts	<0.01%
142-71-2	copper di(acetate)	<0.01%

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

100-42-5	styrene
108-88-3	toluene
67-56-1	methanol
108-31-6	maleic anhydride

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-42-5	styrene	*	30-39.99%
----------	---------	---	-----------

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene	2.5-4.99%
----------	---------	-----------

(Contd. on page 15)

Product number TG1323**Trade name: PE CLEAR SEALER**

(Contd. of page 14)

67-56-1	methanol	<0.5%
---------	----------	-------

- **Carcinogenic categories**

· EPA (Environmental Protection Agency)		
108-88-3	toluene	II 2.5-4.99%
67-64-1	acetone	I 1-2.49%

· TLV (Threshold Limit Value)		
100-42-5	styrene	A4
108-88-3	toluene	A4
67-64-1	acetone	A4
108-31-6	maleic anhydride	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)		
None of the ingredients is listed.		

- **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl
- **Contact:** See emergency phone
 - **Date of preparation / last revision** 09/07/2022 / 96
 - **Abbreviations and acronyms:**
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - NFPA: National Fire Protection Association (USA)
 - HMS: Hazardous Materials Identification System (USA)
 - VOC: Volatile Organic Compounds (USA, EU)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - NIOSH: National Institute for Occupational Safety
 - OSHA: Occupational Safety & Health
 - TLV: Threshold Limit Value
 - PEL: Permissible Exposure Limit
 - REL: Recommended Exposure Limit
 - BEI: Biological Exposure Limit
 - Flammable Liquids 2: Flammable liquids . Category 2
 - Flammable Liquids 3: Flammable liquids . Category 3
 - Acute Toxicity - Oral 3: Acute toxicity . Category 3
 - Acute Toxicity - Inhalation 4: Acute toxicity . Category 4
 - Skin Corrosion 1B: Skin corrosion/irritation . Category 1B
 - Skin Irritation 2: Skin corrosion/irritation . Category 2
 - Eye Irritation 2A: Serious eye damage/eye irritation . Category 2A
 - Sensitization - Respiratory 1: Respiratory sensitisation . Category 1
 - Sensitization - Skin 1: Skin sensitisation . Category 1
 - Carcinogenicity 1B: Carcinogenicity . Category 1B
 - Toxic to Reproduction 2: Reproductive toxicity . Category 2

(Contd. on page 16)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/07/2022

Version number 97

Reviewed on 09/07/2022

Product number TG1323**Trade name: PE CLEAR SEALER**

(Contd. of page 15)

*Specific Target Organ Toxicity - Single Exposure 1: Specific target organ toxicity (single exposure) . Category 1**Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) . Category 3**Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) . Category 1**Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) . Category 2**Aspiration Hazard 1: Aspiration hazard . Category 1**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3***• Sources****REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments**

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

• * Data compared to the previous version altered.

US