

Printing date 08/08/2022

Version number 1

Reviewed on 08/08/2022

#### 1 Identification

- · Product identifier
  - · Product number HUM5AA34
  - · Trade name: SELF SEALER WB UV CLEAR 30 GL
    - · Application of the substance / the mixture For professional use
- · Details of the supplier of the safety data sheet
  - · Manufacturer/Supplier:

IVM Chemicals Srl

Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441

1.3.2 Importer

Name I.C.& S. DISTRIBUTING CO.

Address P.O.BOX 10845

LANCASTER. PA

USA

E-Mail: nelson@ics-company.com

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

001 813-248-0585

## 2 Hazard(s) identification

· Classification of the substance or mixture

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- · Label elements
  - · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labeling:

Trimethylolpropane, ethoxylated, esters with acrylic acid

Glycerol, propoxylated, esters with acrylic acid

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid

· Hazard statements

H317 May cause an allergic skin reaction.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P321 Specific treatment (see on this label).
P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

(Contd. on page 2)



Printing date 08/08/2022

Version number 1

Reviewed on 08/08/2022

**Product number HUM5AA34** 

Trade name: SELF SEALER WB UV CLEAR 30 GL

(Contd. of page 1)

#### · Classification system:

· NFPA ratings (scale 0 - 4)



Health = 0 Fire = 1 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0 Fire = 1 Reactivity = 0

## 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

28061-12 5	Trimethylolpropane, ethoxylated, esters with acrylic acid	2.5-4.99%
20901-43-3	Eye Irritation 2A, H319; Sensitization - Skin 1B, H317     Aquatic Chronic 3, H412	2.3-4.99/0
7473-98-5	2-hydroxy-2-methylpropiophenone	<2.5%
111-90-0	Diethylene glycol monoethyl ether Flammable Liquids 4, H227	0.5-1%
112-34-5	2-(2-butoxyethoxy)ethanol  © Eye Irritation 2A, H319	0.5-1%
111-76-2	2-butoxyethanol  Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irrititation 2, H315; Eye Irritation 2A, H319  Flammable Liquids 4, H227	<0.5%
52408-84-1	Glycerol, propoxylated, esters with acrylic acid  © Eye Irritation 2A, H319; Sensitization - Skin 1, H317	≥0.1-<1%
55818-57-0	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid Aquatic Chronic 2, H411 Sensitization - Skin 1, H317 Aquatic Acute 2, H401	≥0.25-<1%
121-44-8	triethylamine  Flammable Liquids 2, H225 Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331 Skin Corrosion 1A, H314 Acute Toxicity - Oral 4, H302	<0.5%
68439-49-6	c16-18 alcohols ethoxylated  ♦ Acute Toxicity - Oral 3, H301  ⇒ Eye Damage 1, H318	<0.5%



Printing date 08/08/2022 Version number 1 Reviewed on 08/08/2022

**Product number HUM5AA34** 

Trade name: SELF SEALER WB UV CLEAR 30 GL

		(Contd. of page 2)
34590-94-8	(2-methoxymethylethoxy)propanol	<1%
	Flammable Liquids 4, H227	
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)	≥0.00025-<0.0015%
	<ul> <li>Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 2, H310; Acute Toxicity - Inhalation 2, H330</li> <li>Skin Corrosion 1B, H314; Eye Damage 1, H318</li> <li>Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100)</li> <li>Sensitization - Skin 1A, H317</li> </ul>	

### 4 First-aid measures

#### · Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
  - Most important symptoms and effects, both acute and delayed Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

## 5 Fire-fighting measures

#### · Extinguishing media

· Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

### Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.



Printing date 08/08/2022

Version number 1

Reviewed on 08/08/2022

**Product number HUM5AA34** 

Trade name: SELF SEALER WB UV CLEAR 30 GL

(Contd. of page 3)

## 6 Accidental release measures

#### · Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

#### · Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

#### Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

#### · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### · Protective Action Criteria for Chemicals

· PAC-1:			
7631-86-9	silicon dioxide, chemically prepared		18 mg/m³
111-90-0	Diethylene glycol monoethyl ether		75 ppm
112-34-5	2-(2-butoxyethoxy)ethanol		30 ppm
111-76-2	2-butoxyethanol		60 ppm
68439-49-6	c16-18 alcohols ethoxylated		3.8 mg/m <sup>3</sup>
121-44-8	triethylamine		1 ppm
68439-49-6	c16-18 alcohols ethoxylated		3.8 mg/m <sup>3</sup>
34590-94-8	(2-methoxymethylethoxy)propanol		150 ppm
· PAC-2:			•
7631-86-9	silicon dioxide, chemically prepared		740 mg/m <sup>3</sup>
111-90-0	Diethylene glycol monoethyl ether		100 ppm
112-34-5	2-(2-butoxyethoxy)ethanol		33 ppm
111-76-2	2-butoxyethanol		120 ppm
68439-49-6	c16-18 alcohols ethoxylated		42 mg/m³
121-44-8	triethylamine		170 ppm
68439-49-6	c16-18 alcohols ethoxylated		42 mg/m³
34590-94-8	(2-methoxymethylethoxy)propanol		1700* ppm
· PAC-3:			
7631-86-9	silicon dioxide, chemically prepared	4	1,500 mg/m <sup>3</sup>
111-90-0	Diethylene glycol monoethyl ether	4	150 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	2	200 ppm
111-76-2	2-butoxyethanol	7	700 ppm
68439-49-6	c16-18 alcohols ethoxylated	2	250 mg/m³
121-44-8	triethylamine	1	1,000 ppm
68439-49-6	c16-18 alcohols ethoxylated	2	250 mg/m³
34590-94-8	(2-methoxymethylethoxy)propanol	9	9900** ppm

-US



Printing date 08/08/2022 Version number 1 Reviewed on 08/08/2022

**Product number HUM5AA34** 

Trade name: SELF SEALER WB UV CLEAR 30 GL

(Contd. of page 4)

## 7 Handling and storage

- · Handling:
  - · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
  - · Storage:
    - Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
  - · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits

All	nis time, the other constituents have no known exposure limits.			
111-90	1-0 Diethylene glycol monoethyl ether			
WEEL	Long-term value: 25 ppm			
112-34	112-34-5 2-(2-butoxyethoxy)ethanol			
TLV	Long-term value: 10* ppm *Inhalable fraction and vapor			
111-76	-2 2-butoxyethanol			
PEL	Long-term value: 240 mg/m³, 50 ppm Skin			
REL	Long-term value: 24 mg/m³, 5 ppm Skin			
TLV	Long-term value: 20 ppm BEI, A3			
121-44	-8 triethylamine			
PEL	Long-term value: 100 mg/m³, 25 ppm			
TLV	Short-term value: 1 ppm Long-term value: 0.5 ppm Skin, A4			
34590-	4590-94-8 (2-methoxymethylethoxy)propanol			
PEL	Long-term value: 600 mg/m³, 100 ppm Skin			
REL	Short-term value: 900 mg/m³, 150 ppm Long-term value: 600 mg/m³, 100 ppm Skin			

(Contd. on page 6)



Printing date 08/08/2022 Reviewed on 08/08/2022 Version number 1

**Product number HUM5AA34** 

SELF SEALER WB UV CLEAR 30 GL Trade name:

(Contd. of page 5)

TLV Long-term value: NIC-50 ppm (Skin)

· Ingredients with biological limit values:

### 111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

· Additional information: The lists that were valid during the creation were used as basis.

#### · Exposure controls

- · Personal protective equipment:
  - · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· Breathing equipment: Short term filter device:



Suitable respiratory protective device recommended.

Filter A

· Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

### 9 Physical and chemical properties

#### · Information on basic physical and chemical properties

- · General Information
  - · Appearance:

· Form:

· Color: According to product specification

Fluid

· Odor: Characteristic · Odor threshold:

Not determined.

(Contd. on page 7)



Printing date 08/08/2022 Version number 1 Reviewed on 08/08/2022

**Product number HUM5AA34** 

Trade name: SELF SEALER WB UV CLEAR 30 GL

		(Contd. of page
· pH-value:	Mixture is non-polar/aprotic. Range: 7 - 9	
<ul> <li>Change in condition</li> <li>Melting point/Melting range:</li> <li>Boiling point/Boiling range:</li> </ul>	Undetermined. 100°C (212°F)	
· Flash point:	100 °C (212 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	>370 °C (>698 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion	hazard.
· Explosion limits: · Lower: · Upper:	Not determined. Not determined.	
· Vapor pressure at 20 °C (68 °F):	0 hPa	
<ul> <li>Density (+/- 0,03) at 20 °C (68 °F)</li> <li>Relative density</li> <li>Vapor density</li> <li>Evaporation rate</li> </ul>	: 1.03 g/cm³ (8.595 lbs/gal) Not determined. Not determined. Not determined.	
· Solubility in / Miscibility with · Water:	Fully miscible.	
· Partition coefficient (n-octanol/wa	uter): Not determined.	
<ul> <li>Viscosity:</li> <li>Dynamic:</li> <li>Kinematic at 20 °C (68 °F):</li> <li>Oxidising properties:</li> </ul>	Not determined. 60 s (ISO 6 mm) N.A.	
· Solvent content:  · Water:  · VOC content:	57.9 % 3.04 % 31.4 g/l / 0.26 lb/gal	
· Solids content:	39.0 %	
Other information (HAPS)		
111-90-0 Diethylene glycol monoet		0.5-1%
112-34-5 2-(2-butoxyethoxy)ethand	ol	0.5-1%
121-44-8 triethylamine		<0.5%
110-80-5 2-ethoxyethanol		<0.01%

## 10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
- · Chemical stability The product is stable in normal conditions of storage and use recommended
  - · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

(Contd. on page 8)



Printing date 08/08/2022

Version number 1

Reviewed on 08/08/2022

**Product number HUM5AA34** 

SELF SEALER WB UV CLEAR 30 GL Trade name:

(Contd. of page 7)

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Acids, alkalis and oxidizing agents
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects

· Acute to	oxicity:				
· <i>LD</i> /.	· LD/LC50 values that are relevant for classification:				
ATE (Acu	ATE (Acute Toxicity Estimate)				
Oral	LD50	48,754 mg/kg			
Dermal	LD50	333,333 mg/kg (rabbit)			
Inhalative	LC50/4 h	6,264 mg/l (mouse)			
28961-43-	5 Trimeth	ylolpropane, ethoxylated, esters with acrylic acid			
Oral	LD50	2,001 mg/kg (mouse)			
Dermal	LD50	13,201 mg/kg (rabbit)			
7473-98-5	2-hydrox	y-2-methylpropiophenone			
Oral	LD50	1,694 mg/kg (mouse)			
Dermal	LD50	6,929 mg/kg (mouse)			
111-90-0	Diethylene	glycol monoethyl ether			
Oral	LD50	6,031 mg/kg (mouse)			
Dermal	LD50	9,143 mg/kg (rabbit)			
112-34-5	2-(2-butox	yethoxy)ethanol			
Oral	LD50	6,600 mg/kg (mouse)			
Dermal	LD50	2,764 mg/kg (rabbit)			
111-76-2	2-butoxye	thanol			
Oral	LD50	1,200 mg/kg (ATE)			
		1,480 mg/kg (mouse)			
Dermal	LD50	1,100 mg/kg (rab)			
Inhalative	LC50/4 h	11 mg/l (mouse)			
55818-57-		propylidenediphenol, oligomeric reaction products with 1-chloro-2,3-ropane, esters with acrylic acid			
Oral	LD50	2,001 mg/kg (mouse)			
Dermal	LD50	2,001 mg/kg (rabbit)			
121-44-8 1	triethylam	ine			
Oral	LD50	730 mg/kg (mouse)			
Dermal	LD50	580 mg/kg (rabbit)			
Inhalative	LC50/4 h	10.9 mg/l (mouse)			
34590-94-	8 (2-meth	oxymethylethoxy)propanol			
Oral	LD50	5,135 mg/kg (mouse)			
Dermal	LD50	19,020 mg/kg (rabbit)			
D .	Drimary irritant offect				

- · Primary irritant effect:
  - on the skin: No irritant effect.
  - · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.

(Contd. on page 9)



Printing date 08/08/2022 Version number 1 Reviewed on 08/08/2022

**Product number HUM5AA34** 

Trade name: SELF SEALER WB UV CLEAR 30 GL

(Contd. of page 8)

· Additional toxicological information:

Irritant

May cause an allergic skin reaction.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

3

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

· Aquatic t	oxicity:
28961-43-5	Trimethylolpropane, ethoxylated, esters with acrylic acid
EC50	70.7 mg/l (daphnia) 48H
LC50 (96h)	1.95 mg/l (Fish)
7473-98-5 2	-hydroxy-2-methylpropiophenone
EC50	119 mg/l (daphnia) (48h)
LC50 (96h)	160 mg/l (Fish)
111-90-0 Di	ethylene glycol monoethyl ether
LC50 48h	1,982 mg/l (daphnia)
LC50 (96h)	101 mg/l (Fish)
112-34-5 2-	(2-butoxyethoxy)ethanol
EC50	1,001 mg/l (daphnia) (48 h)
LC50 (96h)	1,300 mg/l (Leuciscus idus melanotus)
111-76-2 2-	butoxyethanol
EC50	101 mg/l (daphnia) (24 h)
LC50 (96h)	101 mg/l (Fish)
52408-84-1	Glycerol, propoxylated, esters with acrylic acid
EC50	12.2 mg/l (algae) (72 h)
	91.4 mg/l (daphnia) (48 h)
LC50 (96h)	5.74 mg/l (Fish)
55818-57-0	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,
	epoxypropane, esters with acrylic acid
EC50	105 mg/l (algae) (72h)
	101 mg/l (daphnia) (48h)
	101 mg/l (Fish)
121-44-8 tri	ethylamine
EC50	8 mg/l (algae) (72 h)
	17 mg/l (daphnia) (48 h)
LC50 (96h)	36 mg/l (Fish)



Version number 1 Printing date 08/08/2022 Reviewed on 08/08/2022

**Product number HUM5AA34** 

Trade name: SELF SEALER WB UV CLEAR 30 GL

	(Contd. of page 9)		
34590-94-8	34590-94-8 (2-methoxymethylethoxy)propanol		
EC50	970 mg/l (algae) (72 h)		
	1,919 mg/l (daphnia) (48 h)		
LC50 (96h)	1,001 mg/l (Fish)		
55965-84-9 a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2- methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)			
EC50	0.027 mg/l (algae) (72 h)		
	0.16 mg/l (daphnia) (48 h)		
LC50 (96h)	0.19 mg/l (Fish)		

· Persistence and degradability No further relevant information available.

	nces Easily biodegradable	
	Diethylene glycol monoethyl ether	
112-34-5	2-(2-butoxyethoxy)ethanol	

- Behavior in environmental systems:
  - · Bioaccumulative potential No further relevant information available.
  - · Mobility in soil No further relevant information available.
- Additional ecological information:
  - · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Other adverse effects No further relevant information available.

#### 13 Disposal considerations

- · Waste treatment methods
  - · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- · Uncleaned packagings:
  - · Recommendation: Disposal must be made according to official regulations.
  - · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number	
· DOT, ADN, IMDG, IATA	Not applicable
· Note	Check viscosity and flash point at section 9
UN proper shipping name	
· DOT, ADN, IMDG, IATA	Not applicable
Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA	
· Class	Not applicable

(Contd. on page 11)



Printing date 08/08/2022 Version number 1

Reviewed on 08/08/2022

Product number HUM5AA34

Trade name: SELF SEALER WB UV CLEAR 30 GL

		(Contd. of page 10
· Packing group · DOT, IMDG, IATA	Not applicable	
Environmental hazards:		
· Marine pollutant:	No	
· Special precautions for user	Not applicable.	
Transport in bulk according to Anne.	x II of	
MARPOL73/78 and the IBC Code	Not applicable.	
· UN "Model Regulation":	Not applicable	

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
  - · Various regulations

· SA	RA	
	Section 355 (extremely hazardous substances):	
None of t	he ingredients is listed.	
	Section 313 (Specific toxic chemical listings) :	
111-90-0	Diethylene glycol monoethyl ether	0.5-1%
112-34-5	2-(2-butoxyethoxy)ethanol	0.5-1%
111-76-2	2-butoxyethanol	<0.5%
121-44-8	triethylamine	<0.5%
110-80-5	2-ethoxyethanol	<0.01%
52-51-7	bronopol (INN)	<0.01%
· TS	CA (Toxic Substances Control Act):	
All compo	onents have the value ACTIVE.	
	Hazardous Air Pollutants	
121-44-8	triethylamine	
· Pro	position 65	
	Chemicals known to cause cancer:	
None of t	he ingredients is listed.	
	Chemicals known to cause reproductive toxicity for females:	
None of t	he ingredients is listed.	
	Chemicals known to cause reproductive toxicity for males:	
110-80-5	2-ethoxyethanol	<0.01%
	Chemicals known to cause developmental toxicity:	
110-80-5	2-ethoxyethanol	<0.01%
· Car	cinogenic categories	
	EPA (Environmental Protection Agency)	
	2-butoxyethanol N	L <0.5%
	TLV (Threshold Limit Value)	
	2-butoxyethanol	A3



Printing date 08/08/2022

Version number 1

Reviewed on 08/08/2022

**Product number HUM5AA34** 

SELF SEALER WB UV CLEAR 30 GL Trade name:

(Contd. of page 11)

121-44-8 triethylamine

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
  - · Date of preparation / last revision 08/08/2022 / -
  - · Abbreviations and acronvms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids - Category 2 Flammable Liquids 4: Flammable liquids - Category 4

Acute Toxicity - Oral 4: Acute toxicity - Category 4

Acute Toxicity - Dermal 2: Acute toxicity - Category 2

Acute Toxicity - Dermal 3: Acute toxicity - Category 3

Skin Corrosion 1A: Skin corrosion/irritation - Category 1A

Skin Corrosion 1B: Skin corrosion/irritation - Category 1B Skin Irrititation 2: Skin corrosion/irritation - Category 2

Eye Damage 1: Serious eye damage/eye irritation - Category 1

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Sensitization - Skin 1: Skin sensitisation - Category 1

Sensitization - Skin 1A: Skin sensitisation - Category 1A

Sensitization - Skin 1B: Skin sensitisation - Category 1B

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2 Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard - Category 3

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

Sources

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

\* \* Data compared to the previous version altered.