US



# Safety Data Sheet acc. to OSHA HCS

Printing date 11/12/2023

#### Version number 147

Reviewed on 11/10/2023

#### **1** Identification

- · Product identifier
  - · Product number TW710
  - · Trade name: CLEAR WB CONVERTER
    - · Application of the substance / the mixture For professional use

#### · Details of the supplier of the safety data sheet

- Manufacturer/Supplier: IVM Chemicals Srl Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
- Information department: Environmental Health and safety office hseoffice @ivmchemicals.com
- Emergency telephone number: ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

# 2 Hazard(s) identification

#### • Classification of the substance or mixture The product is not classified, according to the Globally Harmonized System (GHS).

#### · Label elements

- · GHS label elements Not applicable
  - · Hazard pictograms Not applicable
  - · Signal word Not applicable
  - · Hazard statements Not applicable

#### · Classification system:

· NFPA ratings (scale 0 - 4)

 $\begin{array}{c} Health = 0\\ Fire = 1\\ Reactivity = 0 \end{array}$ 

· HMIS-ratings (scale 0 - 4)

HEALTH $\bigcirc$ Health = 0FIRE1Fire = 1REACTIVITY $\bigcirc$ Reactivity = 0

#### 3 Composition/information on ingredients

#### · Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

	3 (2-methoxymethylethoxy)propanol	1-<5%
	Flammable Liquids 4, H227	
5131-66-8	3 3-butoxypropan-2-ol	1-2.49%
	Skin Irritation 2, H315; Eye Irritation 2A, H319 Flammable Liquids 4, H227	



# Safety Data Sheet acc. to OSHA HCS

Reviewed on 11/10/2023

Printing date 11/12/2023

Version number 147

Product number TW710 Trade name: CLEAR WB CONVERTER

112-34-5	2-(2-butoxyethoxy)ethanol	(Contd. of page 1 1-2.49%
112-34-3	Eye Irritation 2A, H319	1-2.4970
108-01-0	2-dimethylaminoethanol	<0.5%
	<ul> <li>Flammable Liquids 3, H226</li> <li>Acute Toxicity - Inhalation 3, H331</li> <li>Skin Corrosion 1B, H314</li> <li>Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312</li> </ul>	
68439-49-6	c16-18 alcohols ethoxylated	<0.5%
	Acute Toxicity - Oral 3, H301 Eye Damage 1, H318	
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)	≥0.00025-<0.0015%
	<ul> <li>Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 2, H310; Acute Toxicity - Inhalation 2, H330</li> <li>Skin Corrosion 1B, H314</li> </ul>	
	Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100)	
	Sensitization - Skin 1A, H317	

# 4 First-aid measures

#### · Description of first aid measures

· General information:

- No special measures required.
- personal protective equipment for first aid responders is recommended. (please see section 8) • After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eve contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

· Information for doctor:

- Most important symptoms and effects, both acute and delayed
  - For symptoms and effects caused by substances, refer to Section 11.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

# 5 Fire-fighting measures

- · Extinguishing media
  - · Suitable extinguishing agents:
  - CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
  - · For safety reasons unsuitable extinguishing agents:
  - Do not use a jet water stream as it may scatter and spread fire.
- Special hazards arising from the substance or mixture In case of fire, the following can be released: Nitrogen oxides (NOx) Carbon monoxide (CO)
- · Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

(Contd. on page 3)

(Contd. of page 2)



#### Printing date 11/12/2023

# Safety Data Sheet acc. to OSHA HCS

Version number 147

Reviewed on 11/10/2023

Product number TW710 Trade name: CLEAR WB CONVERTER

· Protective equipment: No special measures required.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Not required. · Environmental precautions: Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water. · Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to Section 13. Reference to other sections No dangerous substances are released. See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. Protective Action Criteria for Chemicals · PAC-1: 34590-94-8 (2-methoxymethylethoxy)propanol 150 ppm 112-34-5 2-(2-butoxyethoxy)ethanol 30 ppm 7631-86-9 silicon dioxide, chemically prepared 18 mg/m<sup>3</sup> 25322-69-4 Propane-1,2-diol, propoxylated 30 mg/m<sup>3</sup> 108-01-0 2-dimethylaminoethanol 3.7 ppm 68439-49-6 c16-18 alcohols ethoxylated 3.8 mg/m<sup>3</sup> 68439-49-6 c16-18 alcohols ethoxylated 3.8 mg/m<sup>3</sup> 124-68-5 2-amino-2-methylpropanol 17 mg/m<sup>3</sup> · PAC-2: 34590-94-8 (2-methoxymethylethoxy)propanol 1700\* ppm 112-34-5 2-(2-butoxyethoxy)ethanol 33 ppm 7631-86-9 silicon dioxide, chemically prepared 740 mg/m<sup>3</sup> 25322-69-4 Propane-1,2-diol, propoxylated 330 mg/m<sup>3</sup> 108-01-0 2-dimethylaminoethanol 40 ppm 68439-49-6 c16-18 alcohols ethoxylated 42 mg/m<sup>3</sup> 68439-49-6 c16-18 alcohols ethoxylated 42 mg/m<sup>3</sup> 124-68-5 2-amino-2-methylpropanol 190 mg/m<sup>3</sup> · PAC-3: 34590-94-8 (2-methoxymethylethoxy)propanol 9900\*\* ppm 112-34-5 2-(2-butoxyethoxy)ethanol 200 ppm 7631-86-9 silicon dioxide, chemically prepared 4,500 mg/m<sup>3</sup> 25322-69-4 Propane-1,2-diol, propoxylated 2,000 mg/m<sup>3</sup> 108-01-0 2-dimethylaminoethanol 72 ppm 68439-49-6 c16-18 alcohols ethoxylated 250 mg/m<sup>3</sup> 68439-49-6 c16-18 alcohols ethoxylated 250 mg/m<sup>3</sup> 124-68-5 2-amino-2-methylpropanol 570 mg/m<sup>3</sup>

(Contd. on page 4)



Version number 147

Reviewed on 11/10/2023

Product number TW710 Trade name: CLEAR WB CONVERTER

(Contd. of page 3)

#### 7 Handling and storage

· Handling:

Printing date 11/12/2023

- · Precautions for safe handling No special measures required.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
  - · Storage:
    - Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date , it means that the product must be used within 8 months.

- Take on temperature greater than 5 ° C
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.

• Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

#### 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

- · Control parameters
  - · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

#### 34590-94-8 (2-methoxymethylethoxy)propanol

- PEL Long-term value: 600 mg/m<sup>3</sup>, 100 ppm Skin
- REL Short-term value: 900 mg/m<sup>3</sup>, 150 ppm Long-term value: 600 mg/m<sup>3</sup>, 100 ppm Skin

TLV Long-term value: 50 ppm

#### 112-34-5 2-(2-butoxyethoxy)ethanol

- TLV Long-term value: 10\* ppm
  - \*Inhalable fraction and vapor

· Regulatory information

PEL: Guide to Occupational Exposure Values (OSHA PELs)

REL: Guide to Occupational Exposure Values (NIOSH RELs)

TLV: Guide to Occupational Exposure Values (TLV)

• Additional information: The lists that were valid during the creation were used as basis.

#### · Exposure controls

· Personal protective equipment:

• General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is



Printing date 11/12/2023

# Safety Data Sheet acc. to OSHA HCS

Version number 147

Reviewed on 11/10/2023

Product number TW710 Trade name: CLEAR WB CONVERTER

(Contd. of page 4)

a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. • Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

#### 9 Physical and chemical properties

• General Information • Color:	According to product specification
· Odor:	Characteristic
• Odor threshold:	Not determined.
· pH-value:	Mixture is non-polar/aprotic.
	Range: 7 - 9
· Change in condition	
• Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	100 °C (212 °F)
· Flammability (solid, gaseous):	Not applicable.
· Auto igniting:	225 °C (437 °F)
· Decomposition temperature:	Not determined.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
· Lower:	0.9 Vol %
· Upper:	14 Vol %
· Vapor pressure at 20 °C (68 °F):	1.3 hPa (1 mm Hg)
• Density (+/- 0,03) at 20 °C (68 °F):	1.041 g/cm³ (8.687 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Fully miscible.
· Partition coefficient (n-octanol/water	·): Not determined.
· Viscosity:	<b>N C C C</b>
· Dynamic:	Not determined.
• Kinematic at 20 °C (68 °F):	60 s (ISO 6 mm)
• Oxidising properties:	N.A.
· Solvent content:	
· Water:	58.5 %
· VOC content:	5.43 % 145.2 g/l / 1.21 lb/gal
· Solids content:	35.9 %



# Safety Data Sheet acc. to OSHA HCS

Reviewed on 11/10/2023

Printing date 11/12/2023

# Version number 147

Product number TW710 Trade name: CLEAR WB CONVERTER

(Contd. of page 5)

1-2.49%

· Other information (HAPS)

112-34-5 2-(2-butoxyethoxy)ethanol

# 10 Stability and reactivity

· Reactivity typical of the product as indicated in the data sheet

- **Chemical stability** The product is stable in normal conditions of storage and use recommended • Thermal decomposition / conditions to be avoided:
  - No decomposition if used and stored according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Acids, alkalis and oxidizing agents
- · Hazardous decomposition products: No dangerous decomposition products known.

# 11 Toxicological information

#### · Information on toxicological effects

· Acute toxicity:

Acuit	2	
		es that are relevant for classification:
ATE (Acu	te Toxicit	y Estimate)
Oral	LD50	64,249 mg/kg
Inhalative	LC50/4 h	2,125 mg/l (mouse)
34590-94-	8 (2-meth	oxymethylethoxy)propanol
Oral	LD50	5,135 mg/kg (mouse)
Dermal	LD50	9,510 mg/kg (rabbit)
5131-66-8	3-butoxy	propan-2-ol
Oral	LD50	3,300 mg/kg (mouse)
Dermal	LD50	8,001 mg/kg (mouse)
112-34-5	2-(2-butox	yethoxy)ethanol
Oral	LD50	6,600 mg/kg (mouse)
Dermal	LD50	2,764 mg/kg (rabbit)
108-01-0	2-dimethy	laminoethanol
Oral	LD50	1,183 mg/kg (mouse)
Dermal	LD50	1,219 mg/kg (rabbit)
Inhalative	LC50/4 h	6.1 mg/l (mouse)
55965-84-		re of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-
	-	2 H -isothiazol-3-one [EC No 220-239-6] (3:1)
Oral	LD50	64 mg/kg (mouse)
Dermal	LD50	87.12 mg/kg (mouse)
	nary irritan	
		No irritant effect. No irritating effect.
		No initialing effects. No sensitizing effects known.
Sen		(Contd. on page

US



Version number 147

Reviewed on 11/10/2023

Printing date 11/12/2023

#### Product number TW710 Trade name: CLEAR WB CONVERTER

(Contd. of page 6)

• Additional toxicological information:

(Conta. o

The product is not subject to classification according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

# **12 Ecological information**

· Toxicity

-	oxicity: (2-methoxymethylethoxy)propanol			
EC50	970 mg/l (algae) (72 h)			
	1,919 mg/l (daphnia) (48 h)			
LC50 (96h)	1,001 mg/l (Fish)			
5131-66-8 3	3-butoxypropan-2-ol			
EC50	1,001 mg/l (algae) (96 h)			
	1,001 mg/l (daphnia) (48 h)			
LC50 (96h)	1,000 mg/l (Fish)			
112-34-5 2-	(2-butoxyethoxy)ethanol			
EC50	1,001 mg/l (daphnia) (48 h)			
LC50 (96h)	1,300 mg/l (Leuciscus idus melanotus)			
108-01-0 2-	dimethylaminoethanol			
EC50	66.1 mg/l (algae) (72 h)			
	98.4 mg/l (daphnia) (48 h)			
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)			
EC50	0.027 mg/l (algae) (72 h)			
	0.16 mg/l (daphnia) (48 h)			
LC50 (96h)	0.19 mg/l (Fish)			
Persistence	e and degradability No further relevant information available.			
· Substanc	es Easily biodegradable			
34590-94-8	(2-methoxymethylethoxy)propanol .			
5131-66-8	3-butoxypropan-2-ol .			
0101 00 0	2-(2-butoxyethoxy)ethanol			

(Contd. on page 8)



# Printing date 11/12/2023

# Safety Data Sheet acc. to OSHA HCS

Version number 147

Reviewed on 11/10/2023

Product number TW710 Trade name: **CLEAR WB CONVERTER** 

· Other adverse effects No further relevant information available.

(Contd. of page 7)

# 13 Disposal considerations

#### · Waste treatment methods

· Recommendation:

Smaller quantities can be disposed of with household waste.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

#### · Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

· Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number	
· DOT, ADN, IMDG, IATA	Not applicable
· Note	Check viscosity and flash point at section 9
UN proper shipping name	
· DOT, ADN, IMDG, IATA	Not applicable
Transport hazard class(es)	
· DOT, ADR/RID, ADN, IMDG, IATA	
· Class	Not applicable
Packing group	
· DOT, IMDG, IATA	Not applicable
Environmental hazards:	
• Marine pollutant:	No
Special precautions for user	Not applicable.
Transport in bulk according to Annex I	ll of
MARPOL73/78 and the IBC Code	Not applicable.
UN "Model Regulation":	Not applicable

# 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

· Various regulations · SARA · Section 355 (extremely hazardous substances): None of the ingredients is listed. · Section 313 (Specific toxic chemical listings) : 112-34-5 2-(2-butoxyethoxy)ethanol 1-2.49% (Contd. on page 9) US



# Safety Data Sheet acc. to OSHA HCS

Reviewed on 11/10/2023

Printing date 11/12/2023

# Version number 147

Product number TW710 **CLEAR WB CONVERTER** Trade name:

(Contd. of page 8)

· TSCA (Toxic Substances Control Act): All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the inaredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone • Date of preparation / last revision 11/12/2023 · Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)
  - LC50: Lethal concentration, 50 percent
  - LD50: Lethal dose, 50 percent
  - NIOSH: National Institute for Occupational Safety
  - OSHA: Occupational Safety & Health
  - TLV: Threshold Limit Value
  - PEL: Permissible Exposure Limit REL: Recommended Exposure Limit
  - Flammable Liquids 3: Flammable liquids Category 3
  - Flammable Liquids 4: Flammable liquids Category 4
  - Acute Toxicity Oral 4: Acute toxicity Category 4
  - Acute Toxicity Dermal 2: Acute toxicity Category 2
  - Acute Toxicity Inhalation 3: Acute toxicity Category 3
  - Skin Corrosion 1B: Skin corrosion/irritation Category 1B
  - Skin Irritation 2: Skin corrosion/irritation Category 2 Eye Damage 1: Serious eye damage/eye irritation - Category 1

# Chemicals ners technolog

Printing date 11/12/2023

# Safety Data Sheet acc. to OSHA HCS

Version number 147

Reviewed on 11/10/2023

#### Product number TW710 **CLEAR WB CONVERTER** Trade name:

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Sensitization - Skin 1A: Skin sensitisation - Category 1A Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 · Sources REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments Agency ECHA web site INRS Fiche Toxicologique

IARC International agency for research on cancer

 $\cdot$  \* Data compared to the previous version altered.

(Contd. of page 9)

US