

Safety Data Sheet acc. to OSHA HCS

Printing date 08/01/2019

Version number 20

Reviewed on 08/01/2019

1 Identification

- · Product identifier
 - · Product number HMMB054
 - · Trade name: WB SATIN MULTILAYR FLOOR FINSH · Application of the substance / the mixture For professional use

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: IVM Chemicals srl Viale della Stazione 3 -27020 Parona (PV) Italy tel +39 038425441

1.3.2 Importer Name I.C.& S. DISTRIBUTING CO. Address P.O.BOX 10845 LANCASTER. PA USA E-Mail: nelson@ics-company.com

- · Information department: Environmental Health and safety office hseoffice@ivmchemicals.com
- · Emergency telephone number: ChemTel Expert Assistance Hotline/MSDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture The product is not classified, according to the Globally Harmonized System (GHS).

· Label elements

· GHS label elements Not applicable

- · Hazard pictograms Not applicable
- · Signal word Not applicable
- · Hazard statements Not applicable
- · Classification system:

· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)



Health = 0

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

· Dangerous components:				
34590-94-8	Dipropylene glycol monomethyl ether	Flam. Liq. 4, H227	1-<5%	
57-55-6	propane-1,2-diol		2.5-4.99%	
			ICS	

(Contd. on page 2)



Safety Data Sheet acc. to OSHA HCS

Version number 20

Reviewed on 08/01/2019

Printing date 08/01/2019

Product number HMMB054 Trade name: WB SATIN MULTILAYR FLOOR FINSH

(Contd. of page 1)

4 First-aid measures

· Description of first aid measures

- · General information:
- No special measures required.
- personal protective equipment for first aid responders is recommended. (please see section 8)
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
 - Most important symptoms and effects, both acute and delayed For symptoms and effects caused by substances, refer to Section 11. No further relevant information available.
 - Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment. • Special hazards arising from the substance or mixture
- Formation of toxic gases is possible during heating or in case of fire. No further relevant information available.
- · Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to Section 13.
- Reference to other sections
- See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:				
34590-94-8	Dipropylene glycol monomethyl ether	150 ppm		
57-55-6	propane-1,2-diol	30 mg/m ³		
7631-86-9	silicon dioxide, chemically prepared	18 mg/m³		
· PAC-2:				
34590-94-8	Dipropylene glycol monomethyl ether 1	700* ppm		
57-55-6	propane-1,2-diol 1	,300 mg/m³		
7631-86-9	silicon dioxide, chemically prepared 7	'40 mg/m³		
	(C	ontd. on page 3)		



Version number 20

Reviewed on 08/01/2019

Printing date 08/01/2019

Product number HMMB054

Trade name: WB SATIN MULTILAYR FLOOR FINSH

		(Contd. of page 2)
· PAC-3:		
34590-94-8	Dipropylene glycol monomethyl ether	9900** ppm
57-55-6	propane-1,2-diol	7,900 mg/m³
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m³

7 Handling and storage

· Handling:

- · Precautions for safe handling No special measures required.
- · Information about protection against explosions and fires: No special measures required.

· Conditions for safe storage, including any incompatibilities

- · Storage:
- Requirements to be met by storerooms and receptacles:
 - Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.
 - In cases where there is no reported expiration date , it means that the product must be used within 8 months.
 - Take on temperature greater than 5 $^\circ$ C
 - · Information about storage in one common storage facility: Not required.
 - · Further information about storage conditions: None.

• Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

Components with limit values that require monitoring at the workplace:
 34590-94-8 Dipropylene glycol monomethyl ether
 PEL (USA) Long-term value: 600 mg/m³, 100 ppm
 Skin
 REL (USA) Short-term value: 900 mg/m³, 150 ppm
 Long-term value: 600 mg/m³, 100 ppm
 Skin
 TLV (USA) Short-term value: 909 mg/m³, 150 ppm
 Long-term value: 606 mg/m³, 100 ppm
 Skin
 57-55-6 propane-1,2-diol
 WEEL (USA) Long-term value: 10 mg/m³

WEEL (USA) Long-term value: 10 mg/m³

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

- General protective and hygienic measures:
- The usual precautionary measures for handling chemicals should be followed.
- · Breathing equipment: Not required.
- · Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

(Contd. on page 4)

ics



Version number 20

Reviewed on 08/01/2019

ngs & polymers technologies

Printing date 08/01/2019

Product number HMMB054 Trade name: WB SATIN MULTILAYR FLOOR FINSH

(Contd. of page 3)

	(Contd. of page 3)	
 Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective sloves and has the observed. 		
gloves and has to be observ • Eye protection: Goggles recomm		
Lyc protection. Coggico roconni		
9 Physical and chemical proper	ties	
• Information on basic physical and o • General Information	chemical properties	
· Appearance:		
· Form: · Color:	Fluid According to product specification	
· Color: · Odor:	Characteristic	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
 Melting point/Melting range: 	Undetermined.	
· Boiling point/Boiling range:	100 °C (212 °F)	
· Flash point:	Not applicable.	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	270 °C (518 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
· Lower:	1.1 Vol %	
· Upper:	14 Vol %	
• Vapor pressure at 20 $\bullet C$ (68 $\bullet F$):	0.4 hPa (0.3 mm Hg)	
• Density (+/- 0,03) at 20 •C (68 •F):	1.031 g/cm ³ (8.604 lbs/gal)	
· Relative density	Not determined. Not determined.	
• Vapor density • Evaporation rate	Not determined.	
-		
• Solubility in / Miscibility with • Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water): Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
• <i>Kinematic at 20 •C (68 •F):</i>	40 s (ISO 4 mm)	
• Oxidising properties:	N.A.	

(Contd. on page 5)

ICS



Version number 20

Reviewed on 08/01/2019

Printing date 08/01/2019

Product number	HIMIMBU34
Trade name:	WB SATIN MULTILAYR FLOOR FINSH

		(Contd. of page 4)
· Solvent content:		
· Water:	61.8 %	
· VOC content:	9.01 %	
	92.9 g/l / 0.78 lb/gal	
· Solids content:	29.2 %	
· Other information (HAPS)	No further relevant information available.	
None of the ingredients is listed.		
· Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity typical of the product as indicated in the data sheet

- Chemical stability The product is stable in normal conditions of storage and use recommended • Thermal decomposition / conditions to be avoided:
- No decomposition if used and stored according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

Acute toxicity:

· LD/LC50 values that are relevant for classification:

34590-94-	34590-94-8 Dipropylene glycol monomethyl ether		
Oral	LD50	5,135 mg/kg (mouse)	
Dermal	LD50	19,020 mg/kg (rabbit)	
57-55-6 p	57-55-6 propane-1,2-diol		
Oral	LD50	20,000 mg/kg (mouse)	
Dermal	LD50	2,001 mg/kg (mouse)	
108-01-0	108-01-0 2-dimethylaminoethanol		
Oral	LD50	1,183 mg/kg (mouse)	
Dermal	LD50	1,219 mg/kg (rabbit)	
Inhalative	LC50/4 h	6.1 mg/l (mouse)	

• Primary irritant effect:

• on the skin: No irritant effect.

• on the eye: No irritating effect.

· Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product is not subject to classification according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

Safety data sheet available on request.

(Contd. on page 6)



Safety Data Sheet acc. to OSHA HCS

Printing date 08/01/2019

Version number 20

Reviewed on 08/01/2019

Product number HMMB054 Trade name: WB SATIN MULTILAYR FLOOR FINSH

(Contd. of page 5)

· Carcinogenic categories

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecol	onica	linform	ation
12 LCUI	Uyica		auon

· Toxicity					
· Aquatic t	· Aquatic toxicity:				
34590-94-8	Dipropylene glycol monomethyl eth	ner			
EC50	970 mg/l (algae) (72 h)				
	1,919 mg/l (daphnia) (48 h)				
LC50 (96h)	1,001 mg/l (Fish)				
57-55-6 pro	pane-1,2-diol				
EC50	19,000 mg/l (algae) (48 h)				
	18,340 mg/l (daphnia) (48 h)				
LC50 (96h)	40,613 mg/l (Fish)				
108-01-0 2-	dimethylaminoethanol				
EC50	66.1 mg/l (algae) (72 h)				
	98.4 mg/l (daphnia) (48 h)				
· Persistence	e and degradability No further relevar	nt information available.			
· Substanc	es Easily biodegradable				
34590-94-8	Dipropylene glycol monomethyl ether				
57-55-6	propane-1,2-diol				
• Bioaccun • Mobility • Additional • General n Water ha Do not a sewage	azard class 1 (Self-assessment): slightl illow undiluted product or large quanti	vailable. y hazardous for water ties of it to reach ground water, water course or			

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

(Contd. on page 7)

ICS



Safety Data Sheet acc. to OSHA HCS

Version number 20

Reviewed on 08/01/2019

Product number HMMB054

Printing date 08/01/2019

Trade name: WB SATIN MULTILAYR FLOOR FINSH

(Contd. of page 6)

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

UN-Number		
· DOT, ADN, IMDG, IATA	Not applicable	
UN proper shipping name		
· DOT, ADN, IMDG, IATA	Not applicable	
Transport hazard class(es)		
· DOT, ADR, ADN, IMDG, IATA		
· Class	Not applicable	
Packing group		
· DOT, IMDG, IATA	Not applicable	
Environmental hazards:		
· Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Anne	x II of	
MARPOL73/78 and the IBC Code	Not applicable.	
UN "Model Regulation":	Not applicable	

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

· SARA

5/11/1		
· Sect	ion 355 (extremely hazardous substances):	
None of th	e ingredients is listed.	
· Sect	ion 313 (Specific toxic chemical listings) :	
111-76-2	2-butoxyethanol	<0.1%
1344-28-1	aluminium oxide	<0.1%
· TSCA (Toxic Substances Control Act):	
All compoi	nents have the value ACTIVE.	
· Haza	ardous Air Pollutants	
None of th	e ingredients is listed.	
· Proposi	tion 65	
· Che	micals known to cause cancer:	
None of th	e ingredients is listed.	
· Che	micals known to cause reproductive toxicity for females:	
None of th	e ingredients is listed.	
· Che	micals known to cause reproductive toxicity for males:	
None of th	e ingredients is listed.	
		(Contd. on page 8)
		ICS

ivm Chemicals

Safety Data Sheet acc. to OSHA HCS

Printing date 08/01/2019

Version number 20

Reviewed on 08/01/2019

(Contd. of page 7)

NL <0.1%

A4 A3

A4

Product number HMMB054

Trade name: WB SATIN MULTILAYR FLOOR FINSH

• Chemicals known to cause developmental toxicity: None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

111-76-2 2-butoxyethanol

• TLV (Threshold Limit Value established by ACGIH) 112945-52-5 silicon dioxide

111-76-2 2-butoxyethanol

1344-28-1 aluminium oxide

·NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: IVM Chemicals Srl

· Contact: See emergency phone

Date of preparation / last revision 08/01/2019 / 19
 Abbreviations and acronyms:
 IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flam. Liq. 4: Flammable liquids - Category 4 Sources REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site INRS Fiche Toxicologique IARC International agency for research on cancer

ICS