ILVA TECHNICAL DATA SHEET

PRODUCT SERIES: KLIMA SERIES

PRODUCT CODE: TN090

DESCRIPTION: Klima Honeytone Maintenance by Brush

USES: Used as a field maintenance product for wood tone finishes

APPLICATION SYSTEM: When doing a complete restoration, remove the damaged coating using 150-180 grit sand

paper. Further prepare the wooden surface by sanding down with 240 grit paper to bare wood. Using a brush, apply the desired color impregnator and let dry for at least 4 hours. Next, apply

2 layers of TN090 Maintenance Coat by brush.

FILM THICKNESS: 3.2-4 mils wet

COATS: One

GENERALSpecific Gravity, gr/cc1.038+/-.03PROPERTIES:Viscosity as supplied (Ford 4 cup)83 +/-5Solids, % by weight:40.5 +/-2

Thinner: Water % of dilution: 0-5%

DRYING TIME: At 20°C with ventilation, dry to handle:

(at 20°C/68°F) Dust Free: 20 minutes

Dry to touch: 4 hours
Full dried: 72 hours

(Drying times may vary according to temperature, ventialtion and relative humidity)

WARNINGS: KEEP FROM FREEZING

SHELF LIFE: 12 months

STORAGE: Store in a tightly closed container at room temperatures (18 -25 °C/64 -75 °F) and protect

from moisture and foreign material. Do not store at temperatures below 7°C (45°F

DATE OF ISSUANCE: 2-18