

1 Identification

- **Product identifier**
 - *Product number* PZ60
 - *Trade name:* **POLYESTER PASTE WHITE**
 - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
 - *Manufacturer/Supplier:*
IVM Chemicals Srl
Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
 - *Information department:*
Environmental Health and safety office
hseoffice@ivmchemicals.com
 -
 - *Emergency telephone number:*
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**

Flammable Liquids 2	H225 Highly flammable liquid and vapor.
Sensitization - Skin 1	H317 May cause an allergic skin reaction.
Carcinogenicity 2	H351 Suspected of causing cancer.
Toxic to Reproduction 2	H361 Suspected of damaging fertility or the unborn child.
Specific Target Organ Toxicity - Repeated Exposure 2	H373 May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral and Inhalation.

· Label elements

- *GHS label elements*
The product is classified and labeled according to the Globally Harmonized System (GHS).
- *Hazard pictograms*



GHS02 GHS07 GHS08

- *Signal word* Danger
- *Hazard-determining components of labeling:*
toluene
xylene
maleic anhydride
Fatty acids, C14-18 and C16-18-unsatd., maleated
- *Hazard statements*
H225 Highly flammable liquid and vapor.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral and Inhalation.
- *Precautionary statements*
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.

(Contd. on page 2)

Product number PZ60**Trade name: POLYESTER PASTE WHITE**

(Contd. of page 1)

P260 Do not breathe dust/fume/gas/mist/vapors/spray.
 P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

· NFPA ratings (scale 0 - 4)



Health = 0
 Fire = 3
 Reactivity = 0

· HMIS-ratings (scale 0 - 4)











HEALTH | 0 Health = 0
 FIRE | 3 Fire = 3
 REACTIVITY | 0 Reactivity = 0

3 Composition/information on ingredients

Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

· Dangerous components:

1330-20-7	xylene  Flammable Liquids 3, H226  Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304  Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irritation 2, H315; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H335 Aquatic Acute 3, H402; Aquatic Chronic 3, H412	5-9.99%
57-55-6	propane-1,2-diol	5-9.99%
108-88-3	toluene  Flammable Liquids 2, H225  Toxic to Reproduction 2, H361; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304  Skin Irritation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H336 Aquatic Chronic 3, H412	1-2.49%
77-99-6	propylidynetrimethanol  Toxic to Reproduction 2, H361	0.5-1%
	Fatty acids, C14-18 and C16-18-unsatd., maleated  Skin Irritation 2, H315; Sensitization - Skin 1, H317	≥0.1-<0.5%

(Contd. on page 3)

Product number PZ60
Trade name: POLYESTER PASTE WHITE

		(Contd. of page 2)
78-93-3	butanone ⚠ Flammable Liquids 2, H225 ⚠ Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	<0.5%
100-41-4	ethylbenzene ⚠ Flammable Liquids 2, H225 ⚠ Carcinogenicity 2, H351; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304 ⚠ Acute Toxicity - Inhalation 4, H332 Aquatic Chronic 3, H412	≥0.1-<0.5%
108-31-6	maleic anhydride ⚠ Sensitization - Respiratory 1, H334 ⚠ Skin Corrosion 1B, H314 ⚠ Acute Toxicity - Oral 4, H302; Sensitization - Skin 1, H317	≥0.001-<0.1%

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact: Rinse opened eye for several minutes under running water.

· After swallowing: Do not induce vomiting; immediately call for medical help.

· Information for doctor:

· Most important symptoms and effects, both acute and delayed

Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

Alcohol resistant foam

Alcohol resistant foam, CO, powder, water spray/mist.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

In case of fire, the following can be released:

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

(Contd. on page 4)

Product number PZ60**Trade name: POLYESTER PASTE WHITE**

(Contd. of page 3)

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

· Environmental precautions: Do not allow to enter sewers/ surface or ground water.**· Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals**· PAC-1:**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	30 mg/m
1330-20-7	xylene	130 ppm
57-55-6	propane-1,2-diol	30 mg/m
108-88-3	toluene	67 ppm
78-93-3	butanone	200 ppm
100-41-4	ethylbenzene	33 ppm

· PAC-2:

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	330 mg/m
1330-20-7	xylene	920* ppm
57-55-6	propane-1,2-diol	1,300 mg/m
108-88-3	toluene	560 ppm
78-93-3	butanone	2700* ppm
100-41-4	ethylbenzene	1100* ppm

· PAC-3:

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2,000 mg/m
1330-20-7	xylene	2500* ppm
57-55-6	propane-1,2-diol	7,900 mg/m
108-88-3	toluene	3700* ppm
78-93-3	butanone	4000* ppm
100-41-4	ethylbenzene	1800* ppm

7 Handling and storage

· Handling:**· Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 5)

Product number PZ60**Trade name: POLYESTER PASTE WHITE**

(Contd. of page 4)

- Open and handle receptacle with care.
- Prevent formation of aerosols.
- Protect against electrostatic charges.
- Keep respiratory protective device available.
- Use explosion-proof apparatus / fittings and spark-proof tools.
- **Information about protection against explosions and fires:**
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
 - Keep respiratory protective device available.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

- Store in a cool, well-ventilated area, away from heat and sources of ignition

- Provide solvent resistant, sealed floor.

- Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

- In cases where there is no reported expiration date, it means that the product must be used within 8 months.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:**

- Keep receptacle tightly sealed.

- Store in cool, dry conditions in well sealed receptacles.

- **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

1330-20-7 xylene

PEL Long-term value: 435 mg/m , 100 ppm

REL Short-term value: 655 mg/m , 150 ppm

Long-term value: 435 mg/m , 100 ppm

TLV Short-term value: (150) ppm

Long-term value: (100) NIC-20 ppm

BEI, A4

57-55-6 propane-1,2-diol

WEEL Long-term value: 10 mg/m

108-88-3 toluene

PEL Long-term value: 200 ppm

Ceiling limit value: 300; 500* ppm

*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m , 150 ppm

Long-term value: 375 mg/m , 100 ppm

TLV Long-term value: 20 ppm

BEI, OTO, A4

(Contd. on page 6)

Product number PZ60**Trade name: POLYESTER PASTE WHITE**

(Contd. of page 5)

78-93-3 butanone

PEL	Long-term value: 590 mg/m , 200 ppm
REL	Short-term value: 885 mg/m , 300 ppm Long-term value: 590 mg/m , 200 ppm
TLV	Short-term value: 300 ppm Long-term value: 200 ppm BEI

100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m , 100 ppm
REL	Short-term value: 545 mg/m , 125 ppm Long-term value: 435 mg/m , 100 ppm
TLV	Long-term value: 20 NIC-20 ppm BEI, A3, NIC: OTO, BEI, A3

108-31-6 maleic anhydride

PEL	Long-term value: 1 mg/m , 0.25 ppm
REL	Long-term value: 1 mg/m , 0.25 ppm
TLV	Long-term value: 0.01* mg/m DSEN, RSEN; *inh. fraction + vapor, A4

· Ingredients with biological limit values:**1330-20-7 xylene**

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

108-88-3 toluene

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

78-93-3 butanone

BEI	2 mg/L Medium: urine Time: end of shift Parameter: Methyl ethyl ketone (nonspecific)
-----	---

100-41-4 ethylbenzene

BEI	0.15 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)
-----	---

(Contd. on page 7)

Product number PZ60

Trade name: POLYESTER PASTE WHITE

(Contd. of page 6)

· *Additional information:* The lists that were valid during the creation were used as basis.

· **Exposure controls**

· *Personal protective equipment:*

· *General protective and hygienic measures:*

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Pregnant women should strictly avoid inhalation or skin contact.

· *Breathing equipment:*

Short term filter device:



Suitable respiratory protective device recommended.

Filter A

· *Protection of hands:*



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· *Penetration time of glove material*

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· *Eye protection:*



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· *General Information*

· *Appearance:*

- *Form:* Fluid
- *Color:* According to product specification
- *Odor:* Characteristic
- *Odor threshold:* Not determined.

· *pH-value:* Mixture is non-polar/aprotic.

· *Change in condition*

· *Melting point/Melting range:* Undetermined.

(Contd. on page 8)

Product number PZ60
Trade name: POLYESTER PASTE WHITE

(Contd. of page 7)

· Boiling point/Boiling range:	110-111 °C (230-231.8 °F)	
· Flash point:	4 °C (39.2 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	>370 °C (>698 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.	
· Explosion limits:		
· Lower:	1.1 Vol %	
· Upper:	12.6 Vol %	
· Vapor pressure at 20 °C (68 °F):	29 hPa (21.8 mm Hg)	
· Density (+/- 0,03) at 20 °C (68 °F):	1.881 g/cm (15.697 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water):	Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
· Kinematic at 20 °C (68 °F):	40 s (ISO 4 mm)	
· Oxidising properties:	N.A.	
· Solvent content:		
· VOC content:	12.39 % 233.1 g/l / 1.95 lb/gal	
· Solids content:	87.1 %	
· Other information (HAPS)		
1330-20-7	xylene	5-9.99%
108-88-3	toluene	1-2.49%
100-41-4	ethylbenzene	≥0.1-<0.5%
108-31-6	maleic anhydride	≥0.001-<0.1%
· Other information	No further relevant information available.	

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents

(Contd. on page 9)

US

Product number PZ60
Trade name: POLYESTER PASTE WHITE

(Contd. of page 8)

· **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Dermal	LD50	21,825 mg/kg
Inhalative	LC50/4 h	218 mg/l (mouse)

1330-20-7 xylene

Oral	LD50.	3,523 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rabbit) (ATE value)
	LD50.	12,126 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (mouse) (ATE value)
	LC50/4h.	27.571 mg/l (mouse)

57-55-6 propane-1,2-diol

Oral	LD50	20,000 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (mouse)

108-88-3 toluene

Oral	LD50	5,000 mg/kg (mouse)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	25.7 mg/l (mouse)

77-99-6 propylidynetrimethanol

Oral	LD50	14,700 mg/kg (mouse)
Dermal	LD50	10,001 mg/kg (mouse)

Fatty acids, C14-18 and C16-18-unsatd., maleated

Oral	LD50	2,001 mg/kg (mouse)
------	------	---------------------

78-93-3 butanone

Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 h	21 mg/l (mouse)

100-41-4 ethylbenzene

Oral	LD50	3,500 mg/kg (mouse)
Dermal	LD50	15,486 mg/kg (rabbit)
Inhalative	LC50/4 h	17.2 mg/l (mouse)

108-31-6 maleic anhydride

Oral	LD50	1,090 mg/kg (mouse)
Dermal	LD50	2,620 mg/kg (rabbit)

· Primary irritant effect:

· on the skin: No irritant effect.

· on the eye: No irritating effect.

· Sensitization: Sensitization possible through skin contact.

· Additional toxicological information:

Irritant

May cause an allergic skin reaction.

Suspected of causing cancer.

(Contd. on page 10)

Product number PZ60**Trade name: POLYESTER PASTE WHITE**

(Contd. of page 9)

Suspected of damaging fertility or the unborn child.

May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral and Inhalation.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

· **Carcinogenic categories**

Titanium dioxide

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

Ethylbenzene

From IARC MONOGRAPHS VOLUME 77/2000

Human carcinogenicity data

Two studies of workers potentially exposed to ethylbenzene in a production plant and a styrene polymerization plant were available. In the first study, no excess of cancer incidence was found but the description of methods was insufficient to allow proper evaluation of this finding. In the second study, no cancer mortality excess was observed during the follow-up of 15 years.

Evaluation

There is inadequate evidence in humans for the carcinogenicity of ethylbenzene. There is sufficient evidence in experimental animals for the carcinogenicity of ethylbenzene.

· **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2B - DUST
100-41-4	ethylbenzene	2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

1330-20-7 xylene

EC50 2.2 mg/l (algae)

LC50 48h 1 mg/l (daphnia)

LC50 (96h) 2.6 mg/l (Fish)

57-55-6 propane-1,2-diol

EC50 19,000 mg/l (algae) (48 h)

18,340 mg/l (daphnia) (48 h)

LC50 (96h) 40,613 mg/l (Fish)

108-88-3 toluene

EC50 134 mg/l (algae) (96 h)

3.78 mg/l (daphnia) (48 h)

LC50 (96h) 5.5 mg/l (Fish)

(Contd. on page 11)

Product number PZ60**Trade name: POLYESTER PASTE WHITE**

(Contd. of page 10)

77-99-6 propylidynetrimehanol

EC50	1,001 mg/l (algae) (72h)
	13,000 mg/l (daphnia) (48h)
LC50 (96h)	1,001 mg/l (Fish)

Fatty acids, C14-18 and C16-18-unsatd., maleated

EC50	101 mg/l (algae) (72 h)
	101 mg/l (daphnia) (48 h)
LC50 48h	151 mg/l (Fish)

78-93-3 butanone

EC50	2,029 mg/l (algae) (96 h)
	308 mg/l (daphnia) (48 h)
LC50 (96h)	2,993 mg/l (Fish)

100-41-4 ethylbenzene

EC50	438 mg/l (algae) (72h)
	1.8 mg/l (daphnia) (48 h)
LC50 (96h)	12.1 mg/l (Fish)

108-31-6 maleic anhydride

EC50	29 mg/l (algae) (72 h)
	42.8 mg/l (daphnia) (48 h)
LC50 (96h)	75 mg/l (Fish)

- **Persistence and degradability** No further relevant information available.

- **Substances Easily biodegradable**

1330-20-7	xylene	.
57-55-6	propane-1,2-diol	.
108-88-3	toluene	.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

(Contd. on page 12)

Product number PZ60
Trade name: POLYESTER PASTE WHITE

(Contd. of page 11)

- **Uncleaned packagings:**
- *Recommendation: Disposal must be made according to official regulations.*

14 Transport information

- **UN-Number**
- *DOT, IMDG, IATA* UN1263
- *Note* Check viscosity and flash point at section 9

- **UN proper shipping name**
- *DOT* Paint
- *IMDG, IATA* PAINT

- **Transport hazard class(es)**
- *DOT*
- 
- *Class* 3 Flammable liquids
- *Label* 3
- *Class* 3 Flammable liquids
- *Label* 3

- *IMDG, IATA*
- 
- *Class* 3 Flammable liquids
- *Label* 3

- **Packing group**
- *DOT, IMDG, IATA* II

- **Environmental hazards:**
- *Marine pollutant:* No

- **Special precautions for user** Warning: Flammable liquids
- *Hazard identification number (Kemler code):* 33
- *EMS Number:* F-E, S-E
- *Stowage Category* B

- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

- **Transport/Additional information:**

- *IMDG*
- *Limited quantities (LQ)* 5L
- *Excepted quantities (EQ)* Code: E2
- Maximum net quantity per inner packaging: 30 ml
- Maximum net quantity per outer packaging: 500 ml

(Contd. on page 13)

Product number PZ60
Trade name: POLYESTER PASTE WHITE

(Contd. of page 12)

· **UN "Model Regulation": UN 1263 PAINT, 3, II**

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

Requirements of Federal Register

- Various regulations
- SARA

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings) :**

1330-20-7	xylene	5-9.99%
108-88-3	toluene	1-2.49%
100-41-4	ethylbenzene	≥0.1-<0.5%
108-31-6	maleic anhydride	≥0.001-<0.1%

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

1330-20-7	xylene	
108-88-3	toluene	
100-41-4	ethylbenzene	
108-31-6	maleic anhydride	

· **Proposition 65**

· **Chemicals known to cause cancer:**

Titanium dioxide only in bound form

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	only for Dust	50-74.99%
100-41-4	ethylbenzene	*	≥0.1-<0.5%

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene	1-2.49%
----------	---------	---------

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I	5-9.99%
108-88-3	toluene	II	1-2.49%
78-93-3	butanone	I	<0.5%
100-41-4	ethylbenzene	D	≥0.1-<0.5%

· **TLV (Threshold Limit Value)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	A4
1330-20-7	xylene	A4

(Contd. on page 14)

Product number PZ60**Trade name: POLYESTER PASTE WHITE**

(Contd. of page 13)

108-88-3	toluene	A4
100-41-4	ethylbenzene	A3
108-31-6	maleic anhydride	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	50-74.99%
------------	---	-----------

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl

- **Contact:** See emergency phone

· **Date of preparation / last revision** 09/07/2022 / 79

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids . Category 2

Flammable Liquids 3: Flammable liquids . Category 3

Acute Toxicity - Dermal 4: Acute toxicity . Category 4

Skin Corrosion 1B: Skin corrosion/irritation . Category 1B

Skin Irritation 2: Skin corrosion/irritation . Category 2

Eye Irritation 2A: Serious eye damage/eye irritation . Category 2A

Sensitization - Respiratory 1: Respiratory sensitisation . Category 1

Sensitization - Skin 1: Skin sensitisation . Category 1

Carcinogenicity 2: Carcinogenicity . Category 2

Toxic to Reproduction 2: Reproductive toxicity . Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) . Category 3

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) . Category 2

Aspiration Hazard 1: Aspiration hazard . Category 1

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard . Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3

· **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

- *** Data compared to the previous version altered.**