

Printing date 09/14/2022

Version number 57

Reviewed on 09/09/2022

1 Identification

- · Product identifier
 - · Product number TW344
 - · Trade name: WB CLEAR 2K TOP-COAT 20 SH
 - · Application of the substance / the mixture For professional use
- · Details of the supplier of the safety data sheet
 - · Manufacturer/Supplier:

IVM Chemicals Srl

Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture

The product is not classified, according to the Globally Harmonized System (GHS).

- · Label elements
 - · GHS label elements Not applicable
 - · Hazard pictograms Not applicable
 - · Signal word Not applicable
 - · Hazard statements Not applicable
- · Classification system:
 - · NFPA ratings (scale 0 4)



Health = 0

Fire = 1

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0

Fire = 1

Reactivity = 0

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

· Dangerou	us components:	
34590-94-8	(2-methoxymethylethoxy)propanol	1-<5%
	Flammable Liquids 4, H227	
111-76-2	2-butoxyethanol	1-2.49%
	Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irrititation 2, H315; Eye Irritation 2A, H319 Flammable Liquids 4, H227	
57-55-6	propane-1,2-diol	0.5-1%
68439-49-6	c16-18 alcohols ethoxylated	<0.5%
	Acute Toxicity - Oral 3, H301 Eye Damage 1, H318	

(Contd. on page 2)



Printing date 09/14/2022 Version number 57 Reviewed on 09/09/2022

Product number TW344

WB CLEAR 2K TOP-COAT 20 SH Trade name:

(Contd. of page 1)

55965-84-9 a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No ≥0.00025-<0.0015% 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)

- Acute Toxicity Oral 3. H301: Acute Toxicity Dermal 2. H310; Acute Toxicity - Inhalation 2, H330
- A Skin Corrosion 1B, H314; Eye Damage 1, H318
- 🛦 Aguatic Acute 1, H400 (M=100); Aguatic Chronic 1, H410 (M=100)
- 🕦 Sensitization Skin 1A, H317

4 First-aid measures

- · Description of first aid measures
 - · General information:

No special measures required.

personal protective equipment for first aid responders is recommended. (please see section 8)

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eve contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
 - · Most important symptoms and effects, both acute and delayed For symptoms and effects caused by substances, refer to Section 11.
 - · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
 - · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 3)



Printing date 09/14/2022

Version number 57

Reviewed on 09/09/2022

Product number TW344

Trade name: WB CLEAR 2K TOP-COAT 20 SH

(Contd. of page 2)

Dispose contaminated material as waste according to Section 13.

· Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

34590-94-8	8 (2-methoxymethylethoxy)propanol		
	2-butoxyethanol	150 ppm 60 ppm	
	silicon dioxide, chemically prepared	18 mg/m³	
	2,2,4-Trimethyl-1,3-pentanediolmono(2-methylpropanoate)	13 mg/m³	
	propane-1,2-diol	30 mg/m³	
68439-49-6	c16-18 alcohols ethoxylated	3.8 mg/m ³	
108-01-0	2-dimethylaminoethanol	3.7 ppm	
68439-49-6	c16-18 alcohols ethoxylated	3.8 mg/m³	
· PAC-2:			
34590-94-8	(2-methoxymethylethoxy)propanol	1700* ppm	
111-76-2	2-butoxyethanol	120 ppm	
7631-86-9	silicon dioxide, chemically prepared	740 mg/m³	
25265-77-4	2,2,4-Trimethyl-1,3-pentanediolmono(2-methylpropanoate)	140 mg/m³	
57-55-6	propane-1,2-diol	1,300 mg/m³	
68439-49-6	c16-18 alcohols ethoxylated	42 mg/m³	
108-01-0	2-dimethylaminoethanol	40 ppm	
68439-49-6	6 c16-18 alcohols ethoxylated 42 mg/		
· PAC-3:		•	
34590-94-8	(2-methoxymethylethoxy)propanol	9900** ppm	
111-76-2	2-butoxyethanol	700 ppm	
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m³	
25265-77-4	2,2,4-Trimethyl-1,3-pentanediolmono(2-methylpropanoate)	840 mg/m³	
57-55-6	propane-1,2-diol	7,900 mg/m ³	
68439-49-6	c16-18 alcohols ethoxylated	250 mg/m³	
108-01-0	2-dimethylaminoethanol 72		
68439-49-6	c16-18 alcohols ethoxylated	250 mg/m³	

7 Handling and storage

- · Handling:
 - · Precautions for safe handling No special measures required.
 - · Information about protection against explosions and fires: No special measures required.

· Conditions for safe storage, including any incompatibilities

- · Storage:
 - Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

(Contd. on page 4)



Printing date 09/14/2022 Version number 57 Reviewed on 09/09/2022

Product number TW344

Trade name: WB CLEAR 2K TOP-COAT 20 SH

(Contd. of page 3)

Take on temperature greater than 5 ° C

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At	this time, the other constituents have no known exposure limits.
3459	0-94-8 (2-methoxymethylethoxy)propanol
PEL	Long-term value: 600 mg/m³, 100 ppm Skin
REL	Short-term value: 900 mg/m³, 150 ppm Long-term value: 600 mg/m³, 100 ppm Skin
TLV	Long-term value: NIC-50 ppm (Skin)
111-7	76-2 2-butoxyethanol
PEL	Long-term value: 240 mg/m³, 50 ppm Skin
REL	Long-term value: 24 mg/m³, 5 ppm Skin
TLV	Long-term value: 20 ppm BEI, A3
57-55	-6 propane-1,2-diol
WEE	L Long-term value: 10 mg/m³
	· Ingredients with biological limit values:
111-7	'6-2 2-butoxyethanol
	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
 - General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)



Printing date 09/14/2022 Version number 57 Reviewed on 09/09/2022

Product number TW344

Trade name: WB CLEAR 2K TOP-COAT 20 SH

(Contd. of page 4)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

nformation on basic physical and o	chemical properties
· General Information	
· Appearance:	
· Form:	Fluid
· Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Mixture is non-polar/aprotic.
	Range: 7 - 9
· Change in condition	
· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	100 °C (212 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	240 °C (464 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
· Lower:	1.1 Vol %
· Upper:	14 Vol %
· Vapor pressure at 20 °C (68 °F):	1.2 hPa (0.9 mm Hg)
· Density (+/- 0,03) at 20 °C (68 °F):	1.029 g/cm³ (8.587 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Fully miscible.
· Partition coefficient (n-octanol/water	e): Not determined.
· Viscosity:	
· Dynamic:	Not determined.
• Kinematic at 20 °C (68 °F):	40 s (ISO 4 mm)
· Oxidising properties:	N.A.
· Solvent content:	
· Water:	63.0 %
· VOC content:	4.23 %
	43.5 g/l / 0.36 lb/gal



Printing date 09/14/2022

Version number 57

Reviewed on 09/09/2022

Product number TW344

Trade name: WB CLEAR 2K TOP-COAT 20 SH

(Contd. of page 5)

· Other information (HAPS)

None of the ingredients is listed.

· Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
- · Chemical stability The product is stable in normal conditions of storage and use recommended
 - · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Acids, alkalis and oxidizing agents
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
 - · Acute toxicity:

man		
\cdot LD/.	LC50 value	es that are relevant for classification:
ATE (Acu	te Toxicit	y Estimate)
Oral	LD50	35,588 mg/kg
Dermal	LD50	66,971 mg/kg (rab)
Inhalative	LC50/4 h	670 mg/l (mouse)
34590-94-	8 (2-meth	oxymethylethoxy)propanol
Oral	LD50	5,135 mg/kg (mouse)
Dermal	LD50	19,020 mg/kg (rabbit)
111-76-2	2-butoxye	thanol
Oral	LD50	1,200 mg/kg (ATE)
		1,480 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rab)
Inhalative	LC50/4 h	11 mg/l (mouse)
57-55-6 p	ropane-1,2	2-diol
Oral	LD50	20,000 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (mouse)
108-01-0	2-dimethy	laminoethanol
Oral	LD50	1,183 mg/kg (mouse)
Dermal	LD50	1,219 mg/kg (rabbit)
Inhalative	LC50/4 h	6.1 mg/l (mouse)
. Prin	narv irritan	t offact

- · Primary irritant effect:
 - · on the skin: No irritant effect.
 - · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.

(Contd. on page 7)



Printing date 09/14/2022 Version number 57 Reviewed on 09/09/2022

Product number TW344

Trade name: WB CLEAR 2K TOP-COAT 20 SH

(Contd. of page 6)

· Additional toxicological information:

The product is not subject to classification according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us. Safety data sheet available on request.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

· Aquatic t	oxicity:
34590-94-8	(2-methoxymethylethoxy)propanol
EC50	970 mg/l (algae) (72 h)
	1,919 mg/l (daphnia) (48 h)
LC50 (96h)	1,001 mg/l (Fish)
111-76-2 2-	butoxyethanol
EC50	101 mg/l (daphnia) (24 h)
LC50 (96h)	101 mg/l (Fish)
57-55-6 pro	pane-1,2-diol
EC50	19,000 mg/l (algae) (48 h)
	18,340 mg/l (daphnia) (48 h)
LC50 (96h)	40,613 mg/l (Fish)
108-01-0 2-	dimethylaminoethanol
EC50	66.1 mg/l (algae) (72 h)
	98.4 mg/l (daphnia) (48 h)
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)
EC50	0.027 mg/l (algae) (72 h)
	0.16 mg/l (daphnia) (48 h)
LC50 (96h)	0.19 mg/l (Fish)
Dorointono	and dogradability No further relevant information available

- · Persistence and degradability No further relevant information available.
- Substances Easily biodegradable

 34590-94-8 (2-methoxymethylethoxy)propanol .

 111-76-2 2-butoxyethanol .

 57-55-6 propane-1,2-diol .
 - · Behavior in environmental systems:
 - · Bioaccumulative potential No further relevant information available.
 - · Mobility in soil No further relevant information available.

(Contd. on page 8)



Printing date 09/14/2022 Version number 57 Reviewed on 09/09/2022

Product number TW344

Trade name: WB CLEAR 2K TOP-COAT 20 SH

(Contd. of page 7)

· Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
 - · Recommendation:

Smaller quantities can be disposed of with household waste.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- · Uncleaned packagings:
 - · Recommendation: Disposal must be made according to official regulations.
 - · Recommended cleansing agent: Water, if necessary with cleansing agents.

Transport information	
UN-Number	
· DOT, ADN, IMDG, IATA	Not applicable
· Note	Check viscosity and flash point at section 9
UN proper shipping name	
· DOT, ADN, IMDG, IATA	Not applicable
Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA	
· Class	Not applicable
Packing group	
· DOT, IMDG, IATA	Not applicable
Environmental hazards:	
· Marine pollutant:	No
Special precautions for user	Not applicable.
Transport in bulk according to Annex	r II of
MARPOL73/78 and the IBC Code	Not applicable.
UN "Model Regulation":	Not applicable

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

(Contd. on page 9)



Printing date 09/14/2022 Version

Version number 57

Reviewed on 09/09/2022

Product number TW344

Trade name: WB CLEAR 2K TOP-COAT 20 SH

(Contd. of page 8)

· Various regulations

· SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

111-76-2 2-butoxyethanol

1-2.49%

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

111-76-2 2-butoxyethanol

NL 1-2.49%

· TLV (Threshold Limit Value)

111-76-2 2-butoxyethanol

А3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
 - Date of preparation / last revision 09/14/2022 / 56
 - · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

(Contd. on page 10)



Printing date 09/14/2022

Version number 57

Reviewed on 09/09/2022

Product number TW344

Trade name: WB CLEAR 2K TOP-COAT 20 SH

(Contd. of page 9)

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 4: Flammable liquids - Category 4

Acute Toxicity - Oral 3: Acute toxicity - Category 3
Acute Toxicity - Oral 4: Acute toxicity - Category 4

Acute Toxicity - Dermal 2: Acute toxicity - Category 2

Skin Corrosion 1B: Skin corrosion/irritation – Category 1B Skin Irrititation 2: Skin corrosion/irritation - Category 2

Eye Damage 1: Serious eye damage/eye irritation - Category 1

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Sensitization - Skin 1A: Skin sensitisation - Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

· Sources

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

* Data compared to the previous version altered.