

1 Identification

- **Product identifier**
 - *Product number* PZ409
 - *Trade name:* **WB EXT PASTE BLACK**
 - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
 - *Manufacturer/Supplier:*
IVM Chemicals Srl
Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
 - *Information department:*
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - *Emergency telephone number:*
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**

Skin Irritation 2 H315 Causes skin irritation.
Eye Irritation 2A H319 Causes serious eye irritation.
Sensitization - Skin 1 H317 May cause an allergic skin reaction.
- **Label elements**
 - *GHS label elements*
The product is classified and labeled according to the Globally Harmonized System (GHS).
 - *Hazard pictograms*



GHS07

- *Signal word* Warning
- *Hazard-determining components of labeling:*
C.I. ACID BLACK 194
- *Hazard statements*
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
- *Precautionary statements*
 - P261 Avoid breathing dust/fume/gas/mist/vapors/spray
 - P280 Wear protective gloves / eye protection / face protection.
 - P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 - P363 Wash contaminated clothing before reuse.
 - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Classification system:**
 - *NFPA ratings (scale 0 - 4)*



Health = 2
Fire = 1
Reactivity = 0

Product number PZ409
Trade name: WB EXT PASTE BLACK

(Contd. of page 1)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture: consisting of the following components.

· **Dangerous components:**

1333-86-4	Carbon black ⚠ Carcinogenicity 2, H351	10-12.49%
111-90-0	Diethylene glycol monoethyl ether Flammable Liquids 4, H227	5-9.99%
5131-66-8	3-butoxypropan-2-ol ⚠ Skin Irritation 2, H315; Eye Irritation 2A, H319 Flammable Liquids 4, H227	1-2.49%
108-01-0	2-dimethylaminoethanol ⚠ Flammable Liquids 3, H226 ⚠ Skin Corrosion 1B, H314 ⚠ Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332	1-2.49%
111-76-2	2-butoxyethanol ⚠ Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irritation 2, H315; Eye Irritation 2A, H319 Flammable Liquids 4, H227	0.5-1%
112-34-5	2-(2-butoxyethoxy)ethanol ⚠ Eye Irritation 2A, H319	0.5-1%
57693-14-8	C.I. ACID BLACK 194 ⚠ Aquatic Chronic 2, H411 ⚠ Eye Irritation 2A, H319; Sensitization - Skin 1, H317 Aquatic Acute 2, H401	≥0.5-<1%
95-63-6	1,2,4-trimethylbenzene ⚠ Flammable Liquids 3, H226 ⚠ Aquatic Chronic 2, H411 ⚠ Acute Toxicity - Inhalation 4, H332; Skin Irritation 2, H315; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H335	<0.25%

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

(Contd. on page 3)

Product number PZ409

Trade name: WB EXT PASTE BLACK

(Contd. of page 2)

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary).

Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist , consult a doctor.

· **After swallowing:** *Do not induce vomiting; immediately call for medical help.*

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:**

Do not use a jet water stream as it may scatter and spread fire.

· **Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

· **Advice for firefighters**

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· **Protective equipment:**

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Keep away from ignition sources

· **Environmental precautions:**

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· **Reference to other sections**

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)

Product number PZ409**Trade name: WB EXT PASTE BLACK**

(Contd. of page 3)

· Protective Action Criteria for Chemicals

· PAC-1:		
1333-86-4	Carbon black	9 mg/m
111-90-0	Diethylene glycol monoethyl ether	75 ppm
108-01-0	2-dimethylaminoethanol	3.7 ppm
577-11-7	docusate sodium	5.7 mg/m
111-76-2	2-butoxyethanol	60 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm
95-63-6	1,2,4-trimethylbenzene	140 ppm
· PAC-2:		
1333-86-4	Carbon black	99 mg/m
111-90-0	Diethylene glycol monoethyl ether	100 ppm
108-01-0	2-dimethylaminoethanol	40 ppm
577-11-7	docusate sodium	63 mg/m
111-76-2	2-butoxyethanol	120 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm
95-63-6	1,2,4-trimethylbenzene	360 ppm
· PAC-3:		
1333-86-4	Carbon black	590 mg/m
111-90-0	Diethylene glycol monoethyl ether	450 ppm
108-01-0	2-dimethylaminoethanol	72 ppm
577-11-7	docusate sodium	380 mg/m
111-76-2	2-butoxyethanol	700 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm
95-63-6	1,2,4-trimethylbenzene	480 ppm

7 Handling and storage

· Handling:**· Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires: No special measures required.**· Conditions for safe storage, including any incompatibilities****· Storage:****· Requirements to be met by storerooms and receptacles:**

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

· Information about storage in one common storage facility: Not required.**· Further information about storage conditions: Keep receptacle tightly sealed.****· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.**

US

(Contd. on page 5)

Product number PZ409**Trade name: WB EXT PASTE BLACK**

(Contd. of page 4)

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

111-90-0 Diethylene glycol monoethyl ether

WEEL Long-term value: 25 ppm

111-76-2 2-butoxyethanol

PEL Long-term value: 240 mg/m , 50 ppm
Skin

REL Long-term value: 24 mg/m , 5 ppm
Skin

TLV Long-term value: 20 ppm
BEI, A3

112-34-5 2-(2-butoxyethoxy)ethanol

TLV Long-term value: 10* ppm
*Inhalable fraction and vapor

95-63-6 1,2,4-trimethylbenzene

REL Long-term value: 125 mg/m , 25 ppm

TLV Long-term value: (25) NIC-10 ppm
NIC-A4

· **Ingredients with biological limit values:**

111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

Not required.

Short term filter device:



Filter A

Suitable respiratory protective device recommended.

(Contd. on page 6)

US

Product number PZ409

Trade name: WB EXT PASTE BLACK

(Contd. of page 5)

· **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:**

Fluid

· **Color:**

According to product specification

· **Odor:**

Characteristic

· **Odor threshold:**

Not determined.

· **pH-value:**

Mixture is non-polar/aprotic.
Range: 7 - 9

· **Change in condition**

· **Melting point/Melting range:**

Undetermined.

· **Boiling point/Boiling range:**

100 °C (212 °F)

· **Flash point:**

100 °C (212 °F)

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

230 °C (446 °F)

· **Decomposition temperature:**

Not determined.

· **Auto igniting:**

Product is not selfigniting.

· **Danger of explosion:**

Product does not present an explosion hazard.

· **Explosion limits:**

· **Lower:**

1.1 Vol %

· **Upper:**

50 Vol %

· **Vapor pressure at 20 °C (68 °F):**

1.3 hPa (1 mm Hg)

(Contd. on page 7)

Product number PZ409
Trade name: WB EXT PASTE BLACK

(Contd. of page 6)

· Density (+/- 0,03) at 20 °C (68 °F):	1.06 g/cm (8.846 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Fully miscible.	
· Partition coefficient (n-octanol/water):	Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
· Kinematic at 20 °C (68 °F):	40 s (ISO 4 mm)	
· Oxidising properties:	N.A.	
· Solvent content:		
· Water:	66.1 %	
· VOC content:	10.12 % 107.2 g/l / 0.89 lb/gal	
· Solids content:	23.8 %	
· Other information (HAPS)		
111-90-0	Diethylene glycol monoethyl ether	5-9.99%
112-34-5	2-(2-butoxyethoxy)ethanol	0.5-1%
1330-20-7	xylene	<0.1%
98-82-8	cumene	<0.1%
110-80-5	2-ethoxyethanol	<0.01%
· Other information	No further relevant information available.	

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral	LD50	117,129 mg/kg (mouse)
Dermal	LD50	120,693 mg/kg (rabbit)
Inhalative	LC50/4 h	604 mg/l (mouse)

(Contd. on page 8)

Product number PZ409**Trade name: WB EXT PASTE BLACK**

(Contd. of page 7)

1333-86-4 Carbon black		
Oral	LD50	5,001 mg/kg (mouse)
111-90-0 Diethylene glycol monoethyl ether		
Oral	LD50	6,031 mg/kg (mouse)
Dermal	LD50	9,143 mg/kg (rabbit)
5131-66-8 3-butoxypropan-2-ol		
Oral	LD50	3,300 mg/kg (mouse)
Dermal	LD50	8,001 mg/kg (mouse)
108-01-0 2-dimethylaminoethanol		
Oral	LD50	1,183 mg/kg (mouse)
Dermal	LD50	1,219 mg/kg (rabbit)
Inhalative	LC50/4 h	6.1 mg/l (mouse)
577-11-7 docusate sodium		
Oral	LD50	3,001 mg/kg (mouse)
Dermal	LD50	2,525 mg/kg (rabbit)
111-76-2 2-butoxyethanol		
Oral	LD50	1,200 mg/kg (ATE)
		1,480 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rab)
Inhalative	LC50/4 h	11 mg/l (mouse)
112-34-5 2-(2-butoxyethoxy)ethanol		
Oral	LD50	6,600 mg/kg (mouse)
Dermal	LD50	2,764 mg/kg (rabbit)
64742-95-6 Solvent naphtha (petroleum), light arom.		
Oral	LD50	6,801 mg/kg (mouse)
Dermal	LD50	3,401 mg/kg (rab)
Inhalative	LC50/4 h	20.1 mg/l (mouse)
95-63-6 1,2,4-trimethylbenzene		
Oral	LD50	5,000 mg/kg (mouse)
Inhalative	LC50/4 h	11 mg/l (mouse)

- **Primary irritant effect:**

- **on the skin:**

- Irritant to skin and mucous membranes.

- Causes skin irritation.

- **on the eye:**

- Irritating effect.

- Causes serious eye irritation.

- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

- Irritant

- Causes skin irritation.

- Causes serious eye irritation.

- May cause an allergic skin reaction.

- **Carcinogenic categories**

- Carbon Black

- IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to carbon black but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No

(Contd. on page 9)

Product number PZ409**Trade name: WB EXT PASTE BLACK**

(Contd. of page 8)

significant exposure to carbon black is thought to occur during the use of products in which carbon black is bound to other materials, such as paint."

· **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

1333-86-4	Carbon black	2B
98-82-8	cumene	2B

· **NTP (National Toxicology Program)**

98-82-8	cumene	<0.1%
---------	--------	-------

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· Toxicity

· **Aquatic toxicity:**

1333-86-4 Carbon black

EC50	10,001 mg/l (algae) (72h)
	5,601 mg/l (daphnia) (24h)
LC50 (96h)	1,000 mg/l (Fish)

111-90-0 Diethylene glycol monoethyl ether

LC50 48h	1,982 mg/l (daphnia)
LC50 (96h)	101 mg/l (Fish)

5131-66-8 3-butoxypropan-2-ol

EC50	1,001 mg/l (algae) (96 h)
	1,001 mg/l (daphnia) (48 h)
LC50 (96h)	1,000 mg/l (Fish)

108-01-0 2-dimethylaminoethanol

EC50	66.1 mg/l (algae) (72 h)
	98.4 mg/l (daphnia) (48 h)

577-11-7 docusate sodium

EC50	82.5 mg/l (algae) (72 h)
	15.2 mg/l (daphnia) (48 h)
LC50 (96h)	49 mg/l (Fish)

111-76-2 2-butoxyethanol

EC50	101 mg/l (daphnia) (24 h)
LC50 (96h)	101 mg/l (Fish)

112-34-5 2-(2-butoxyethoxy)ethanol

EC50	1,001 mg/l (daphnia) (48 h)
LC50 (96h)	1,300 mg/l (Leuciscus idus melanotus)

64742-95-6 Solvent naphtha (petroleum), light arom.

EC50	1 mg/l (algae) (72 h)
	1 mg/l (daphnia) (48 h)
LC50 (96h)	1 mg/l (Fish)

· **Persistence and degradability** No further relevant information available.

(Contd. on page 10)

Product number PZ409**Trade name: WB EXT PASTE BLACK**

(Contd. of page 9)

- **Substances Easily biodegradable**

111-90-0	Diethylene glycol monoethyl ether	.
5131-66-8	3-butoxypropan-2-ol	.
111-76-2	2-butoxyethanol	.
112-34-5	2-(2-butoxyethoxy)ethanol	.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- **UN-Number**

- DOT, ADN, IMDG, IATA

Not applicable

- Note

Check viscosity and flash point at section 9

- **UN proper shipping name**

- DOT, ADN, IMDG, IATA

Not applicable

- **Transport hazard class(es)**

- DOT, ADR, ADN, IMDG, IATA

- Class

Not applicable

- **Packing group**

- DOT, IMDG, IATA

Not applicable

- **Environmental hazards:**

- **Marine pollutant:**

No

- **Special precautions for user**

Not applicable.

- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

(Contd. on page 11)

Product number PZ409
Trade name: WB EXT PASTE BLACK

(Contd. of page 10)

· **UN "Model Regulation":** Not applicable

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

Requirements of Federal Register

- Various regulations
- SARA

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings) :**

111-90-0	Diethylene glycol monoethyl ether	5-9.99%
111-76-2	2-butoxyethanol	0.5-1%
112-34-5	2-(2-butoxyethoxy)ethanol	0.5-1%
95-63-6	1,2,4-trimethylbenzene	<0.25%
1330-20-7	xylene	<0.1%
98-82-8	cumene	<0.1%
110-80-5	2-ethoxyethanol	<0.01%

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

1330-20-7	xylene
98-82-8	cumene

· **Proposition 65**

· **Chemicals known to cause cancer:**
 Carbon black only in bound form

1333-86-4	Carbon black	*	10-12.49%
98-82-8	cumene	*	<0.1%

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

110-80-5	2-ethoxyethanol	<0.01%
----------	-----------------	--------

· **Chemicals known to cause developmental toxicity:**

110-80-5	2-ethoxyethanol	<0.01%
----------	-----------------	--------

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

111-76-2	2-butoxyethanol	NL	0.5-1%
95-63-6	1,2,4-trimethylbenzene	II	<0.25%
1330-20-7	xylene	I	<0.1%
98-82-8	cumene	D, CBD	<0.1%
526-73-8	1,2,3-trimethylbenzene	II	<0.1%

(Contd. on page 12)

Product number PZ409**Trade name: WB EXT PASTE BLACK**

(Contd. of page 11)

· TLV (Threshold Limit Value)		
1333-86-4	Carbon black	A4
111-76-2	2-butoxyethanol	A3
1330-20-7	xylene	A4
· NIOSH-Ca (National Institute for Occupational Safety and Health)		
1333-86-4	Carbon black	10-12.49%

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl

- **Contact:** See emergency phone

- **Date of preparation / last revision** 09/07/2022 / 436

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 3: Flammable liquids . Category 3

Flammable Liquids 4: Flammable liquids . Category 4

Acute Toxicity - Oral 4: Acute toxicity . Category 4

Skin Corrosion 1B: Skin corrosion/irritation . Category 1B

Skin Irritation 2: Skin corrosion/irritation . Category 2

Eye Irritation 2A: Serious eye damage/eye irritation . Category 2A

Sensitization - Skin 1: Skin sensitisation . Category 1

Carcinogenicity 2: Carcinogenicity . Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) . Category 3

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard . Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard . Category 2

· **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

- *** Data compared to the previous version altered.**