

Printing date 08/08/2022

Version number 1

Reviewed on 08/08/2022

### 1 Identification

- · Product identifier
  - · Product number HUM5AA13
  - · Trade name: CLEAR WB UV SELF SEALER 30SH
    - · Application of the substance / the mixture For professional use
- · Details of the supplier of the safety data sheet
  - · Manufacturer/Supplier:

IVM Chemicals Srl

Viale della Stazione 3 -27020 Parona (PV) Italy -Tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

001 813-248-0585

### 2 Hazard(s) identification

· Classification of the substance or mixture

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- · Label elements
  - · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labeling:

Trimethylolpropane, ethoxylated, esters with acrylic acid

Glycerol, propoxylated, esters with acrylic acid

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid

· Hazard statements

H317 May cause an allergic skin reaction.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P321 Specific treatment (see on this label).P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

- · Classification system:
  - · NFPA ratings (scale 0 4)



Health = 0 Fire = 1 Reactivity = 0

(Contd. on page 2)



Printing date 08/08/2022 Version number 1

Reviewed on 08/08/2022

**Product number HUM5AA13** 

Trade name: CLEAR WB UV SELF SEALER 30SH

(Contd. of page 1)

· HMIS-ratings (scale 0 - 4)



### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
  - · Description: Mixture: consisting of the following components.

· Dangerou	s components:		
28961-43-5	Trimethylolpropane, ethoxylated, esters with acrylic acid  • Eye Irritation 2A, H319; Sensitization - Skin 1B, H317 Aquatic Chronic 3, H412	2.5-4.99%	
7473-98-5	2-hydroxy-2-methylpropiophenone      Acute Toxicity - Oral 4, H302 Aquatic Acute 3, H402; Aquatic Chronic 3, H412	<2.5%	
111-90-0	Diethylene glycol monoethyl ether Flammable Liquids 4, H227	0.5-1%	
112-34-5	2-(2-butoxyethoxy)ethanol  © Eye Irritation 2A, H319	0.5-1%	
111-76-2	2-butoxyethanol  Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irrititation 2, H315; Eye Irritation 2A, H319  Flammable Liquids 4, H227	0.5-1%	
52408-84-1	Glycerol, propoxylated, esters with acrylic acid  © Eye Irritation 2A, H319; Sensitization - Skin 1, H317	≥0.1-<1%	
55818-57-0	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid Aquatic Chronic 2, H411 Sensitization - Skin 1, H317 Aquatic Acute 2, H401	≥0.25-<1%	
121-44-8	triethylamine  Flammable Liquids 2, H225  Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331  Skin Corrosion 1A, H314  Acute Toxicity - Oral 4, H302	<0.5%	
68439-49-6	c16-18 alcohols ethoxylated Acute Toxicity - Oral 3, H301 Eye Damage 1, H318	<0.5%	
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)  Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 2, H310; Acute Toxicity - Inhalation 2, H330  Skin Corrosion 1B, H314; Eye Damage 1, H318  Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100)  Sensitization - Skin 1A, H317	≥0.00025-<0.00159	



Printing date 08/08/2022 Version number 1 Reviewed on 08/08/2022

**Product number HUM5AA13** 

Trade name: CLEAR WB UV SELF SEALER 30SH

(Contd. of page 2)

### 4 First-aid measures

#### · Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
  - · Most important symptoms and effects, both acute and delayed Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire-fighting measures

### · Extinguishing media

· Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

### · Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

(Contd. on page 4)



Printing date 08/08/2022 Version number 1 Reviewed on 08/08/2022

**Product number HUM5AA13** 

Trade name: CLEAR WB UV SELF SEALER 30SH

(Contd. of page 3)

#### · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### Protective Action Criteria for Chemicals

Trotective	Action official for officials		
· PAC-1:			
7631-86-9	silicon dioxide, chemically prepared		18 mg/m³
111-90-0	Diethylene glycol monoethyl ether	7	75 ppm
112-34-5	2-(2-butoxyethoxy)ethanol		30 ppm
111-76-2	2-butoxyethanol	(	60 ppm
68439-49-6	c16-18 alcohols ethoxylated	:	3.8 mg/m³
121-44-8	triethylamine		1 ppm
68439-49-6	c16-18 alcohols ethoxylated		3.8 mg/m³
· PAC-2:		-	
7631-86-9	silicon dioxide, chemically prepared	7	'40 mg/m³
111-90-0	Diethylene glycol monoethyl ether	1	00 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	3	3 ррт
111-76-2	2-butoxyethanol	1	20 ppm
68439-49-6	c16-18 alcohols ethoxylated	4	2 mg/m³
121-44-8	triethylamine	1	70 ppm
68439-49-6	c16-18 alcohols ethoxylated	4	2 mg/m³
· PAC-3:		<u>'</u>	
7631-86-9	silicon dioxide, chemically prepared	4,5	i00 mg/m³
111-90-0	Diethylene glycol monoethyl ether	450	) ррт
112-34-5	2-(2-butoxyethoxy)ethanol	200	) ррт
111-76-2	2-butoxyethanol	700	) ррт
68439-49-6	c16-18 alcohols ethoxylated	250	) mg/m³
121-44-8	triethylamine		100 ppm
68439-49-6	c16-18 alcohols ethoxylated	250	) mg/m³
00.00 10 0	oro roundering curary, acou	200	,ig/

### 7 Handling and storage

### · Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires: No special measures required.

### · Conditions for safe storage, including any incompatibilities

- · Storage:
  - · Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.

(Contd. on page 5)



Printing date 08/08/2022 Version number 1 Reviewed on 08/08/2022

**Product number HUM5AA13** 

Trade name: CLEAR WB UV SELF SEALER 30SH

(Contd. of page 4)

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

### 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

### · Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

111-90	111-90-0 Diethylene glycol monoethyl ether				
WEEL	WEEL Long-term value: 25 ppm				
112-34	-5 2-(2-butoxyethoxy)ethanol				
TLV	Long-term value: 10* ppm *Inhalable fraction and vapor				
111-76	111-76-2 2-butoxyethanol				
PEL	Long-term value: 240 mg/m³, 50 ppm Skin				
REL	Long-term value: 24 mg/m³, 5 ppm Skin				
TLV	Long-term value: 20 ppm BEI, A3				
121-44	121-44-8 triethylamine				
PEL	Long-term value: 100 mg/m³, 25 ppm				
TLV	Short-term value: 1 ppm Long-term value: 0.5 ppm Skin, A4				

#### · Ingredients with biological limit values:

#### 111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine

Medium: urine
Time: end of shift

Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

· Additional information: The lists that were valid during the creation were used as basis.

### · Exposure controls

- · Personal protective equipment:
  - · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· Breathing equipment:

Short term filter device:



Suitable respiratory protective device recommended.

Filter A

(Contd. on page 6)



Printing date 08/08/2022 Version number 1 Reviewed on 08/08/2022

**Product number HUM5AA13** 

Trade name: CLEAR WB UV SELF SEALER 30SH

(Contd. of page 5)

### · Protection of hands:



### Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

### 9 Physical and chemical properties

Information on basic physical and o	chemical properties
· General Information	
· Appearance:	Fluid
· Form:	
· Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Mixture is non-polar/aprotic.
	Range: 7 - 9
· Change in condition	
· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	120 °C (248 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	>370 °C (>698 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
· Lower:	Not determined.
· Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	0 hPa
· Density (+/- 0,03) at 20 °C (68 °F):	1.037 g/cm³ (8.654 lbs/gal)
Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.

(Contd. on page 7)



Printing date 08/08/2022 Version number 1 Reviewed on 08/08/2022

**Product number HUM5AA13** 

Trade name: CLEAR WB UV SELF SEALER 30SH

		(Contd. of page
· Solubility in / Miscibility with · Water:	Fully miscible.	
· Partition coefficient (n-octanol/wat	ter): Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
· Kinematic at 20 °C (68 °F):	60 s (ISO 6 mm)	
· Oxidising properties:	N.A.	
· Solvent content:		
· Water:	57.4 %	
· VOC content:	3.07 %	
	31.9 g/l / 0.27 lb/gal	
· Solids content:	39.4 %	
Other information (HAPS)		
111-90-0 Diethylene glycol monoetl	nyl ether	0.5-1%
112-34-5 2-(2-butoxyethoxy)ethano	I	0.5-1%
121-44-8 triethylamine		<0.5%
110-80-5 2-ethoxyethanol		<0.01%
· Other information	No further relevant information avails	able.

# 10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
- · Chemical stability The product is stable in normal conditions of storage and use recommended
  - · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Acids, alkalis and oxidizing agents
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
  - Acute toxicity:

· Acute to	oxicity:	
· <i>LD</i> /	LC50 value	es that are relevant for classification:
ATE (Acu	te Toxicit	y Estimate)
Oral	LD50	48,754 mg/kg
Dermal	LD50	325,843 mg/kg (rabbit)
Inhalative	LC50/4 h	6,124 mg/l (mouse)
28961-43-	5 Trimeth	ylolpropane, ethoxylated, esters with acrylic acid
Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	13,201 mg/kg (rabbit)
7473-98-5	2-hydrox	y-2-methylpropiophenone
Oral	LD50	1,694 mg/kg (mouse)
Dermal	LD50	6,929 mg/kg (mouse)
		(Contd. on page 8



Printing date 08/08/2022

Version number 1

Reviewed on 08/08/2022

**Product number HUM5AA13** 

**CLEAR WB UV SELF SEALER 30SH** Trade name:

		(Contd. of page 7)
111-90-0	Diethylene	e glycol monoethyl ether
Oral	LD50	6,031 mg/kg (mouse)
Dermal	LD50	9,143 mg/kg (rabbit)
112-34-5	2-(2-butox	yethoxy)ethanol
Oral	LD50	6,600 mg/kg (mouse)
Dermal	LD50	2,764 mg/kg (rabbit)
111-76-2	2-butoxye	thanol
Oral	LD50	1,200 mg/kg (ATE)
		1,480 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rab)
Inhalative	LC50/4 h	11 mg/l (mouse)
55818-57-		propylidenediphenol, oligomeric reaction products with 1-chloro-2,3-
	ерохур	ropane, esters with acrylic acid
Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (rabbit)
121-44-8	triethylam	ine
Oral	LD50	730 mg/kg (mouse)
Dermal	LD50	580 mg/kg (rabbit)
Inhalative	LC50/4 h	10.9 mg/l (mouse)
. Prin	narv irritan	t offeet

- · Primary irritant effect:
  - on the skin: No irritant effect.
  - · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

May cause an allergic skin reaction.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)	
1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane	3
· NTP (National Toxicology Program)	
None of the ingredients is listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

# 12 Ecological information

· I oxicity	
· Aquatic to	oxicity:
28961-43-5	Trimethylolpropane, ethoxylated, esters with acrylic acid
EC50	70.7 mg/l (daphnia) 48H
LC50 (96h)	1.95 mg/l (Fish)
7473-98-5 2	-hydroxy-2-methylpropiophenone
EC50	119 mg/l (daphnia) (48h)
LC50 (96h)	160 mg/l (Fish)

(Contd. on page 9)



Printing date 08/08/2022

Version number 1

Reviewed on 08/08/2022

**Product number HUM5AA13** 

**CLEAR WB UV SELF SEALER 30SH** Trade name:

111-90-0 Di	(Contd. of p. (ethylene glycol monoethyl ether
	1,982 mg/l (daphnia)
LC50 (96h)	101 mg/l (Fish)
112-34-5 2-	(2-butoxyethoxy)ethanol
EC50	1,001 mg/l (daphnia) (48 h)
LC50 (96h)	1,300 mg/l (Leuciscus idus melanotus)
111-76-2 2-	butoxyethanol
EC50	101 mg/l (daphnia) (24 h)
LC50 (96h)	101 mg/l (Fish)
52408-84-1	Glycerol, propoxylated, esters with acrylic acid
EC50	12.2 mg/l (algae) (72 h)
	91.4 mg/l (daphnia) (48 h)
LC50 (96h)	5.74 mg/l (Fish)
	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2 epoxypropane, esters with acrylic acid
EC50	105 mg/l (algae) (72h)
	101 mg/l (daphnia) (48h)
LC50 (96h)	101 mg/l (Fish)
121-44-8 tri	ethylamine
EC50	8 mg/l (algae) (72 h)
	17 mg/l (daphnia) (48 h)
LC50 (96h)	36 mg/l (Fish)
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)
EC50	0.027 mg/l (algae) (72 h)
	0.16 mg/l (daphnia) (48 h)
LC50 (96h)	0.19 mg/l (Fish)

· Substances Easily bloaegraaable		
	Diethylene glycol monoethyl ether	
112-34-5	2-(2-butoxyethoxy)ethanol	

111-76-2 2-butoxyethanol

### Behavior in environmental systems:

- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

### · Additional ecological information:

### · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or

sewage system.

· Other adverse effects No further relevant information available.



Printing date 08/08/2022 Version number 1 Reviewed on 08/08/2022

**Product number HUM5AA13** 

Trade name: **CLEAR WB UV SELF SEALER 30SH** 

(Contd. of page 9)

# 13 Disposal considerations

- · Waste treatment methods
  - · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- Uncleaned packagings:
  - · Recommendation: Disposal must be made according to official regulations.
  - · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number	
· DOT, ADN, IMDG, IATA	Not applicable
· Note	Check viscosity and flash point at section 9
UN proper shipping name	
· DOT, ADN, IMDG, IATA	Not applicable
Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA	
· Class	Not applicable
Packing group	
· DOT, IMDG, IATA	Not applicable
Environmental hazards:	
· Marine pollutant:	No
Special precautions for user	Not applicable.
Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
UN "Model Regulation":	Not applicable

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
  - · Various regulations
    - · SARA

	Section 355 (extremely hazardous substances):	
None of	the ingredients is listed.	
	Section 313 (Specific toxic chemical listings):	
111-90-0	Diethylene glycol monoethyl ether	0.5-1%
112-34-5	2-(2-butoxyethoxy)ethanol	0.5-1%
111-76-2	2-butoxyethanol	0.5-1%
121-44-8	triethylamine	<0.5%
	(Contd	on page 11)



Printing date 08/08/2022

Version number 1

Reviewed on 08/08/2022

**Product number HUM5AA13** 

Trade name: CLEAR WB UV SELF SEALER 30SH

110 00 5			of page ′<0.01%
	2-ethoxyethanol		
	bronopol (INN)	'	<0.019
	CA (Toxic Substances Control Act):		
All compo	onents have the value ACTIVE.		
	Hazardous Air Pollutants		
121-44-8	triethylamine		
· Pro	position 65		
	Chemicals known to cause cancer:		
None of t	he ingredients is listed.		
•	Chemicals known to cause reproductive toxicity for females:		
None of t	he ingredients is listed.		
	Chemicals known to cause reproductive toxicity for males:		
110-80-5	2-ethoxyethanol		<0.019
	Chemicals known to cause developmental toxicity:		
110-80-5	2-ethoxyethanol		<0.019
· Car	cinogenic categories		
	EPA (Environmental Protection Agency)		
111-76-2	2-butoxyethanol	NL	0.5-19
	TLV (Threshold Limit Value)		
111-76-2	2-butoxyethanol		Α
121-44-8	triethylamine		Α
	NIOSH-Ca (National Institute for Occupational Safety and Health)		•
	he ingredients is listed.		

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
  - · Date of preparation / last revision 08/08/2022 / -
  - · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit

(Contd. on page 12)



Printing date 08/08/2022

Version number 1

Reviewed on 08/08/2022

**Product number HUM5AA13** 

Trade name: **CLEAR WB UV SELF SEALER 30SH** 

(Contd. of page 11)

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids - Category 2

Flammable Liquids 4: Flammable liquids – Category 4

Acute Toxicity - Oral 4: Acute toxicity - Category 4

Acute Toxicity - Dermal 2: Acute toxicity - Category 2

Acute Toxicity - Dermal 3: Acute toxicity - Category 3

Skin Corrosion 1A: Skin corrosion/irritation – Category 1A

Skin Corrosion 1B: Skin corrosion/irritation - Category 1B

Skin Irrititation 2: Skin corrosion/irritation - Category 2

Eye Damage 1: Serious eye damage/eye irritation – Category 1

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Sensitization - Skin 1: Skin sensitisation - Category 1

Sensitization - Skin 1A: Skin sensitisation - Category 1A

Sensitization - Skin 1B: Skin sensitisation - Category 1B

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard - Category 3

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

Sources

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

\* Data compared to the previous version altered.