

## 1 Identification

- **Product identifier**
  - Product number HTM5077
  - Trade name: **KLIMA WB CLEAR 5 SHEEN FINISH**
    - Application of the substance / the mixture For professional use
- **Details of the supplier of the safety data sheet**
  - **Manufacturer/Supplier:**  
IVM Chemicals srl  
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
  - **Information department:**  
Environmental Health and safety office  
hseoffice@ivmchemicals.com
  - **Emergency telephone number:**  
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

## 2 Hazard(s) identification

- **Classification of the substance or mixture**  
Sensitization - Skin 1 H317 May cause an allergic skin reaction.
- **Label elements**
  - **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
    - **Hazard pictograms**



GHS07

- **Signal word** Warning
- **Hazard-determining components of labeling:**  
Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)
- **Hazard statements**  
H317 May cause an allergic skin reaction.
- **Precautionary statements**
  - P261 Avoid breathing dust/fume/gas/mist/vapors/spray
  - P280 Wear protective gloves.
  - P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
  - P321 Specific treatment (see on this label).
  - P363 Wash contaminated clothing before reuse.
  - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**
  - **NFPA ratings (scale 0 - 4)**



Health = 0  
Fire = 1  
Reactivity = 0

**Product number HTM5077**

**Trade name: KLIMA WB CLEAR 5 SHEEN FINISH**

(Contd. of page 1)

· **HMIS-ratings (scale 0 - 4)**

|            |   |                |
|------------|---|----------------|
| HEALTH     | 0 | Health = 0     |
| FIRE       | 1 | Fire = 1       |
| REACTIVITY | 0 | Reactivity = 0 |

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture: consisting of the following components.

· **Dangerous components:**

|            |   |                   |
|------------|---|-------------------|
| 112-34-5   | 2-(2-butoxyethoxy)ethanol<br>⚠ Eye Irritation 2A, H319  | 2.5-4.99%         |
| 34590-94-8 | (2-methoxymethylethoxy)propanol<br>Flammable Liquids 4, H227  | 1-<5%             |
| 111-76-2   | 2-butoxyethanol<br>⚠ Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irritation 2, H315; Eye Irritation 2A, H319<br>Flammable Liquids 4, H227   | 0.5-1%            |
|            | Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)<br>⚠ Aquatic Chronic 2, H411<br>⚠ Sensitization - Skin 1, H317   | ≥0.5-<1%          |
| 68439-49-6 | c16-18 alcohols ethoxylated<br>⚠ Acute Toxicity - Oral 3, H301<br>⚠ Eye Damage 1, H318<br>⚠ Skin Irritation 2, H315   | <0.5%             |
| 25322-68-3 | Polyethylene glycol   | <0.5%             |
| 55965-84-9 | a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)<br>⚠ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 2, H310; Acute Toxicity - Inhalation 2, H330<br>⚠ Skin Corrosion 1B, H314; Eye Damage 1, H318<br>⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100)<br>⚠ Sensitization - Skin 1A, H317 | ≥0.00025-<0.0015% |

### 4 First-aid measures

· **Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

(Contd. on page 3)

**Product number HTM5077****Trade name: KLIMA WB CLEAR 5 SHEEN FINISH**

(Contd. of page 2)

*In case of unconsciousness place patient stably in side position for transportation.*

- *After skin contact: Immediately wash with water and soap and rinse thoroughly.*
- *After eye contact: Rinse opened eye for several minutes under running water.*
- *After swallowing: Do not induce vomiting; immediately call for medical help.*
- **Information for doctor:**
  - *Most important symptoms and effects, both acute and delayed*  
Allergic reactions
  - *For symptoms and effects caused by substances, refer to Section 11.*
  - *Indication of any immediate medical attention and special treatment needed*  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
  - *Suitable extinguishing agents:*  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
  - *For safety reasons unsuitable extinguishing agents:*  
Do not use a jet water stream as it may scatter and spread fire.
- **Special hazards arising from the substance or mixture**  
*In case of fire, the following can be released:*  
Nitrogen oxides (NO<sub>x</sub>)  
Carbon monoxide (CO)
- **Advice for firefighters**  
*Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.*
  - **Protective equipment:**  
*Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.*

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
*Ensure adequate ventilation*  
*Keep away from ignition sources*
- **Environmental precautions:**  
*Dilute with plenty of water.*  
*Do not allow to enter sewers/ surface or ground water.*
- **Methods and material for containment and cleaning up:**  
*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).*  
*Dispose contaminated material as waste according to Section 13.*  
*Ensure adequate ventilation.*
- **Reference to other sections**  
*See Section 7 for information on safe handling.*  
*See Section 8 for information on personal protection equipment.*  
*See Section 13 for disposal information.*
- **Protective Action Criteria for Chemicals**

| · PAC-1:   |                                      |         |
|------------|--------------------------------------|---------|
| 112-34-5   | 2-(2-butoxyethoxy)ethanol            | 30 ppm  |
| 34590-94-8 | (2-methoxymethylethoxy)propanol      | 150 ppm |
| 7631-86-9  | silicon dioxide, chemically prepared | 18 mg/m |

(Contd. on page 4)

**Product number HTM5077**  
**Trade name: KLIMA WB CLEAR 5 SHEEN FINISH**

(Contd. of page 3)

|            |                             |          |
|------------|-----------------------------|----------|
| 111-76-2   | 2-butoxyethanol             | 60 ppm   |
| 124-68-5   | 2-amino-2-methylpropanol    | 17 mg/m  |
| 68439-49-6 | c16-18 alcohols ethoxylated | 3.8 mg/m |
| 25322-68-3 | Polyethylene glycol         | 30 mg/m  |

**· PAC-2:**

|            |                                      |            |
|------------|--------------------------------------|------------|
| 112-34-5   | 2-(2-butoxyethoxy)ethanol            | 33 ppm     |
| 34590-94-8 | (2-methoxymethylethoxy)propanol      | 1700* ppm  |
| 7631-86-9  | silicon dioxide, chemically prepared | 740 mg/m   |
| 111-76-2   | 2-butoxyethanol                      | 120 ppm    |
| 124-68-5   | 2-amino-2-methylpropanol             | 190 mg/m   |
| 68439-49-6 | c16-18 alcohols ethoxylated          | 42 mg/m    |
| 25322-68-3 | Polyethylene glycol                  | 1,300 mg/m |

**· PAC-3:**

|            |                                      |            |
|------------|--------------------------------------|------------|
| 112-34-5   | 2-(2-butoxyethoxy)ethanol            | 200 ppm    |
| 34590-94-8 | (2-methoxymethylethoxy)propanol      | 9900** ppm |
| 7631-86-9  | silicon dioxide, chemically prepared | 4,500 mg/m |
| 111-76-2   | 2-butoxyethanol                      | 700 ppm    |
| 124-68-5   | 2-amino-2-methylpropanol             | 570 mg/m   |
| 68439-49-6 | c16-18 alcohols ethoxylated          | 250 mg/m   |
| 25322-68-3 | Polyethylene glycol                  | 7,700 mg/m |

## 7 Handling and storage

**· Handling:**

**· Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

**· Information about protection against explosions and fires: No special measures required.**

**· Conditions for safe storage, including any incompatibilities**

**· Storage:**

**· Requirements to be met by storerooms and receptacles:**

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

**· Information about storage in one common storage facility: Not required.**

**· Further information about storage conditions: None.**

**· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.**

## 8 Exposure controls/personal protection

**· Additional information about design of technical systems: No further data; see item 7.**

**· Control parameters**

**· Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

(Contd. on page 5)

**Product number HTM5077**  
**Trade name: KLIMA WB CLEAR 5 SHEEN FINISH**

(Contd. of page 4)

At this time, the other constituents have no known exposure limits.

**112-34-5 2-(2-butoxyethoxy)ethanol**

TLV Long-term value: 10\* ppm  
\*Inhalable fraction and vapor

**34590-94-8 (2-methoxymethylethoxy)propanol**

PEL Long-term value: 600 mg/m , 100 ppm  
Skin  
REL Short-term value: 900 mg/m , 150 ppm  
Long-term value: 600 mg/m , 100 ppm  
Skin  
TLV Long-term value: NIC-50 ppm  
(Skin)

**111-76-2 2-butoxyethanol**

PEL Long-term value: 240 mg/m , 50 ppm  
Skin  
REL Long-term value: 24 mg/m , 5 ppm  
Skin  
TLV Long-term value: 20 ppm  
BEI, A3

**25322-68-3 Polyethylene glycol**

WEEL Long-term value: 10 mg/m  
(H); MW>200

**· Ingredients with biological limit values:**

**111-76-2 2-butoxyethanol**

BEI 200 mg/g creatinine  
Medium: urine  
Time: end of shift  
Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

· **Additional information:** The lists that were valid during the creation were used as basis.

**· Exposure controls**

**· Personal protective equipment:**

**· General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.

**· Breathing equipment:**

Short term filter device:



Suitable respiratory protective device recommended.

Filter A

**· Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

(Contd. on page 6)

**Product number HTM5077****Trade name: KLIMA WB CLEAR 5 SHEEN FINISH**

(Contd. of page 5)

- **Material of gloves**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Goggles recommended during refilling.

## 9 Physical and chemical properties

### · Information on basic physical and chemical properties

#### · General Information

##### · Appearance:

- **Form:** Fluid
- **Color:** According to product specification
- **Odor:** Characteristic
- **Odor threshold:** Not determined.

- **pH-value:** Mixture is non-polar/aprotic.  
Range: 7 - 9

#### · Change in condition

- **Melting point/Melting range:** Undetermined.
- **Boiling point/Boiling range:** 100 °C (212 °F)

- **Flash point:** 94 °C (201.2 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 225 °C (437 °F)

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product does not present an explosion hazard.

#### · Explosion limits:

- **Lower:** 0.9 Vol %
- **Upper:** 14 Vol %

- **Vapor pressure at 20 °C (68 °F):** 0.4 hPa (0.3 mm Hg)

- **Density (+/- 0,03) at 20 °C (68 °F):** 1.02 g/cm (8.512 lbs/gal)

- **Relative density** Not determined.
- **Vapor density** Not determined.
- **Evaporation rate** Not determined.

#### · Solubility in / Miscibility with

- **Water:** Fully miscible.

- **Partition coefficient (n-octanol/water):** Not determined.

#### · Viscosity:

- **Dynamic:** Not determined.
- **Kinematic at 20 °C (68 °F):** 60 s (ISO 6 mm)

- **Oxidising properties:** N.A.

(Contd. on page 7)



**Product number HTM5077****Trade name: KLIMA WB CLEAR 5 SHEEN FINISH**

(Contd. of page 6)

|                           |                                  |
|---------------------------|----------------------------------|
| · <b>Solvent content:</b> |                                  |
| · <b>Water:</b>           | 65.9 %                           |
| · <b>VOC content:</b>     | 5.60 %<br>57.2 g/l / 0.48 lb/gal |
| · <b>Solids content:</b>  | 28.3 %                           |

· **Other information (HAPS)**

|          |                           |           |
|----------|---------------------------|-----------|
| 112-34-5 | 2-(2-butoxyethoxy)ethanol | 2.5-4.99% |
|----------|---------------------------|-----------|

|                            |  |
|----------------------------|--|
| · <b>Other information</b> | No further relevant information available. |
|----------------------------|--|

## 10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
  - **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

· **Information on toxicological effects**· **Acute toxicity:**· **LD/LC50 values that are relevant for classification:****ATE (Acute Toxicity Estimate)**

|      |      |              |
|------|------|--------------|
| Oral | LD50 | 77,229 mg/kg |
|------|------|--------------|

**112-34-5 2-(2-butoxyethoxy)ethanol**

|        |      |                      |
|--------|------|----------------------|
| Oral   | LD50 | 6,600 mg/kg (mouse)  |
| Dermal | LD50 | 2,764 mg/kg (rabbit) |

**34590-94-8 (2-methoxymethylethoxy)propanol**

|        |      |                       |
|--------|------|-----------------------|
| Oral   | LD50 | 5,135 mg/kg (mouse)   |
| Dermal | LD50 | 19,020 mg/kg (rabbit) |

**111-76-2 2-butoxyethanol**

|            |          |                     |
|------------|----------|---------------------|
| Oral       | LD50     | 1,200 mg/kg (ATE)   |
|            |          | 1,480 mg/kg (mouse) |
| Dermal     | LD50     | 1,100 mg/kg (rab)   |
| Inhalative | LC50/4 h | 11 mg/l (mouse)     |

**Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)**

|        |      |                                  |
|--------|------|----------------------------------|
| Oral   | LD50 | 5,001 mg/kg (mouse) (OECD - 401) |
| Dermal | LD50 | 2,001 mg/kg (mouse) (OECD - 402) |

(Contd. on page 8)

US

**Product number HTM5077**

**Trade name: KLIMA WB CLEAR 5 SHEEN FINISH**

(Contd. of page 7)

**25322-68-3 Polyethylene glycol**

Oral LD50 2,001 mg/kg (mouse)

Dermal LD50 2,001 mg/kg (rabbit)

**69011-36-5 Isotridecanolo 3-5 EO**

Oral LD50 2,000 mg/kg (mouse)

· **Primary irritant effect:**

· *on the skin:* No irritant effect.

· *on the eye:* No irritating effect.

· **Sensitization:** Sensitization possible through skin contact.

· **Additional toxicological information:**

Irritant

May cause an allergic skin reaction.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

None of the ingredients is listed.

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**12 Ecological information**

· **Toxicity**

· **Aquatic toxicity:**

**112-34-5 2-(2-butoxyethoxy)ethanol**

EC50 1,001 mg/l (daphnia) (48 h)

LC50 (96h) 1,300 mg/l (Leuciscus idus melanotus)

**34590-94-8 (2-methoxymethylethoxy)propanol**

EC50 970 mg/l (algae) (72 h)

1,919 mg/l (daphnia) (48 h)

LC50 (96h) 1,001 mg/l (Fish)

**111-76-2 2-butoxyethanol**

EC50 101 mg/l (daphnia) (24 h)

LC50 (96h) 101 mg/l (Fish)

**Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)**

EC50 101 mg/l (algae) (72h)

4 mg/l (daphnia) (OECD linee guida 202 parte 1)

LC50 (96h) 2.8 mg/l (Leuciscus idus melanotus) (OECD linee guida 203)

**68439-49-6 c16-18 alcohols ethoxylated**

EC50 0.85 mg/l (algae) (72 h)

LC50 (96h) 2.9 mg/l (Fish)

(Contd. on page 9)



**Product number** HTM5077  
**Trade name:** KLIMA WB CLEAR 5 SHEEN FINISH

(Contd. of page 8)

**25322-68-3 Polyethylene glycol**

|            |                          |
|------------|--------------------------|
| EC50       | 101 mg/l (algae) (48h)   |
|            | 101 mg/l (daphnia) (48h) |
| LC50 (96h) | 101 mg/l (Fish)          |

**55965-84-9 a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)**

|            |                            |
|------------|----------------------------|
| EC50       | 0.027 mg/l (algae) (72 h)  |
|            | 0.16 mg/l (daphnia) (48 h) |
| LC50 (96h) | 0.19 mg/l (Fish)           |

· **Persistence and degradability** No further relevant information available.

· **Substances Easily biodegradable**

|            |                                 |   |
|------------|---------------------------------|---|
| 112-34-5   | 2-(2-butoxyethoxy)ethanol       | . |
| 34590-94-8 | (2-methoxymethylethoxy)propanol | . |
| 111-76-2   | 2-butoxyethanol                 | . |

· **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

· **Recommended cleansing agent:** Water, if necessary with cleansing agents.

**14 Transport information**

· **UN-Number**

· DOT, ADN, IMDG, IATA

Not applicable

· **Note**

Check viscosity and flash point at section 9

· **UN proper shipping name**

· DOT, ADN, IMDG, IATA

Not applicable

· **Transport hazard class(es)**

· DOT, ADR, ADN, IMDG, IATA

· **Class**

Not applicable

(Contd. on page 10)

**Product number HTM5077****Trade name: KLIMA WB CLEAR 5 SHEEN FINISH**

(Contd. of page 9)

- |  |                 |
|--|-----------------|
| · <b>Packing group</b><br>· DOT, IMDG, IATA                                      | Not applicable  |
| · <b>Environmental hazards:</b><br>· Marine pollutant:                           | No              |
| · <b>Special precautions for user</b>  | Not applicable. |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b> | Not applicable. |
| · <b>UN "Model Regulation":</b>  | Not applicable  |

## 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

Requirements of Federal Register

- Various regulations
- SARA

- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

- Section 313 (Specific toxic chemical listings) :

|           |                           |           |
|-----------|---------------------------|-----------|
| 112-34-5  | 2-(2-butoxyethoxy)ethanol | 2.5-4.99% |
| 111-76-2  | 2-butoxyethanol           | 0.5-1%    |
| 1336-21-6 | ammonia                   | <0.01%    |

- TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

- Hazardous Air Pollutants

None of the ingredients is listed.

- Proposition 65

- Chemicals known to cause cancer:

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

- Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- Carcinogenic categories

- EPA (Environmental Protection Agency)

|          |                 |    |        |
|----------|-----------------|----|--------|
| 111-76-2 | 2-butoxyethanol | NL | 0.5-1% |
|----------|-----------------|----|--------|

- TLV (Threshold Limit Value)

|          |                 |    |
|----------|-----------------|----|
| 111-76-2 | 2-butoxyethanol | A3 |
|----------|-----------------|----|

- NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

(Contd. on page 11)

**Product number HTM5077****Trade name: KLIMA WB CLEAR 5 SHEEN FINISH**

(Contd. of page 10)

- **National regulations:**  
The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl
- **Contact:** See emergency phone
  - **Date of preparation / last revision** 08/08/2022 / 88
  - **Abbreviations and acronyms:**  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 NIOSH: National Institute for Occupational Safety  
 OSHA: Occupational Safety & Health  
 TLV: Threshold Limit Value  
 PEL: Permissible Exposure Limit  
 REL: Recommended Exposure Limit  
 BEI: Biological Exposure Limit  
 Flammable Liquids 4: Flammable liquids . Category 4  
 Acute Toxicity - Oral 3: Acute toxicity . Category 3  
 Acute Toxicity - Oral 4: Acute toxicity . Category 4  
 Acute Toxicity - Dermal 2: Acute toxicity . Category 2  
 Skin Corrosion 1B: Skin corrosion/irritation . Category 1B  
 Skin Irritation 2: Skin corrosion/irritation . Category 2  
 Eye Damage 1: Serious eye damage/eye irritation . Category 1  
 Eye Irritation 2A: Serious eye damage/eye irritation . Category 2A  
 Sensitization - Skin 1: Skin sensitisation . Category 1  
 Sensitization - Skin 1A: Skin sensitisation . Category 1A  
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard . Category 1  
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard . Category 1  
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard . Category 2
- **Sources**  
 REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments  
  
 Agency ECHA web site  
 INRS Fiche Toxicologique  
 IARC International agency for research on cancer
- **\* Data compared to the previous version altered.**