

Safety Data Sheet acc. to OSHA HCS

Printing date 12/13/2023

Version number 8

Reviewed on 11/15/2023

1 Identification

- · Product identifier
 - · Product number HBS5AA2
 - Trade name: CLEAR WB SEALER

```
\cdot Application of the substance / the mixture For professional use
```

· Details of the supplier of the safety data sheet

- Manufacturer/Supplier: IVM Chemicals Srl
 Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
- Information department: Environmental Health and safety office hseoffice @ivmchemicals.com
- Emergency telephone number: ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

• Classification of the substance or mixture The product is not classified, according to the Globally Harmonized System (GHS).

· Label elements

- · GHS label elements Not applicable
 - · Hazard pictograms Not applicable
 - · Signal word Not applicable
 - · Hazard statements Not applicable

· Classification system:

· NFPA ratings (scale 0 - 4)

 $\begin{array}{c} \textbf{Health} = 0\\ Fire = 1\\ Reactivity = 0 \end{array}$

· HMIS-ratings (scale 0 - 4)

HEALTH \bigcirc Health = 0FIRE1Fire = 1REACTIVITY \bigcirc Reactivity = 0

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

· Dangerou	us components:	
112-34-5	2-(2-butoxyethoxy)ethanol	1-2.49%
	🚸 Eye Irritation 2A, H319	
107-98-2	1-methoxy-2-propanol	1-2.49%
	 Flammable Liquids 3, H226 Specific Target Organ Toxicity - Single Exposure 3, H336 	
5131-66-8	3-butoxypropan-2-ol	1-2.49%
	Skin Irritation 2, H315; Eye Irritation 2A, H319 Flammable Liquids 4, H227	
57-55-6	propane-1,2-diol	0.5-1%
		(Contd. on page 2)

US



Safety Data Sheet acc. to OSHA HCS

Version number 8

Reviewed on 11/15/2023

Printing date 12/13/2023

Product number HBS5AA2 Trade name: CLEAR WB SEALER

 34590-94-8
 (2-methoxymethylethoxy)propanol
 <1%</td>

 Flammable Liquids 4, H227

4 First-aid measures

· Description of first aid measures

· General information:

No special measures required.

personal protective equipment for first aid responders is recommended. (please see section 8)

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
 - · Most important symptoms and effects, both acute and delayed
 - For symptoms and effects caused by substances, refer to Section 11.
 - · Indication of any immediate medical attention and special treatment needed
 - No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
 - · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents:
- Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

In case of fire, the following can be released: Nitrogen oxides (NOx) Carbon monoxide (CO)

Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to Section 13.

- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.
- Protective Action Criteria for Chemicals
 - PAC-1:

471-34-1 calcium carbonate

45 mg/m³

(Contd. on page 3)



Safety Data Sheet acc. to OSHA HCS

Reviewed on 11/15/2023

Printing date 12/13/2023

Version number 8

Product number HBS5AA2 Trade name: CLEAR WB SEALER

		(Contd. of page 2	
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm	
107-98-2	1-methoxy-2-propanol	100 ppm	
57-55-6	propane-1,2-diol	30 mg/m ³	
34590-94-8	(2-methoxymethylethoxy)propanol	150 ppm	
· PAC-2:			
471-34-1	calcium carbonate	210 mg/m³	
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm	
107-98-2	1-methoxy-2-propanol	160 ppm	
57-55-6	propane-1,2-diol	1,300 mg/m ³	
34590-94-8	(2-methoxymethylethoxy)propanol	1700* ppm	
· PAC-3:			
471-34-1	calcium carbonate	1,300 mg/m ³	
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm	
107-98-2	1-methoxy-2-propanol	660 ppm	
57-55-6	propane-1,2-diol	7,900 mg/m ³	
34590-94-8	(2-methoxymethylethoxy)propanol	9900** ppm	

7 Handling and storage

· Handling:

· Precautions for safe handling No special measures required.

· Information about protection against explosions and fires: No special measures required.

· Conditions for safe storage, including any incompatibilities

- Storage:
 - Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date , it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

112-34-5 2-(2-butoxyethoxy)ethanol

TLV Long-term value: 10* ppm *Inhalable fraction and vapor

(Contd. on page 4)

US



Version number 8

Reviewed on 11/15/2023

Product number HBS5AA2 Trade name: CLEAR WB SEALER

Printing date 12/13/2023

107-08	8-2 1-methoxy-2-propanol	(Contd. of page 3)
REL	Short-term value: 540 mg/m ³ , 150) nnm
NEL	Long-term value: 360 mg/m ³ , 100	
TLV	Short-term value: 100 ppm	
	Long-term value: 50 ppm	
	A4	
	-6 propane-1,2-diol	
	L Long-term value: 10 mg/m ³	
)-94-8 (2-methoxymethylethoxy)p	-
PEL	Long-term value: 600 mg/m³, 100 Skin	ppm
REL	Short-term value: 900 mg/m ³ , 150	
	Long-term value: 600 mg/m ³ , 100	ррт
T 1.1	Skin	
TLV	Long-term value: 50 ppm	
	• Regulatory information TLV: Guide to Occupational Exp	$r_{\rm Malues}(T_{\rm M})$
	REL: Guide to Occupational Exp	
		Exposure Values (AIHA WEELs)
	PEL: Guide to Occupational Ex	
• .		nt were valid during the creation were used as basis.
Per	Protection of hands: Due to missing tests no recomment Selection of the glove material on and the degradation The glove material has to be imper- Material of gloves The selection of the suitable g further marks of quality and varia a preparation of several subst calculated in advance and has t Penetration time of glove material	for handling chemicals should be followed. dation to the glove material can be given for the product. consideration of the penetration times, rates of diffusion meable and resistant to the product . loves does not only depend on the material, but also on ries from manufacturer to manufacturer. As the product is tances, the resistance of the glove material can not be herefore to be checked prior to the application.
9 Phys	sical and chemical propertie	9 5
	mation on basic physical and che	mical properties
· Gen	neral Information · Color:	According to product specification
	Odor:	Characteristic
	Odor threshold:	Not determined.
· pH-		<i>Aixture is non-polar/aprotic.</i> Range: 7 - 9

(Contd. on page 5)

US



Printing date 12/13/2023

Version number 8

Reviewed on 11/15/2023

Product number HBS5AA2 Trade name: CLEAR WB SEALER

	IC	ontd. of page
· Change in condition	(0	onto: or page
• Change in condition • Melting point/Melting range:	Undetermined.	
· Boiling point/Boiling range:	100 °C (212 °F)	
· Flash point:	100 °C (212 °F)	
-		
· Flammability (solid, gaseous):	Not applicable.	
• Auto igniting:	225 °C (437 °F)	
• Decomposition temperature:	Not determined.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
· Lower:	0.9 Vol %	
· Upper:	~20 Vol %	
· Vapor pressure at 20 °C (68 °F):	12 hPa (9 mm Hg)	
• Density (+/- 0,03) at 20 •C (68 •F):	1.05 g/cm³ (8.762 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water): Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
 Kinematic at 20 °C (68 °F): 	60 s (ISO 6 mm)	
• Oxidising properties:	N.A.	
· Solvent content:		
· Water:	34.4 %	
· VOC content:	5.22 %	
	85.8 g/l / 0.72 lb/gal	
· Solids content:	60.4 %	
Other information (HAPS)		
112-34-5 2-(2-butoxyethoxy)ethanol		1-2.499
143-22-6 2-[2-(2-butoxyethoxy)ethoxy	r]ethanol	<0.1%

10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended • Thermal decomposition / conditions to be avoided:
 - No decomposition if used and stored according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Acids, alkalis and oxidizing agents
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 6)

us



Safety Data Sheet acc. to OSHA HCS

Version number 8

Reviewed on 11/15/2023

Printing date 12/13/2023

Product number HBS5AA2 Trade name: CLEAR WB SEALER

(Contd. of page 5)

 Informati 	ion on toxi	icological effects	
· Acute t			
· LD/	LC50 value	es that are relevant for classification:	
112-34-5	2-(2-butox	yethoxy)ethanol	
Oral	LD50	6,600 mg/kg (mouse)	
Dermal	LD50	2,764 mg/kg (rabbit)	
107-98-2	1-methoxy	/-2-propanol	
Oral	LD50	4,016 mg/kg (mouse)	
Dermal	LD50	5,001 mg/kg (rabbit)	
Inhalative	LC50/4 h	5,001 mg/l (mouse)	
5131-66-8	3 3-butoxy	propan-2-ol	
Oral	LD50	3,300 mg/kg (mouse)	
Dermal	LD50	8,001 mg/kg (mouse)	
57-55-6 p	ropane-1,2	2-diol	
Oral	LD50	20,001 mg/kg (mouse)	
Dermal	LD50	2,001 mg/kg (mouse)	
34590-94	-8 (2-meth	oxymethylethoxy)propanol	
Oral	LD50	5,135 mg/kg (mouse)	
Dermal	LD50	9,510 mg/kg (rabbit)	
• •	on the eye:	No irritant effect. No irritating effect. No sensitizing effects known.	
· Sen · Additio The pr for pre When effects Safety	nal toxicolo roduct is no parations: used and according data sheet	ogical information: of subject to classification according to internally approved calculation handled according to specifications, the product does not have any to our experience and the information provided to us. t available on request.	
· Sen · Additio The pr for pre When effects Safety · Car Qua No qua	mal toxicolo roduct is no parations: used and according data sheet cinogenic c artz. significant artz is boun	of subject to classification according to internally approved calculation handled according to specifications, the product does not have any to our experience and the information provided to us. t available on request. ategories t exposure to quartz is thought to occur during the use of products of to other materials, such as resin, and for quantities present in the for	harmfu in whic
· Sen · Additio The pr for pre When effects Safety · Car Qua No qua	nal toxicolo roduct is no parations: used and according data sheet cinogenic c artz. significant artz is boun IARC (Inter	of subject to classification according to internally approved calculation handled according to specifications, the product does not have any to our experience and the information provided to us. t available on request. ategories t exposure to quartz is thought to occur during the use of products d to other materials, such as resin, and for quantities present in the for mational Agency for Research on Cancer - Cl. 1 and 2)	harmfu in whic rmula
· Sen · Additio The pr for pre When effects Safety · Car Qua No qua 14808-60	mal toxicolo roduct is no used and according data sheet crinogenic c artz. significant artz is boun IARC (Inter -7 Quartz (of subject to classification according to internally approved calculation handled according to specifications, the product does not have any to our experience and the information provided to us. t available on request. ategories t exposure to quartz is thought to occur during the use of products of to other materials, such as resin, and for quantities present in the for rnational Agency for Research on Cancer - Cl. 1 and 2) (SiO2)	harmfu in whic rmula
· Sen · Additio The pr for pre When effects Safety · Car Qua No qua 14808-60	mal toxicolo roduct is no used and according data sheet crinogenic c artz. significant artz is boun IARC (Inter -7 Quartz (of subject to classification according to internally approved calculation handled according to specifications, the product does not have any to our experience and the information provided to us. t available on request. ategories t exposure to quartz is thought to occur during the use of products d to other materials, such as resin, and for quantities present in the for rnational Agency for Research on Cancer - Cl. 1 and 2) (SiO2) nal Toxicology Program)	harmfu in whic

None of the ingredients is listed.

(Contd. on page 7)

US



Safety Data Sheet acc. to OSHA HCS

Printing date 12/13/2023

Version number 8

Reviewed on 11/15/2023

Product number HBS5AA2 Trade name: CLEAR WB SEALER

(Contd. of page 6)

Toxicity		
· Aquatic 1	•	
	-(2-butoxyethoxy)ethanol	
EC50	1,001 mg/l (daphnia) (48 h)	
, ,	1,300 mg/l (Leuciscus idus melanotus)	
	-methoxy-2-propanol	
EC50	21,100 mg/l (daphnia) (48 h)	
, ,	6,812 mg/l (Fish)	
	3-butoxypropan-2-ol	
EC50	1,001 mg/l (algae) (96 h)	
	1,001 mg/l (daphnia) (48 h)	
, ,) 1,000 mg/l (Fish)	
-	opane-1,2-diol	
EC50	19,000 mg/l (algae) (48 h)	
	18,340 mg/l (daphnia) (48 h)	
• • •) 40,613 mg/l (Fish)	
	3 (2-methoxymethylethoxy)propanol	
EC50	970 mg/l (algae) (72 h)	
	1,919 mg/l (daphnia) (48 h)	
, ,) 1,001 mg/l (Fish)	
	e and degradability No further relevant information available.	
	ces Easily biodegradable	
	2-(2-butoxyethoxy)ethanol .	
	1-methoxy-2-propanol .	
5131-66-8	3-butoxypropan-2-ol .	
57-55-6	propane-1,2-diol .	
· General Water h Do not a	l ecological information: notes: pazard class 1 (Self-assessment): slightly hazardous for water allow undiluted product or large quantities of it to reach ground water, wa system.	ter cours

13 Disposal considerations

· Waste treatment methods

- · Recommendation:
- Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- · Uncleaned packagings:
 - Recommendation: Disposal must be made according to official regulations.

(Contd. on page 8)

US

(Contd. of page 7)



Version number 8

Reviewed on 11/15/2023

Product number HBS5AA2 Trade name: CLEAR WB SEALER

Printing date 12/13/2023

14 Transport information · UN-Number · DOT, IMDG, IATA Not applicable Check viscosity and flash point at section 9 · Note · UN proper shipping name · DOT, IMDG, IATA Not applicable · Transport hazard class(es) · DOT, ADR/RID, ADN, IMDG, IATA · Class Not applicable · Packing group · DOT, IMDG, IATA Not applicable · Environmental hazards: No · Marine pollutant: · Special precautions for user Not applicable. · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · UN "Model Regulation": Not applicable

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Various regulations	
· SARA	
• Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
· Section 313 (Specific toxic chemical listings) :	
112-34-5 2-(2-butoxyethoxy)ethanol	1-2.49%
143-22-6 2-[2-(2-butoxyethoxy)ethoxy]ethanol	<0.1%
· TSCA (Toxic Substances Control Act):	
All components have the value ACTIVE.	
· Hazardous Air Pollutants	
None of the ingredients is listed.	
· Proposition 65	
· Chemicals known to cause cancer:	
Quartz (SiO2) only in bound form	
14808-60-7 Quartz (SiO2)	* <0.1%
· Chemicals known to cause reproductive toxicity for females:	
1589-47-5 2-methoxypropanol	<0.01%
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
	(Contd. on page 9



Safety Data Sheet acc. to OSHA HCS

Version number 8

Reviewed on 11/15/2023

Printing date 12/13/2023

Product number HBS5AA2 Trade name: CLEAR WB SEALER

		(Contd. of page 8
· Carcin	nogenic categories	
· EF	PA (Environmental Protection Agency)	
None of the	ingredients is listed.	
· TL	V (Threshold Limit Value)	
14807-96-6	Talc (Mg3H2(SiO3)4)	A4
14808-60-7	Quartz (SiO2)	A2
· NI	OSH-Ca (National Institute for Occupational Safety and Health)	
14808-60-7	Quartz (SiO2)	<0.1%
	QUARTZ (SIO2) afety assessment: A Chemical Safety Assessment has not been	

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: IVM Chemicals Srl

· Contact: See emergency phone · Date of preparation / last revision 12/13/2023 • Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flammable Liquids 3: Flammable liquids - Category 3 Flammable Liquids 4: Flammable liquids – Category 4 Skin Irritation 2: Skin corrosion/irritation – Category 2 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3 Sources REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments Agency ECHA web site INRS Fiche Toxicologique IARC International agency for research on cancer

• * Data compared to the previous version altered.

US -