



1 Identification

- **Product identifier**
 - *Product number* PN35
 - *Trade name:* **WB EXT IMPREGN DOUGLAS**
 - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
 - *Manufacturer/Supplier:*
IVM Chemicals Srl
Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
 - *Information department:*
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - *Emergency telephone number:*
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**
Sensitization - Skin 1 H317 May cause an allergic skin reaction.
Aquatic Acute 2 H401 Toxic to aquatic life.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.
 - **Label elements**
 - *GHS label elements*
The product is classified and labeled according to the Globally Harmonized System (GHS).
 - *Hazard pictograms*
- 

GHS07
- *Signal word* Warning
 - *Hazard-determining components of labeling:*
2-methyl-2H-isothiazol-3-one
3-Iodo-2-propynylbutylcarbamate
 - *Hazard statements*
H317 May cause an allergic skin reaction.
H401 Toxic to aquatic life.
H412 Harmful to aquatic life with long lasting effects.
 - *Precautionary statements*
P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P273 Avoid release to the environment.
P280 Wear protective gloves.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
 - **Classification system:**
 - *NFPA ratings (scale 0 - 4)*
- 

Health = 0
Fire = 1
Reactivity = 0

Product number PN35**Trade name: WB EXT IMPREGN DOUGLAS**

(Contd. of page 1)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	0
FIRE	1
REACTIVITY	0

Health = *0

Fire = 1

Reactivity = 0

3 Composition/information on ingredients

Chemical characterization: Mixtures

 · **Description:** Mixture: consisting of the following components.

 · **Dangerous components:**

111-76-2	2-butoxyethanol ⚠ Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irritation 2, H315; Eye Irritation 2A, H319 Flammable Liquids 4, H227	2.5-4.99%
55406-53-6	3-Iodo-2-propynylbutylcarbamate ⚠ Acute Toxicity - Inhalation 3, H331 ⚠ Specific Target Organ Toxicity - Repeated Exposure 1, H372 ⚠ Eye Damage 1, H318 ⚠ Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1) ⚠ Acute Toxicity - Oral 4, H302; Sensitization - Skin 1, H317	≥0.5-<1%
57-55-6	propane-1,2-diol	<0.5%
107-21-1	ethanediol ⚠ Acute Toxicity - Oral 4, H302	<0.5%
126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol ⚠ Eye Damage 1, H318 ⚠ Sensitization - Skin 1B, H317 Flammable Liquids 4, H227; Aquatic Acute 3, H402; Aquatic Chronic 3, H412	≥0.1-<0.5%
2682-20-4	2-methyl-2H-isothiazol-3-one ⚠ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331 ⚠ Skin Corrosion 1B, H314; Eye Damage 1, H318 ⚠ Sensitization - Skin 1, H317	≥0.0015-<0.01%
3811-73-2	pyridine-2-thiol 1-oxide, sodium salt ⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=10) ⚠ Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irritation 2, H315; Eye Irritation 2A, H319	<0.0025%
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1) ⚠ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 2, H310; Acute Toxicity - Inhalation 2, H330 ⚠ Skin Corrosion 1B, H314; Eye Damage 1, H318 ⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100) ⚠ Sensitization - Skin 1A, H317	<0.00025%

US

(Contd. on page 3)

Product number PN35
Trade name: WB EXT IMPREGN DOUGLAS

(Contd. of page 2)

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:**

Do not use a jet water stream as it may scatter and spread fire.

· **Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

· **Advice for firefighters**

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· **Protective equipment:**

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Keep away from ignition sources

· **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

(Contd. on page 4)

Product number PN35**Trade name: WB EXT IMPREGN DOUGLAS**

(Contd. of page 3)

Ensure adequate ventilation.

- **Reference to other sections**

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

· PAC-1:		
111-76-2	2-butoxyethanol	60 ppm
55406-53-6	3-Iodo-2-propynylbutylcarbamate	3.3 mg/m
57-55-6	propane-1,2-diol	30 mg/m
577-11-7	docusate sodium	5.7 mg/m
107-21-1	ethanediol	30 ppm
126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol	30 mg/m
· PAC-2:		
111-76-2	2-butoxyethanol	120 ppm
55406-53-6	3-Iodo-2-propynylbutylcarbamate	36 mg/m
57-55-6	propane-1,2-diol	1,300 mg/m
577-11-7	docusate sodium	63 mg/m
107-21-1	ethanediol	150 ppm
126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol	330 mg/m
· PAC-3:		
111-76-2	2-butoxyethanol	700 ppm
55406-53-6	3-Iodo-2-propynylbutylcarbamate	220 mg/m
57-55-6	propane-1,2-diol	7,900 mg/m
577-11-7	docusate sodium	380 mg/m
107-21-1	ethanediol	900 ppm
126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol	2,000 mg/m

7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- **Information about protection against explosions and fires:** No special measures required.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:** None.

(Contd. on page 5)

Product number PN35
Trade name: WB EXT IMPREGN DOUGLAS

(Contd. of page 4)

· **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

111-76-2 2-butoxyethanol

PEL Long-term value: 240 mg/m , 50 ppm
Skin

REL Long-term value: 24 mg/m , 5 ppm
Skin

TLV Long-term value: 20 ppm
BEI, A3

57-55-6 propane-1,2-diol

WEEL Long-term value: 10 mg/m

107-21-1 ethanediol

TLV Short-term value: 10** mg/m , 50* ppm
Long-term value: 25* ppm
*vapor fraction:**inh. fraction, aerosol only, A4

WEEL I (2)

· **Ingredients with biological limit values:**

111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· **Breathing equipment:**

Short term filter device:



Suitable respiratory protective device recommended.

Filter A

· **Protection of hands:**



Protective gloves

(Contd. on page 6)

Product number PN35**Trade name: WB EXT IMPREGN DOUGLAS**

(Contd. of page 5)

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Goggles recommended during refilling.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

- **Form:**

Fluid

- **Color:**

According to product specification

- **Odor:**

Characteristic

- **Odor threshold:**

Not determined.

- **pH-value:**

Mixture is non-polar/aprotic.
Range: 7 - 9

- **Change in condition**

- **Melting point/Melting range:**

Undetermined.

- **Boiling point/Boiling range:**

100 °C (212 °F)

- **Flash point:**

100 °C (212 °F)

- **Flammability (solid, gaseous):**

Not applicable.

- **Ignition temperature:**

240 °C (464 °F)

- **Decomposition temperature:**

Not determined.

- **Auto igniting:**

Product is not selfigniting.

- **Danger of explosion:**

Product does not present an explosion hazard.

- **Explosion limits:**

- **Lower:**

1.1 Vol %

- **Upper:**

10.6 Vol %

- **Vapor pressure at 20 °C (68 °F):**

1.2 hPa (0.9 mm Hg)

- **Density (+/- 0,03) at 20 °C (68 °F):**

1.004 g/cm (8.378 lbs/gal)

- **Relative density**

Not determined.

- **Vapor density**

Not determined.

- **Evaporation rate**

Not determined.

- **Solubility in / Miscibility with**

- **Water:**

Fully miscible.

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

- **Dynamic:**

Not determined.

(Contd. on page 7)

Product number PN35
Trade name: WB EXT IMPREGN DOUGLAS

(Contd. of page 6)

· Kinematic at 20 °C (68 °F):	29 s (ISO 3 mm)
· Oxidising properties:	N.A.
· Solvent content:	
· Water:	81.7 %
· VOC content:	4.82 % 48.4 g/l / 0.40 lb/gal
· Solids content:	13.4 %
· Other information (HAPS)	
107-21-1 ethanediol	<0.5%
1330-20-7 xylene	<0.1%
98-82-8 cumene	<0.01%
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	37,209 mg/kg
Dermal	LD50	34,109 mg/kg
Inhalative	LC50/4 h	50.7 mg/l

111-76-2 2-butoxyethanol

Oral	LD50	1,200 mg/kg (ATE) 1,480 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rab)
Inhalative	LC50/4 h	11 mg/l (mouse)

55406-53-6 3-Iodo-2-propynylbutylcarbamate

Oral	LD50	500 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (mouse)

57-55-6 propane-1,2-diol

Oral	LD50	20,000 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (mouse)

(Contd. on page 8)

Product number PN35**Trade name: WB EXT IMPREGN DOUGLAS**

(Contd. of page 7)

577-11-7 docusate sodium

Oral	LD50	3,001 mg/kg (mouse)
Dermal	LD50	2,525 mg/kg (rabbit)

107-21-1 ethanediol

Oral	LD50	301 mg/kg (mouse)
	LD50.	7,712 mg/kg (mouse)
Dermal	LD50	3,501 mg/kg (mouse)
		9,530 mg/kg (rabbit)
Inhalative	LC50/6 h	2.6 ppm (mouse)

126-86-3 2,4,7,9-tetramethyldec-5-yne-4,7-diol

Oral	LD50	4,600 mg/kg (mouse)
------	------	---------------------

2682-20-4 2-methyl-2H-isothiazol-3-one

Oral	LD50	200 mg/kg (mouse)
Dermal	LD50	400 mg/kg (mouse)
Inhalative	LC50/4 h	0.53 mg/l (mouse)

3811-73-2 pyridine-2-thiol 1-oxide, sodium salt

Oral	LD50	1,208 mg/kg (mouse)
Dermal	LD50	1,800 mg/kg (mouse)
Inhalative	LC50/4 h	1.66 mg/l (mouse)

· **Primary irritant effect:**

- *on the skin:* No irritant effect.
- *on the eye:* No irritating effect.

· **Sensitization:** Sensitization possible through skin contact.· **Additional toxicological information:**

Irritant

May cause an allergic skin reaction.

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

98-82-8	cumene	2B
---------	--------	----

· **NTP (National Toxicology Program)**

98-82-8	cumene	<0.01%
---------	--------	--------

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information· **Toxicity** Harmful to aquatic life with long lasting effects.· **Aquatic toxicity:****111-76-2 2-butoxyethanol**

EC50	101 mg/l (daphnia) (24 h)
LC50 (96h)	101 mg/l (Fish)

55406-53-6 3-Iodo-2-propynylbutylcarbamate

EC50	22 mg/l (algae) (72 h)
	0.16 mg/l (daphnia) (48 h)
LC50 (96h)	67 mg/l (Fish)

(Contd. on page 9)

Product number PN35**Trade name: WB EXT IMPREGN DOUGLAS**

(Contd. of page 8)

57-55-6 propane-1,2-diol

EC50	19,000 mg/l (algae) (48 h)
	18,340 mg/l (daphnia) (48 h)
LC50 (96h)	40,613 mg/l (Fish)

577-11-7 docusate sodium

EC50	82.5 mg/l (algae) (72 h)
	15.2 mg/l (daphnia) (48 h)
LC50 (96h)	49 mg/l (Fish)

107-21-1 ethanediol

EC50	101 mg/l (daphnia) (48h)
LC50 (96h)	72,860 mg/l (Fish)

55965-84-9 a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)

EC50	0.027 mg/l (algae) (72 h)
	0.16 mg/l (daphnia) (48 h)
LC50 (96h)	0.19 mg/l (Fish)

- **Persistence and degradability** No further relevant information available.

- **Substances Easily biodegradable**

111-76-2	2-butoxyethanol	.
----------	-----------------	---

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

- **Ecotoxicological effects:**

- **Remark:** Harmful to fish

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Smaller quantities can be disposed of with household waste.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

US

(Contd. on page 10)

Product number PN35
Trade name: WB EXT IMPREGN DOUGLAS

(Contd. of page 9)

14 Transport information

· UN-Number	Not applicable
· DOT, ADN, IMDG, IATA	
· Note	Check viscosity and flash point at section 9
· UN proper shipping name	Not applicable
· DOT, ADN, IMDG, IATA	
· Transport hazard class(es)	Not applicable
· DOT, ADR, ADN, IMDG, IATA	
· Class	
· Packing group	Not applicable
· DOT, IMDG, IATA	
· Environmental hazards:	No
· Marine pollutant:	
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	Not applicable

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
 Requirements of Federal Register

- Various regulations
- SARA

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings) :**

111-76-2	2-butoxyethanol	2.5-4.99%
55406-53-6	3-Iodo-2-propynylbutylcarbamate	≥0.5-<1%
107-21-1	ethanediol	<0.5%
95-63-6	1,2,4-trimethylbenzene	<0.1%
1330-20-7	xylene	<0.1%
98-82-8	cumene	<0.01%
1344-28-1	aluminium oxide	<0.01%

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

107-21-1	ethanediol
1330-20-7	xylene
98-82-8	cumene

(Contd. on page 11)

Product number PN35
Trade name: WB EXT IMPREGN DOUGLAS

(Contd. of page 10)

· **Proposition 65**· **Chemicals known to cause cancer:**

98-82-8	cumene	*	<0.01%
---------	--------	---	--------

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

107-21-1	ethanediol		<0.5%
----------	------------	--	-------

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

111-76-2	2-butoxyethanol	NL	2.5-4.99%
95-63-6	1,2,4-trimethylbenzene	II	<0.1%
1330-20-7	xylene	I	<0.1%
98-82-8	cumene	D, CBD	<0.01%
526-73-8	1,2,3-trimethylbenzene	II	<0.01%

· **TLV (Threshold Limit Value)**

111-76-2	2-butoxyethanol	A3
107-21-1	ethanediol	A4
112945-52-5	silicon dioxide	A4
1330-20-7	xylene	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl
- **Contact:** See emergency phone
- **Date of preparation / last revision** 09/23/2022 / 94

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit

(Contd. on page 12)

Product number PN35**Trade name: WB EXT IMPREGN DOUGLAS**

(Contd. of page 11)

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 4: Flammable liquids . Category 4

Acute Toxicity - Oral 4: Acute toxicity . Category 4

Acute Toxicity - Dermal 2: Acute toxicity . Category 2

Acute Toxicity - Inhalation 3: Acute toxicity . Category 3

Skin Corrosion 1B: Skin corrosion/irritation . Category 1B

Skin Irritation 2: Skin corrosion/irritation . Category 2

Eye Damage 1: Serious eye damage/eye irritation . Category 1

Eye Irritation 2A: Serious eye damage/eye irritation . Category 2A

Sensitization - Skin 1: Skin sensitisation . Category 1

Sensitization - Skin 1A: Skin sensitisation . Category 1A

Sensitization - Skin 1B: Skin sensitisation . Category 1B

Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) . Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard . Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard . Category 2

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard . Category 3

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard . Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3

• **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

• * **Data compared to the previous version altered.**