

Printing date 08/08/2022

Version number 39

Reviewed on 06/15/2022

1 Identification

- · Product identifier
 - ·!Product number HHS1A07
 - Itrade name: WB UV R/C OIL EFFECT PRIMER • Application of the substance / the mixture For professional use

· Details of the supplier of the safety data sheet

- Manufacturer/Supplier: IVM Chemicals Srl
 Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
- Information department: Environmental Health and safety office hseoffice @ivmchemicals.com
- Emergency telephone number:
- ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture

Flammable Liquids 4 H227 Combustible liquid. Flam. Liq. 4

Skin Irrititation 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Warning

· Hazard-determining components of labeling: .beta.-Alanine, N-(2-aminoethyl)-, sodiumsalt (1:1), polymer with .alpha.-hydro-.omega.hydroxypoly(oxy-1,2-ethanediyl), 3-· Hazard statements H227 Combustible liquid. Flam. Liq. 4 H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. · Precautionary statements P210 Keep away from flames and hot surfaces. – No smoking. P261 Avoid breathing dust/fume/gas/mist/vapors/spray P280 Wear protective gloves/protective clothing/eye protection/face protection. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P403+P235 Store in a well-ventilated place. Keep cool. P501 Dispose of contents/container in accordance with local/regional/national/ international regulations. (Contd. on page 2)

____US




Reviewed on 06/15/2022

Printing date 08/08/2022

Version number 39

Product number HHS1A07 Trade name: WB UV R/C OIL EFFECT PRIMER

(Contd. of page 1)



3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

· Dangerous o	components:	
1011480-20-8	.betaAlanine, N-(2-aminoethyl)-, sodiumsalt (1:1), polymer with .alphahydroomegahydroxypoly(oxy-1,2-ethanediyl), 3-	20-24.99%
	Skin Irrititation 2, H315; Eye Irritation 2A, H319; Sensitization - Skin 1, H317	
34590-94-8	(2-methoxymethylethoxy)propanol	5-<10%
	Flammable Liquids 4, H227	
28961-43-5	Trimethylolpropane, ethoxylated, esters with acrylic acid	≥0.5-<1%
	Eye Irritation 2A, H319; Sensitization - Skin 1B, H317 Aquatic Chronic 3, H412	
121-44-8	triethylamine	<0.5%
	 Flammable Liquids 2, H225 Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331 Skin Corrosion 1A, H314 Acute Toxicity - Oral 4, H302 	
	🚸 Acute Toxicity - Oral 4, H302	

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8) · *After inhalation:*

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary). Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

(Contd. on page 3)

US

Version number 39

Reviewed on 06/15/2022

Printing date 08/08/2022

Chemicals

Product number HHS1A07 Trade name: WB UV R/C OIL EFFECT PRIMER

(Contd. of page 2)

- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist , consult a doctor.
- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
 - Most important symptoms and effects, both acute and delayed Allergic reactions
 - For symptoms and effects caused by substances, refer to Section 11.
 - · Indication of any immediate medical attention and special treatment needed
 - No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
 - · Suitable extinguishing agents:
 - CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
 - · For safety reasons unsuitable extinguishing agents:
 - Do not use a jet water stream as it may scatter and spread fire.
- · Special hazards arising from the substance or mixture

In case of fire, the following can be released: Nitrogen oxides (NOx) Carbon monoxide (CO)

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

Wear protect Ensure adect Keep away is Environmen Dilute with p Do not allow Methods ar Absorb with Dispose con Ensure adect Reference to See Section See Section See Section	ecautions, protective equipment and emergency procedures tive equipment. Keep unprotected persons away. quate ventilation from ignition sources ntal precautions: lenty of water. to enter sewers/ surface or ground water. Ind material for containment and cleaning up: liquid-binding material (sand, diatomite, acid binders, universal binders, saw taminated material as waste according to Section 13. quate ventilation. o other sections 7 for information on safe handling. 8 for information on personal protection equipment. 13 for disposal information. Action Criteria for Chemicals	vdust).
• PAC-1:		
34590-94-8	(2-methoxymethylethoxy)propanol	150 ppm
7631-86-9	silicon dioxide, chemically prepared	18 mg/m³
	(Co	ntd. on page 4)



Reviewed on 06/15/2022

Printing date 08/08/2022

Version number 39

Product number HHS1A07 Trade name: WB UV R/C OIL EFFECT PRIMER

104 44 0	this the demains	(Contd. of page 3)
121-44-8	triethylamine	1 ppm
· PAC-2:		
34590-94-8	(2-methoxymethylethoxy)propanol	1700* ppm
7631-86-9	silicon dioxide, chemically prepared	740 mg/m³
121-44-8	triethylamine	170 ppm
• PAC-3:		
	(2-methoxymethylethoxy)propanol	9900** ppm
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m ³
121-44-8	triethylamine	1,000 ppm

7 Handling and storage

- · Handling:
 - · Precautions for safe handling
 - Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
 - Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.

· Conditions for safe storage, including any incompatibilities

- · Storage:
 - · Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date , it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

34590-94-8 (2-methoxymethylethoxy)propanol

- PEL Long-term value: 600 mg/m³, 100 ppm Skin
- REL Short-term value: 900 mg/m³, 150 ppm Long-term value: 600 mg/m³, 100 ppm Skin
- TLV Long-term value: NIC-50 ppm (Skin)

(Contd. on page 5)

US



Version number 39

Reviewed on 06/15/2022

Printing date 08/08/2022

Product number HHS1A07 Trade name: WB UV R/C OIL EFFECT PRIMER

(Contd. of page 4)

121-44-8 triethylamine

- PEL Long-term value: 100 mg/m³, 25 ppm
- TLV Short-term value: 1 ppm Long-term value: 0.5 ppm
 - Skin, A4

Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.
- · Breathing equipment:
- Short term filter device:



Suitable respiratory protective device recommended.

Filter A • Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

- · General Information
 - Appearance:
 - · Form:

· Color: · Odor: Fluid According to product specification Characteristic

(Contd. on page 6)

US



Reviewed on 06/15/2022

Printing date 08/08/2022

Version number 39

Product number HHS1A07					
Trade name:	WB UV R/C	OIL EFFECT PRIMER			

		(Contd. of page
· Odor threshold:	Not determined.	
· pH-value:	Mixture is non-polar/aprotic.	
	Range: 7 - 9	
· Change in condition		
• Melting point/Melting range:	Undetermined.	
· Boiling point/Boiling range:	100 °C (212 °F)	
· Flash point:	75 °C (167 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	>370 °C (>698 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Not determined.	
· Explosion limits:		
Lower:	1.1 Vol %	
· Upper:	14 Vol %	
· Vapor pressure at 20 °C (68 °F):	0.4 hPa (0.3 mm Hg)	
• Density (+/- 0,03) at 20 °C (68 °F):	1.038 g/cm³ (8.662 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Fully miscible.	
· Partition coefficient (n-octanol/water	·): Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
• <i>Kinematic at 20</i> • <i>C</i> (68 • <i>F</i>):	60 s (ISO 6 mm)	
· Oxidising properties:	N.A.	
· Solvent content:		
· Water:	62.9 %	
· VOC content:	6.31 %	
	65.5 g/l / 0.55 lb/gal	
· Solids content:	30.8 %	
Other information (HAPS)		
121-44-8 triethylamine		<0.5%
 Other information 	No further relevant information available.	

10 Stability and reactivity

· Reactivity typical of the product as indicated in the data sheet

• **Chemical stability** The product is stable in normal conditions of storage and use recommended • Thermal decomposition / conditions to be avoided:

- No decomposition if used and stored according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.

• Conditions to avoid No further relevant information available.

 \cdot Incompatible materials: Acids, alkalis and oxidizing agents

(Contd. on page 7)

US



Version number 39

Reviewed on 06/15/2022

Printing date 08/08/2022

Product number HHS1A07 Trade name: WB UV R/C OIL EFFECT PRIMER

(Contd. of page 6) • Hazardous decomposition products: No dangerous decomposition products known.

		formation icological effects
· Acute to		cological ellects
	•	es that are relevant for classification:
		y Estimate)
•	LD50	222,245 mg/kg (rabbit)
Inhalative	LC50/4 h	4,177 mg/l (mouse)
1011480-2		-Alanine, N-(2-aminoethyl)-, sodiumsalt (1:1), polymer with .alph oomegahydroxypoly(oxy-1,2-ethanediyl), 3-
Oral	LD50	5,001 mg/kg (mouse)
34590-94-	·8 (2-meth	oxymethylethoxy)propanol
Oral	LD50	5,135 mg/kg (mouse)
Dermal	LD50	19,020 mg/kg (rabbit)
28961-43-	5 Trimeth	ylolpropane, ethoxylated, esters with acrylic acid
Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	13,201 mg/kg (rabbit)
121-44-8 t	triethylam	ine
Oral	LD50	730 mg/kg (mouse)
Dermal	LD50	580 mg/kg (rabbit)
Inhalative	LC50/4 h	10.9 mg/l (mouse)
		canolo 3-5 EO
Oral	LD50	2,000 mg/kg (mouse)
160901-09	-7 Alcoho	bls, C9-11, branched and linear, ethoxylated
Oral	LD50	1,201 mg/kg (mouse)
• 6 • 6 • Sens • Addition Irritant Causes Causes	on the eye: sitization: S nal toxicolo s skin irrita s serious e	Irritant to skin and mucous membranes. Irritating effect. Sensitization possible through skin contact. ogical information:
	cinogenic c	
	-	rnational Agency for Research on Cancer - Cl. 1 and 2)
		acryloyloxymethyl)butyl acrylate
· /	NTP (Natio	nal Toxicology Program)
	,	nts is listed.
· (OSHA-Ca (Occupational Safety & Health Administration)
None of th	ne ingredie	nts is listed.

(Contd. on page 8)

US

(Contd. of page 7)



Safety Data Sheet acc. to OSHA HCS

Printing date 08/08/2022 Version number 39

Reviewed on 06/15/2022

Product number HHS1A07 Trade name: WB UV R/C OIL EFFECT PRIMER

12 Ecological information · Toxicity · Aquatic toxicity: 34590-94-8 (2-methoxymethylethoxy)propanol EC50 970 mg/l (algae) (72 h) 1,919 mg/l (daphnia) (48 h) LC50 (96h) 1,001 mg/l (Fish) 28961-43-5 Trimethylolpropane, ethoxylated, esters with acrylic acid EC50 70.7 mg/l (daphnia) 48H LC50 (96h) 1.95 mg/l (Fish) 121-44-8 triethylamine EC50 8 mg/l (algae) (72 h) 17 mg/l (daphnia) (48 h) LC50 (96h) 36 mg/l (Fish) · Persistence and degradability No further relevant information available. · Substances Easily biodegradable 34590-94-8 (2-methoxymethylethoxy)propanol . · Behavior in environmental systems: · Bioaccumulative potential No further relevant information available. · Mobility in soil No further relevant information available. Additional ecological information: · General notes: Water hazard class 1 (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

• Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

· UN-Number

· DOT, ADN, IMDG, IATA

Not applicable

· Note

Check viscosity and flash point at section 9

(Contd. on page 9)

US



Printing date 08/08/2022

Version number 39

Reviewed on 06/15/2022

Product number HHS1A07 Trade name: WB UV R/C OIL EFFECT PRIMER

		(Contd. of page
· UN proper shipping name		
· DOT, ADN, IMDĞ, IATA	Not applicable	
· Transport hazard class(es)		
· DOT, ADR, ADN, IMDG, IATA		
· Class	Not applicable	
Packing group		
· DOT, IMDĠ, IATA	Not applicable	
Environmental hazards:		
• Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex	ː II of	
MARPOL73/78 and the IBC Code	Not applicable.	
UN "Model Regulation":	Not applicable	

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Various regulations

· SARA

· Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
· Section 313 (Specific toxic chemical listings) :	
121-44-8 triethylamine	<0.5%
· TSCA (Toxic Substances Control Act):	
.betaAlanine, N-(2-aminoethyl)-, sodiumsalt (1:1), polymer with .alphahydroomega hydroxypoly(oxy-1,2-ethanediyl), 3-	ACTIVE
(2-methoxymethylethoxy)propanol	ACTIVE
Trimethylolpropane, ethoxylated, esters with acrylic acid	ACTIVE
triethylamine	ACTIVE
· Hazardous Air Pollutants	
121-44-8 triethylamine	
· Proposition 65	
· Chemicals known to cause cancer:	
15625-89-5 2,2-bis(acryloyloxymethyl)butyl acrylate *	<0.025%
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
(Contd	on page 10)
	US



Printing date 08/08/2022

Version number 39

Reviewed on 06/15/2022

Product number HHS1A07 Trade name: WB UV R/C OIL EFFECT PRIMER

(Contd. of page 9)

A4

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

• TLV (Threshold Limit Value)

121-44-8 triethylamine

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- Contact: See emergency phone
- · Date of preparation / last revision 08/08/2022 / 38 · Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flammable Liquids 2: Flammable liquids - Category 2 Flammable Liquids 4: Flammable liquids - Category 4 Acute Toxicity - Oral 4: Acute toxicity - Category 4 Acute Toxicity - Dermal 3: Acute toxicity - Category 3 Skin Corrosion 1A: Skin corrosion/irritation - Category 1A Skin Irrititation 2: Skin corrosion/irritation - Category 2 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Sensitization - Skin 1: Skin sensitisation - Category 1 Sensitization - Skin 1B: Skin sensitisation - Category 1B Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 Sources REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments Agency ECHA web site INRS Fiche Toxicologique IARC International agency for research on cancer \cdot * Data compared to the previous version altered.