

## ILVA TECHNICAL DATA SHEET

**PRODUCT SERIES:** KLIMA SERIES

**PRODUCT CODE:** PZ400 Series

**DESCRIPTION:** Pigmented Pastes for Water Based Impregnators

**USES:** To tint and color water based impregnators for outdoor use

**GENERAL PROPERTIES:** Specific Gravity, gr/cc+/-02

<b>AVAILABLE COLORS:</b>	PZ402	Yellow Oxide	1.150
	PZ404	Brown	1.360
	PZ406	Green	1.050
	PZ409	Black	1.200

**NOTES:** For deeper colors use PZ5xx pastes, up to 5% - see page # for list of PZ5xx colors. We recommend mechanical mixing before use for every paste to precisely duplicate color matches. Weighing of tints is important. We recommend using pastes PZ400 series for tinting impregnators started from base TN30 (clear) with a maximum addition is 3%  
**KEEP FROM FREEZING!**

**SHELF LIFE:** 12 Months

**STORAGE:** Store in a tightly closed container at room temperatures (18 -25 °C/64 -75 °F) and protect from moisture and foreign material. Do not store at temperatures below 7°C (45°F).

**DATE OF ISSUANCE:** 03-13, 2-18, 6-23

**IC & S, P.O. BOX 10845, LANCASTER, PA 17605  
(800) 220-4035**

EVERY REASONABLE PRECAUTION IS TAKEN IN THE MANUFACTURE OF OUR PRODUCTS TO INSURE THAT THEY COMPLY WITH OUR STANDARDS. INFORMATION GIVEN IS CORRECT TO THE BEST OF OUR KNOWLEDGE. ANY SUGGESTIONS MADE BY US COVERING THE USE OF OUR PRODUCTS ARE BASED ON EXPERIENCE AND/OR TESTS BELIEVED TO BE RELIABLE. HOWEVER, BECAUSE THE USE OF ANY PRODUCT OF OUR MANUFACTURE IS COMPLETELY BEYOND OUR CONTROL, INCLUDING FOR EXAMPLE, THE METHOD AND CONDITIONS OF APPLICATION, NO GUARANTEE OR WARRANTY, EXPRESSED OR IMPLIED, IS MADE. MANUFACTURER'S MAXIMUM LIABILITY SHALL BE TO REPLACE SUCH QUANTITY OF PRODUCT DETERMINED BY OUR LABORATORY TO BE DEFECTIVE. USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR HIS INTENDED USE AND ASSUME ALL RISK AND LIABILITY IN CONNECTION THEREWITH.