

1 Identification

- **Product identifier**
 - *Product number* TES1A02
 - *Trade name:* **UV solv-b. clear sealer**
 - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
 - *Manufacturer/Supplier:*
IVM Chemicals Srl
Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
 - *Information department:*
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - *Emergency telephone number:*
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**

Flammable Liquids 4	H227 Combustible liquid. Flam. Liq. 4
Skin Irritation 2	H315 Causes skin irritation.
Eye Damage 1	H318 Causes serious eye damage.
Sensitization - Skin 1	H317 May cause an allergic skin reaction.
Carcinogenicity 1A	H350 May cause cancer. Route of exposure: Inhalation.
Toxic to Reproduction 2	H361 Suspected of damaging fertility or the unborn child.
Aquatic Acute 2	H401 Toxic to aquatic life.
Aquatic Chronic 2	H411 Toxic to aquatic life with long lasting effects.

- **Label elements**

- *GHS label elements*

The product is classified and labeled according to the Globally Harmonized System (GHS).

- *Hazard pictograms*



GHS05 GHS07 GHS08 GHS09

- *Signal word* Danger

- *Hazard-determining components of labeling:*

oxybis(methyl-2, 1-ethanediyl) diacrylate
Quartz (SiO₂)
Glycerol, propoxylated, esters with acrylic acid
hexamethylene diacrylate
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

- *Hazard statements*

H227 Combustible liquid. Flam. Liq. 4
H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H350 May cause cancer. Route of exposure: Inhalation.
H361 Suspected of damaging fertility or the unborn child.
H401 Toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.

Product number TES1A02**Trade name: UV solv-b. clear sealer**

(Contd. of page 1)

Precautionary statements

- P210 Keep away from flames and hot surfaces. . No smoking.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a poison center/doctor.
 P321 Specific treatment (see on this label).
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:**NFPA ratings (scale 0 - 4)****HMIS-ratings (scale 0 - 4)**

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture: consisting of the following components.

Dangerous components:

57472-68-1	oxybis(methyl-2,1-ethanediyl) diacrylate Eye Damage 1, H318 Skin Irritation 2, H315; Sensitization - Skin 1, H317	25-29.99%
52408-84-1	Glycerol, propoxylated, esters with acrylic acid Eye Irritation 2A, H319; Sensitization - Skin 1, H317	≥10-<20%
13048-33-4	hexamethylene diacrylate Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Irritation 2, H315; Eye Irritation 2A, H319; Sensitization - Skin 1, H317	≥2.5-<10%
7473-98-5	2-hydroxy-2-methylpropiophenone Acute Toxicity - Oral 4, H302 Aquatic Acute 3, H402; Aquatic Chronic 3, H412	2.5-<25%
123-86-4	n-butyl acetate Flammable Liquids 3, H226 Specific Target Organ Toxicity - Single Exposure 3, H336	2.5-4.99%
108-88-3	toluene Flammable Liquids 2, H225 Toxic to Reproduction 2, H361; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304 Skin Irritation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H336 Aquatic Chronic 3, H412	≥0.1-<0.5%
110-19-0	isobutyl acetate Flammable Liquids 2, H225 Specific Target Organ Toxicity - Single Exposure 3, H336	<0.5%

(Contd. on page 3)

Product number TES1A02
Trade name: UV solv-b. clear sealer

		(Contd. of page 2)
162881-26-7	phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide ⚠ Sensitization - Skin 1A, H317 Aquatic Chronic 4, H413	≥0.1-<0.5%
14808-60-7	Quartz (SiO ₂) ⚠ Carcinogenicity 1A, H350	≥0.1-<0.5%
142-16-5	Bis(2-ethylhexyl) maleate ⚠ Specific Target Organ Toxicity - Repeated Exposure 2, H373 ⚠ Aquatic Chronic 1, H410	≥0.025-<0.25%
108-31-6	maleic anhydride ⚠ Sensitization - Respiratory 1, H334 ⚠ Skin Corrosion 1B, H314 ⚠ Acute Toxicity - Oral 4, H302; Sensitization - Skin 1, H317	≥0.001-<0.1%

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary).

Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: Do not induce vomiting; immediately call for medical help.

· Information for doctor:

· Most important symptoms and effects, both acute and delayed

Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

(Contd. on page 4)

Product number TES1A02**Trade name: UV solv-b. clear sealer**

(Contd. of page 3)

- **Advice for firefighters**

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

- **Protective equipment:**

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

- **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

· PAC-1:		
13048-33-4	hexamethylene diacrylate	3 mg/m
7631-86-9	silicon dioxide, chemically prepared	18 mg/m
123-86-4	n-butyl acetate	5 ppm
108-88-3	toluene	67 ppm
110-19-0	isobutyl acetate	450 ppm
14808-60-7	Quartz (SiO ₂)	0.075 mg/m

· PAC-2:		
13048-33-4	hexamethylene diacrylate	170 mg/m
7631-86-9	silicon dioxide, chemically prepared	740 mg/m
123-86-4	n-butyl acetate	200 ppm
108-88-3	toluene	560 ppm
110-19-0	isobutyl acetate	1300* ppm
14808-60-7	Quartz (SiO ₂)	33 mg/m

· PAC-3:		
13048-33-4	hexamethylene diacrylate	990 mg/m
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m
123-86-4	n-butyl acetate	3000* ppm
108-88-3	toluene	3700* ppm
110-19-0	isobutyl acetate	7500** ppm

(Contd. on page 5)

Product number TES1A02
Trade name: UV solv-b. clear sealer

14808-60-7 Quartz (SiO₂)

(Contd. of page 4)

200 mg/m

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Keep respiratory protective device available.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions: Keep receptacle tightly sealed.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

13048-33-4 hexamethylene diacrylate

WEEL Long-term value: 1 mg/m
 DSEN

123-86-4 n-butyl acetate

PEL Long-term value: 710 mg/m, 150 ppm

REL Short-term value: 950 mg/m, 200 ppm
 Long-term value: 710 mg/m, 150 ppm

TLV Short-term value: 150 ppm
 Long-term value: 50 ppm

108-88-3 toluene

PEL Long-term value: 200 ppm
 Ceiling limit value: 300; 500* ppm
 *10-min peak per 8-hr shift

REL Short-term value: 560 mg/m, 150 ppm
 Long-term value: 375 mg/m, 100 ppm

TLV Long-term value: 20 ppm
 BEI, OTO, A4

(Contd. on page 6)

Product number TES1A02
Trade name: UV solv-b. clear sealer

(Contd. of page 5)

110-19-0 isobutyl acetate

PEL	Long-term value: 700 mg/m , 150 ppm
REL	Long-term value: 700 mg/m , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

14808-60-7 Quartz (SiO₂)

PEL	Long-term value: 0.05* mg/m *resp. dust; 30mg/m ³ /%SiO ₂ +2
REL	Long-term value: 0.05* mg/m *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m *respirable particulate matter, A2

108-31-6 maleic anhydride

PEL	Long-term value: 1 mg/m , 0.25 ppm
REL	Long-term value: 1 mg/m , 0.25 ppm
TLV	Long-term value: 0.01* mg/m DSEN, RSEN,*inh. fraction + vapor, A4

· **Ingredients with biological limit values:****108-88-3 toluene**

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

· **Additional information:** The lists that were valid during the creation were used as basis.· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.
- Pregnant women should strictly avoid inhalation or skin contact.

· **Breathing equipment:**

Short term filter device:



Suitable respiratory protective device recommended.

(Contd. on page 7)

Product number TES1A02**Trade name: UV solv-b. clear sealer**

(Contd. of page 6)

Filter A

· **Protection of hands:**

Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**· **Form:**

Fluid

· **Color:**

According to product specification

· **Odor:**

Characteristic

· **Odor threshold:**

Not determined.

· **pH-value:**

Mixture is non-polar/aprotic.

· **Change in condition**· **Melting point/Melting range:**

Undetermined.

· **Boiling point/Boiling range:**

124-128 °C (255.2-262.4 °F)

· **Flash point:**

79 °C (174.2 °F)

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

370 °C (698 °F)

· **Decomposition temperature:**

Not determined.

· **Auto igniting:**

Product is not selfigniting.

· **Danger of explosion:**

Not determined.

· **Explosion limits:**· **Lower:**

1.2 Vol %

· **Upper:**

7.5 Vol %

· **Vapor pressure at 20 °C (68 °F):**

10.7 hPa (8 mm Hg)

(Contd. on page 8)

Product number TES1A02
Trade name: UV solv-b. clear sealer

(Contd. of page 7)

· Density (+/- 0,03) at 20 °C (68 °F):	1.196 g/cm (9.981 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
· Dynamic:	Not determined.
· Kinematic at 20 °C (68 °F):	60 s (ISO 6 mm)
· Oxidising properties:	N.A.
· Solvent content:	
· VOC content:	4.16 % 49.7 g/l / 0.41 lb/gal
· Solids content:	95.8 %
· Other information (HAPS)	
108-88-3 toluene	≥0.1-<0.5%
1330-20-7 xylene	<0.1%
100-41-4 ethylbenzene	<0.1%
108-31-6 maleic anhydride	≥0.001-<0.1%
79-10-7 acrylic acid	<0.1%
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	45,784 mg/kg (mouse)
------	------	----------------------

57472-68-1 oxybis(methyl-2,1-ethanediyl) diacrylate

Oral	LD50	3,530 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (rabbit)

(Contd. on page 9)

US

Product number TES1A02
Trade name: UV solv-b. clear sealer

(Contd. of page 8)

13048-33-4 hexamethylene diacrylate		
Oral	LD50	5,001 mg/kg (mouse)
Dermal	LD50	3,601 mg/kg (rab)
7473-98-5 2-hydroxy-2-methylpropiophenone		
Oral	LD50	1,694 mg/kg (mouse)
Dermal	LD50	6,929 mg/kg (mouse)
123-86-4 n-butyl acetate		
Oral	LD50	10,760 mg/kg (mouse)
Dermal	LD50	14,000 mg/kg (rabbit)
Inhalative	LC50/4 h	21.1 mg/l (mouse)
108-88-3 toluene		
Oral	LD50	5,000 mg/kg (mouse)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	25.7 mg/l (mouse)
110-19-0 isobutyl acetate		
Oral	LD50	13,400 mg/kg (mouse)
Dermal	LD50	17,401 mg/kg (rabbit)
Inhalative	LC50/4 h	31 mg/l (mouse)
64742-95-6 Solvent naphtha (petroleum), light arom.		
Oral	LD50	6,801 mg/kg (mouse)
Dermal	LD50	3,401 mg/kg (rab)
Inhalative	LC50/4 h	20.1 mg/l (mouse)
162881-26-7 phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide		
Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (mouse)
108-31-6 maleic anhydride		
Oral	LD50	1,090 mg/kg (mouse)
Dermal	LD50	2,620 mg/kg (rabbit)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:**

- Strong caustic effect.

- Strong irritant with the danger of severe eye injury.

- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

- Irritant

- Causes skin irritation.

- Causes serious eye damage.

- May cause an allergic skin reaction.

- May cause cancer. Route of exposure: Inhalation.

- Suspected of damaging fertility or the unborn child.

- **Carcinogenic categories**

- Quartz.

- No significant exposure to quartz is thought to occur during the use of products in which quartz is bound to other materials, such as resin, and for quantities present in the formula

- Ethylbenzene

- From IARC MONOGRAPHS VOLUME 77/2000

- Human carcinogenicity data

- Two studies of workers potentially exposed to ethylbenzene in a production plant and a

(Contd. on page 10)

Product number TES1A02**Trade name: UV solv-b. clear sealer**

(Contd. of page 9)

styrene polymerization plant were available. In the first study, no excess of cancer incidence was found but the description of methods was insufficient to allow proper evaluation of this finding. In the second study, no cancer mortality excess was observed during the follow-up of 15 years.

Evaluation

There is inadequate evidence in humans for the carcinogenicity of ethylbenzene. There is sufficient evidence in experimental animals for the carcinogenicity of ethylbenzene.

· **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

14808-60-7	Quartz (SiO ₂)	1
100-41-4	ethylbenzene	2B

· **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO ₂)	≥0.1-<0.5%
------------	----------------------------	------------

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity** Toxic to aquatic life with long lasting effects.

· **Aquatic toxicity:****57472-68-1 oxybis(methyl-2,1-ethanediyl) diacrylate**

EC50	16.7 mg/l (algae) (72 h)
	22.3 mg/l (daphnia) (48 h)
	2.2 mg/l (Fish) (96 h)

52408-84-1 Glycerol, propoxylated, esters with acrylic acid

EC50	12.2 mg/l (algae) (72 h)
	91.4 mg/l (daphnia) (48 h)
LC50 (96h)	5.74 mg/l (Fish)

13048-33-4 hexamethylene diacrylate

EC50	1.5 mg/l (algae) (72 h)
LC50 48h	2.6 mg/l (daphnia)
LC50 (96h)	10 mg/l (Fish)

7473-98-5 2-hydroxy-2-methylpropiophenone

EC50	119 mg/l (daphnia) (48h)
LC50 (96h)	160 mg/l (Fish)

123-86-4 n-butyl acetate

EC50	397 mg/l (algae) (72 h)
	44 mg/l (daphnia) (48 h)
LC50 (96h)	18 mg/l (Fish)

108-88-3 toluene

EC50	134 mg/l (algae) (96 h)
	3.78 mg/l (daphnia) (48 h)
LC50 (96h)	5.5 mg/l (Fish)

110-19-0 isobutyl acetate

EC50	370 mg/l (algae) (72 h)
------	-------------------------

(Contd. on page 11)

Product number TES1A02
Trade name: UV solv-b. clear sealer

(Contd. of page 10)

LC50 (96h)	25 mg/l (daphnia) 17 mg/l (Fish)
64742-95-6 Solvent naphtha (petroleum), light arom.	
EC50	1 mg/l (algae) (72 h) 1 mg/l (daphnia) (48 h)
LC50 (96h)	1 mg/l (Fish)
162881-26-7 phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	
EC50	1,175 mg/l (daphnia) 48h
108-31-6 maleic anhydride	
EC50	29 mg/l (algae) (72 h) 42.8 mg/l (daphnia) (48 h)
LC50 (96h)	75 mg/l (Fish)

· **Persistence and degradability** No further relevant information available.

· **Substances Easily biodegradable**

57472-68-1	oxybis(methyl-2,1-ethanediyl) diacrylate	.
52408-84-1	Glycerol, propoxylated, esters with acrylic acid	.
13048-33-4	hexamethylene diacrylate	.
123-86-4	n-butyl acetate	.

· **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

· **Ecotoxicological effects:**

· **Remark:** Toxic for fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Must not reach bodies of water or drainage ditch undiluted or unneutralized.
 Danger to drinking water if even small quantities leak into the ground.
 Also poisonous for fish and plankton in water bodies.
 Toxic for aquatic organisms

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.


US

(Contd. on page 12)

Product number TES1A02
Trade name: UV solv-b. clear sealer

(Contd. of page 11)

14 Transport information

<ul style="list-style-type: none"> · UN-Number · DOT, IMDG, IATA · Note 	UN3082 Check viscosity and flash point at section 9
<ul style="list-style-type: none"> · UN proper shipping name · DOT · IMDG · IATA 	Environmentally hazardous substance, liquid, n.o.s. (hexamethylene diacrylate, Solvent naphtha (petroleum), light arom.) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (hexamethylene diacrylate, Solvent naphtha (petroleum), light arom., Bis(2-ethylhexyl) maleate), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (hexamethylene diacrylate, Solvent naphtha (petroleum), light arom.)
<ul style="list-style-type: none"> · Transport hazard class(es) · DOT, IMDG, IATA 	 <ul style="list-style-type: none"> · Class · Label · Class · Label
<ul style="list-style-type: none"> · Packing group · DOT, IMDG, IATA 	III
<ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: · Special marking (IATA): 	Product contains environmentally hazardous substances: hexamethylene diacrylate Yes Symbol (fish and tree) Symbol (fish and tree)
<ul style="list-style-type: none"> · Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category 	Warning: Miscellaneous dangerous substances and articles 90 F-A,S-F A
<ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	Not applicable.
<ul style="list-style-type: none"> · Transport/Additional information: · DOT · Remarks: 	Special marking with the symbol (fish and tree).

(Contd. on page 13)

Product number TES1A02
Trade name: UV solv-b. clear sealer

(Contd. of page 12)

· **IMDG**

- Limited quantities (LQ)
- Excepted quantities (EQ)

5L

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":**

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (HEXAMETHYLENE DIACRYLATE, SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.), 9, III

15 Regulatory information

 · **Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Various regulations
- SARA

 · **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

 · **Section 313 (Specific toxic chemical listings) :**

108-88-3	toluene	≥0.1-<0.5%
1330-20-7	xylene	<0.1%
110-82-7	cyclohexane	≥0.025-<0.1%
100-41-4	ethylbenzene	<0.1%
108-31-6	maleic anhydride	≥0.001-<0.1%
79-10-7	acrylic acid	<0.1%
1338-02-9	Naphthenic acids, copper salts	<0.01%
142-71-2	copper di(acetate)	<0.01%

 · **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

 · **Hazardous Air Pollutants**

108-88-3	toluene
1330-20-7	xylene
100-41-4	ethylbenzene
108-31-6	maleic anhydride
79-10-7	acrylic acid

 · **Proposition 65**

- **Chemicals known to cause cancer:**
 Quartz (SiO₂) only in bound form

14808-60-7	Quartz (SiO ₂)	*	≥0.1-<0.5%
100-41-4	ethylbenzene	*	<0.1%

 · **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

(Contd. on page 14)

Product number TES1A02
Trade name: UV solv-b. clear sealer

(Contd. of page 13)

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene	≥0.1-<0.5%
----------	---------	------------

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

108-88-3	toluene	II	≥0.1-<0.5%
1330-20-7	xylene	I	<0.1%
110-82-7	cyclohexane	I	≥0.025-<0.1%
100-41-4	ethylbenzene	D	<0.1%

· **TLV (Threshold Limit Value)**

14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	A4
108-88-3	toluene	A4
14808-60-7	Quartz (SiO ₂)	A2
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
108-31-6	maleic anhydride	A4
79-10-7	acrylic acid	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

14808-60-7	Quartz (SiO ₂)	≥0.1-<0.5%
------------	----------------------------	------------

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** IVM Chemicals Srl

· **Contact:** See emergency phone

· **Date of preparation / last revision** 09/07/2022 / 69

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

(Contd. on page 15)

Product number TES1A02
Trade name: UV solv-b. clear sealer

(Contd. of page 14)

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids . Category 2

Flammable Liquids 3: Flammable liquids . Category 3

Flammable Liquids 4: Flammable liquids . Category 4

Acute Toxicity - Oral 4: Acute toxicity . Category 4

Skin Corrosion 1B: Skin corrosion/irritation . Category 1B

Skin Irritation 2: Skin corrosion/irritation . Category 2

Eye Damage 1: Serious eye damage/eye irritation . Category 1

Eye Irritation 2A: Serious eye damage/eye irritation . Category 2A

Sensitization - Respiratory 1: Respiratory sensitisation . Category 1

Sensitization - Skin 1: Skin sensitisation . Category 1

Sensitization - Skin 1A: Skin sensitisation . Category 1A

Carcinogenicity 1A: Carcinogenicity . Category 1A

Toxic to Reproduction 2: Reproductive toxicity . Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) . Category 3

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) . Category 2

Aspiration Hazard 1: Aspiration hazard . Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard . Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard . Category 2

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard . Category 3

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard . Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard . Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard . Category 4

• Sources

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

• * Data compared to the previous version altered.