

## TECHNICAL DATA SHEET

**PRODUCT CODE:** PX 70

**DESCRIPTION:** Matting agent additive for acrylic urethanes

**USES:** Use as a matting agent additive for acrylics, TS 0 series.  
Not for use in the PM series polyurethanes.

**PRODUCT APPLICATION:** Add up to 10% maximum to adjust gloss of Acrylic Urethane products

**PRODUCT APPLICATION:** Typical of the product to be adjusted

**GENERAL PROPERTIES:**

Specific Gravity, gr/cc	1.10 +/- 0.05
Solids by Weight, %	51 +/- 2

**SHELF LIFE:** One year

**STORAGE:** Store in a tightly closed container at room temperatures (18 -25 °C/64 -75 °F) and protect from moisture and foreign material.

**DATE OF ISSUANCE:** 03 - 97 Revised 4-02

**IC & S, P.O. BOX 10845, LANCASTER, PA 17605  
(800) 220-4035**

EVERY REASONABLE PRECAUTION IS TAKEN IN THE MANUFACTURE OF OUR PRODUCTS TO INSURE THAT THEY COMPLY WITH OUR STANDARDS. INFORMATION GIVEN IS CORRECT TO THE BEST OF OUR KNOWLEDGE. ANY SUGGESTIONS MADE BY US COVERING THE USE OF OUR PRODUCTS ARE BASED ON EXPERIENCE AND/OR TESTS BELIEVED TO BE RELIABLE. HOWEVER, BECAUSE THE USE OF ANY PRODUCT OF OUR MANUFACTURE IS COMPLETELY BEYOND OUR CONTROL, INCLUDING FOR EXAMPLE, THE METHOD AND CONDITIONS OF APPLICATION, NO GUARANTEE OR WARRANTY, EXPRESSED OR IMPLIED, IS MADE. MANUFACTURER'S MAXIMUM LIABILITY SHALL BE TO REPLACE SUCH QUANTITY OF PRODUCT DETERMINED BY OUR LABORATORY TO BE DEFECTIVE. USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR HIS INTENDED USE AND ASSUME ALL RISK AND LIABILITY IN CONNECTION THEREWITH.