

1 Identification

- **Product identifier**
 - Product number PZ330
 - Trade name: **WHITE TINT. PASTE**
 - Application of the substance / the mixture For professional use
- **Details of the supplier of the safety data sheet**
 - **Manufacturer/Supplier:**
IVM Chemicals Srl
Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
 - **Information department:**
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - **Emergency telephone number:**
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**

Flammable Liquids 3	H226 Flammable liquid and vapor.
Carcinogenicity 2	H351 Suspected of causing cancer.
Toxic to Reproduction 2	H361 Suspected of damaging fertility or the unborn child.
Specific Target Organ Toxicity - Repeated Exposure 2	H373 May cause damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Oral, Inhalation.

· Label elements

- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS08

- **Signal word** Warning

- **Hazard-determining components of labeling:**

xylene
ethylbenzene

- **Hazard statements**

H226 Flammable liquid and vapor.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to the hearing organs through prolonged or repeated exposure.
Route of exposure: Oral, Inhalation.

- **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Product number PZ330
Trade name: WHITE TINT. PASTE

(Contd. of page 1)

Classification system:

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



3 Composition/information on ingredients

Chemical characterization: Mixtures

· **Description:** Mixture: consisting of the following components.

Dangerous components:

1330-20-7	xylene <ul style="list-style-type: none"> ☠ Flammable Liquids 3, H226 ☠ Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304 ⚠ Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irritation 2, H315; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H335 Aquatic Acute 3, H402; Aquatic Chronic 3, H412 	5-9.99%
123-86-4	n-butyl acetate <ul style="list-style-type: none"> ☠ Flammable Liquids 3, H226 ⚠ Specific Target Organ Toxicity - Single Exposure 3, H336 	2.5-4.99%
100-41-4	ethylbenzene <ul style="list-style-type: none"> ☠ Flammable Liquids 2, H225 ☠ Carcinogenicity 2, H351; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304 ⚠ Acute Toxicity - Inhalation 4, H332 Aquatic Chronic 3, H412 	1-2.49%
108-65-6	2-methoxy-1-methylethyl acetate <ul style="list-style-type: none"> ☠ Flammable Liquids 3, H226 ⚠ Specific Target Organ Toxicity - Single Exposure 3, H336 	<0.5%
77-99-6	propylidynetrimehanol <ul style="list-style-type: none"> ☠ Toxic to Reproduction 2, H361 	≥0.1-<0.5%
64-17-5	ethanol <ul style="list-style-type: none"> ☠ Flammable Liquids 2, H225 ⚠ Eye Irritation 2A, H319 	<0.5%
110-19-0	isobutyl acetate <ul style="list-style-type: none"> ☠ Flammable Liquids 2, H225 ⚠ Specific Target Organ Toxicity - Single Exposure 3, H336 	<0.5%

US

(Contd. on page 3)

Product number PZ330
Trade name: WHITE TINT. PASTE

(Contd. of page 2)

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Immediately rinse with water.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

For symptoms and effects caused by substances, refer to Section 11.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

Alcohol resistant foam

Alcohol resistant foam, CO, powder, water spray/mist.

· **For safety reasons unsuitable extinguishing agents:**

Do not use a jet water stream as it may scatter and spread fire.

· **Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

In case of fire, the following can be released:

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

· **Advice for firefighters**

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· **Protective equipment:**

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

(Contd. on page 4)

Product number PZ330
Trade name: WHITE TINT. PASTE

(Contd. of page 3)

See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· PAC-1:		
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	30 mg/m
1330-20-7	xylene	130 ppm
123-86-4	n-butyl acetate	5 ppm
100-41-4	ethylbenzene	33 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
64-17-5	ethanol	1,800 ppm
110-19-0	isobutyl acetate	450 ppm
· PAC-2:		
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	330 mg/m
1330-20-7	xylene	920* ppm
123-86-4	n-butyl acetate	200 ppm
100-41-4	ethylbenzene	1100* ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
64-17-5	ethanol	3300* ppm
110-19-0	isobutyl acetate	1300* ppm
· PAC-3:		
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2,000 mg/m
1330-20-7	xylene	2500* ppm
123-86-4	n-butyl acetate	3000* ppm
100-41-4	ethylbenzene	1800* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
64-17-5	ethanol	15000* ppm
110-19-0	isobutyl acetate	7500** ppm

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

- Ensure good ventilation/exhaustion at the workplace.
- Open and handle receptacle with care.
- Prevent formation of aerosols.
- Protect against electrostatic charges.
- Keep respiratory protective device available.
- Use explosion-proof apparatus / fittings and spark-proof tools.

· **Information about protection against explosions and fires:**

- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

- Provide solvent resistant, sealed floor.
- Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.
- In cases where there is no reported expiration date, it means that the product must be used

(Contd. on page 5)

Product number PZ330
Trade name: WHITE TINT. PASTE

(Contd. of page 4)

- within 8 months.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
 - **Components with limit values that require monitoring at the workplace:**
 The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
 At this time, the remaining constituent has no known exposure limits.

1330-20-7 xylene

PEL	Long-term value: 435 mg/m , 100 ppm
REL	Short-term value: 655 mg/m , 150 ppm Long-term value: 435 mg/m , 100 ppm
TLV	Short-term value: (150) ppm Long-term value: (100) NIC-20 ppm BEI, A4

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m , 150 ppm
REL	Short-term value: 950 mg/m , 200 ppm Long-term value: 710 mg/m , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m , 100 ppm
REL	Short-term value: 545 mg/m , 125 ppm Long-term value: 435 mg/m , 100 ppm
TLV	Long-term value: 20 NIC-20 ppm BEI, A3, NIC: OTO, BEI, A3

108-65-6 2-methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

64-17-5 ethanol

PEL	Long-term value: 1900 mg/m , 1000 ppm
REL	Long-term value: 1900 mg/m , 1000 ppm
TLV	Short-term value: 1000 ppm A3

110-19-0 isobutyl acetate

PEL	Long-term value: 700 mg/m , 150 ppm
REL	Long-term value: 700 mg/m , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

(Contd. on page 6)

Product number PZ330
Trade name: WHITE TINT. PASTE

(Contd. of page 5)

· Ingredients with biological limit values:

1330-20-7 xylene

BEI 1.5 g/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: Methylhippuric acids

100-41-4 ethylbenzene

BEI 0.15 g/g creatinine
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Pregnant women should strictly avoid inhalation or skin contact.

· Breathing equipment:

- Not required.
- Short term filter device:



Suitable respiratory protective device recommended.

Filter A

· Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)

US

Product number PZ330
Trade name: WHITE TINT. PASTE

(Contd. of page 6)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

· Form:

Fluid

· Color:

According to product specification

· Odor:

Characteristic

· Odor threshold:

Not determined.

· pH-value:

Mixture is non-polar/aprotic.

· Change in condition

· Melting point/Melting range:

Undetermined.

· Boiling point/Boiling range:

124-128 °C (255.2-262.4 °F)

· Flash point:

25 °C (77 °F)

· Flammability (solid, gaseous):

Not applicable.

· Ignition temperature:

370 °C (698 °F)

· Decomposition temperature:

Not determined.

· Auto igniting:

Product is not selfigniting.

· Danger of explosion:

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

· Lower:

1 Vol %

· Upper:

7.8 Vol %

· Vapor pressure at 20 °C (68 °F):

10.7 hPa (8 mm Hg)

· Density (+/- 0,03) at 20 °C (68 °F):

1.84 g/cm (15.355 lbs/gal)

· Relative density

Not determined.

· Vapor density

Not determined.

· Evaporation rate

Not determined.

· Solubility in / Miscibility with

· Water:

Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water):

Not determined.

· Viscosity:

· Dynamic:

Not determined.

· Kinematic at 20 °C (68 °F):

55 s (ISO 6 mm)

· Oxidising properties:

N.A.

· Solvent content:

· Water:

0.0 %

· VOC content:

14.88 %

273.7 g/l / 2.28 lb/gal

(Contd. on page 8)

Product number PZ330
Trade name: WHITE TINT. PASTE

(Contd. of page 7)

· Solids content:		84.9 %
· Other information (HAPS)		
1330-20-7	xylene	5-9.99%
100-41-4	ethylbenzene	1-2.49%
· Other information		No further relevant information available.

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions**
Reacts with oxidizing agents.
Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Dermal	LD50	12,225 mg/kg (rabbit)
Inhalative	LC50/4 h	106 mg/l (mouse)

1330-20-7 xylene

Oral	LD50.	3,523 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rabbit) (ATE value)
	LD50.	12,126 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (mouse) (ATE value)
	LC50/4h.	27.571 mg/l (mouse)

123-86-4 n-butyl acetate

Oral	LD50	10,760 mg/kg (mouse)
Dermal	LD50	14,000 mg/kg (rabbit)
Inhalative	LC50/4 h	21.1 mg/l (mouse)

100-41-4 ethylbenzene

Oral	LD50	3,500 mg/kg (mouse)
Dermal	LD50	15,486 mg/kg (rabbit)
Inhalative	LC50/4 h	17.2 mg/l (mouse)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8,532 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 h	35.7 mg/l (mouse)

(Contd. on page 9)

Product number PZ330
Trade name: WHITE TINT. PASTE

(Contd. of page 8)

77-99-6 propylidynetrimethanol

Oral	LD50	14,700 mg/kg (mouse)
Dermal	LD50	10,001 mg/kg (mouse)

64-17-5 ethanol

Oral	LD50	10,470 mg/kg (mouse)
Dermal	LD50	20,000 mg/kg (rabbit)
Inhalative	LC50/4 h	124.7 mg/l (mouse)

110-19-0 isobutyl acetate

Oral	LD50	13,400 mg/kg (mouse)
Dermal	LD50	17,401 mg/kg (rabbit)
Inhalative	LC50/4 h	31 mg/l (mouse)

64741-65-7 Naphtha (petroleum), heavy alkylate

Oral	LD50	6,001 mg/kg (mouse)
Dermal	LD50	3,001 mg/kg (rabbit)

- **Primary irritant effect:**

- *on the skin:* No irritant effect.
- *on the eye:* No irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Oral, Inhalation.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

- **Carcinogenic categories**

Titanium dioxide

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

Ethylbenzene

From IARC MONOGRAPHS VOLUME 77/2000

Human carcinogenicity data

Two studies of workers potentially exposed to ethylbenzene in a production plant and a styrene polymerization plant were available. In the first study, no excess of cancer incidence was found but the description of methods was insufficient to allow proper evaluation of this finding. In the second study, no cancer mortality excess was observed during the follow-up of 15 years.

Evaluation

There is inadequate evidence in humans for the carcinogenicity of ethylbenzene. There is sufficient evidence in experimental animals for the carcinogenicity of ethylbenzene.

- **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2B - DUST
100-41-4	ethylbenzene	2B
64-17-5	ethanol	1 in alcoholic beverages

(Contd. on page 10)

Product number PZ330
Trade name: WHITE TINT. PASTE

(Contd. of page 9)

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· Toxicity

· **Aquatic toxicity:**

1330-20-7 xylene

EC50	2.2 mg/l (algae)
LC50 48h	1 mg/l (daphnia)
LC50 (96h)	2.6 mg/l (Fish)

123-86-4 n-butyl acetate

EC50	397 mg/l (algae) (72 h)
	44 mg/l (daphnia) (48 h)
LC50 (96h)	18 mg/l (Fish)

100-41-4 ethylbenzene

EC50	438 mg/l (algae) (72h)
	1.8 mg/l (daphnia) (48 h)
LC50 (96h)	12.1 mg/l (Fish)

108-65-6 2-methoxy-1-methylethyl acetate

EC50	1,001 mg/l (algae) (72 h)
	501 mg/l (daphnia) (48 h)
LC50 (96h)	134 mg/l (Fish)

77-99-6 propylidynetrimethanol

EC50	1,001 mg/l (algae) (72h)
	13,000 mg/l (daphnia) (48h)
LC50 (96h)	1,001 mg/l (Fish)

64-17-5 ethanol

EC50	5,012 mg/l (daphnia) (48 h)
LC50 (96h)	15.3 mg/l (Fish)

110-19-0 isobutyl acetate

EC50	370 mg/l (algae) (72 h)
	25 mg/l (daphnia)
LC50 (96h)	17 mg/l (Fish)

· **Persistence and degradability** No further relevant information available.

· **Substances Easily biodegradable**

1330-20-7	xylene	.
123-86-4	n-butyl acetate	.
100-41-4	ethylbenzene	.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.
 · **Mobility in soil** No further relevant information available.

(Contd. on page 11)

Product number PZ330
Trade name: WHITE TINT. PASTE

(Contd. of page 10)

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· DOT, IATA

UN1263

· IMDG

Not applicable

· Note

Check viscosity and flash point at section 9

· **UN proper shipping name**

· DOT

Paint

· IMDG

Not applicable

· IATA

PAINT

· **Transport hazard class(es)**

· DOT



· Class

3 Flammable liquids

· Label

3

· Class

Not applicable

· IATA



· Class

3 Flammable liquids

· Label

3

· **Packing group**

· DOT, IATA

III

· IMDG

Not applicable

(Contd. on page 12)

Product number PZ330
Trade name: WHITE TINT. PASTE

(Contd. of page 11)

- | | |
|--|--------------------|
| · Environmental hazards: | |
| · <i>Marine pollutant:</i> | No |
| · Special precautions for user Not applicable. | |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. | |
| · Transport/Additional information: | |
| · DOT | |
| · <i>Remarks:</i> | > 450 l: 3 F1, III |
| · IMDG | |
| · <i>Remarks:</i> | > 450 l: 3, III |
| · UN "Model Regulation": Not applicable | |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

Requirements of Federal Register

- **Various regulations**
- SARA

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings) :**

1330-20-7	xylene	5-9.99%
100-41-4	ethylbenzene	1-2.49%
67-63-0	propan-2-ol	<0.01%

- **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

- **Hazardous Air Pollutants**

1330-20-7	xylene
100-41-4	ethylbenzene

- **Proposition 65**

- **Chemicals known to cause cancer:**

Titanium dioxide only in bound form

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	only for Dust	50-74.99%
100-41-4	ethylbenzene	*	1-2.49%

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

(Contd. on page 13)

Product number PZ330
Trade name: WHITE TINT. PASTE

(Contd. of page 12)

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I	5-9.99%
100-41-4	ethylbenzene	D	1-2.49%
78-93-3	butanone	I	<0.01%

· **TLV (Threshold Limit Value)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
64-17-5	ethanol	A3
67-63-0	propan-2-ol	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	50-74.99%
------------	---	-----------

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl
- **Contact:** See emergency phone
- **Date of preparation / last revision** 08/15/2022 / 465

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 BEI: Biological Exposure Limit
 Flammable Liquids 2: Flammable liquids . Category 2
 Flammable Liquids 3: Flammable liquids . Category 3
 Acute Toxicity - Dermal 4: Acute toxicity . Category 4
 Skin Irritation 2: Skin corrosion/irritation . Category 2
 Eye Irritation 2A: Serious eye damage/eye irritation . Category 2A
 Carcinogenicity 2: Carcinogenicity . Category 2
 Toxic to Reproduction 2: Reproductive toxicity . Category 2
 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) . Category 3
 Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) . Category 2
 Aspiration Hazard 1: Aspiration hazard . Category 1
 Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard . Category 3
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3

(Contd. on page 14)

Product number PZ330

Trade name: WHITE TINT. PASTE

(Contd. of page 13)

· *Sources*

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

· * *Data compared to the previous version altered.*

US