

1 Identification

- **Product identifier**
 - *Product number* TS1170
 - *Trade name:* **UR CLEAR PRECAT SELF-S 80SH**
 - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
 - *Manufacturer/Supplier:*
IVM Chemicals Srl
Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
 - *Information department:*
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - *Emergency telephone number:*
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**

Flammable Liquids 2	H225 Highly flammable liquid and vapor.
Eye Damage 1	H318 Causes serious eye damage.
Specific Target Organ Toxicity - Single Exposure 3H336	May cause drowsiness or dizziness.

· Label elements

- *GHS label elements*
The product is classified and labeled according to the Globally Harmonized System (GHS).
- *Hazard pictograms*



GHS02 GHS05 GHS07

- *Signal word* Danger
- *Hazard-determining components of labeling:*
2-methylpropan-1-ol
isobutyl acetate
butan-1-ol
ethyl acetate
- *Hazard statements*
H225 Highly flammable liquid and vapor.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.
- *Precautionary statements*
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a poison center/doctor.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Product number TS1170
Trade name: UR CLEAR PRECAT SELF-S 80SH

(Contd. of page 1)

Classification system:

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



3 Composition/information on ingredients

Chemical characterization: Mixtures

· **Description:** Mixture: consisting of the following components.

Dangerous components:

110-19-0	isobutyl acetate ⚠ Flammable Liquids 2, H225 ⚠ Specific Target Organ Toxicity - Single Exposure 3, H336	15-19.99%
141-78-6	ethyl acetate ⚠ Flammable Liquids 2, H225 ⚠ Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	15-19.99%
123-86-4	n-butyl acetate ⚠ Flammable Liquids 3, H226 ⚠ Specific Target Organ Toxicity - Single Exposure 3, H336	15-19.99%
67-64-1	acetone ⚠ Flammable Liquids 2, H225 ⚠ Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	10-12.49%
67-63-0	propan-2-ol ⚠ Flammable Liquids 2, H225 ⚠ Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	5-9.99%
78-83-1	2-methylpropan-1-ol ⚠ Flammable Liquids 3, H226 ⚠ Eye Damage 1, H318 ⚠ Skin Irritation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H335-H336	≥2.5-<3%
71-36-3	butan-1-ol ⚠ Flammable Liquids 3, H226 ⚠ Eye Damage 1, H318 ⚠ Acute Toxicity - Oral 4, H302; Skin Irritation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H335-H336	1-2.49%
95-47-6	o-xylene ⚠ Flammable Liquids 3, H226 ⚠ Aspiration Hazard 1, H304 ⚠ Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irritation 2, H315; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H335	<0.5%

(Contd. on page 3)

Product number TS1170
Trade name: UR CLEAR PRECAT SELF-S 80SH

50-00-0	formaldehyde	(Contd. of page 2) <0.1%
	<ul style="list-style-type: none"> Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331 Germ Cell Mutagenicity 2, H341; Carcinogenicity 1B, H350 Skin Corrosion 1B, H314 Sensitization - Skin 1A, H317 Flammable Liquids 4, H227 	

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Immediately rinse with water.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

For symptoms and effects caused by substances, refer to Section 11.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

Alcohol resistant foam

Alcohol resistant foam, CO, powder, water spray/mist.

· **For safety reasons unsuitable extinguishing agents:**

Do not use a jet water stream as it may scatter and spread fire.

· **Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

· **Advice for firefighters**

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· **Protective equipment:**

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

Product number TS1170
Trade name: UR CLEAR PRECAT SELF-S 80SH

(Contd. of page 3)

- *Ensure adequate ventilation*
- *Keep away from ignition sources*
- **Environmental precautions:** *Do not allow to enter sewers/ surface or ground water.*
- **Methods and material for containment and cleaning up:**
*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to Section 13.
Ensure adequate ventilation.*
- **Reference to other sections**
*See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.*
- **Protective Action Criteria for Chemicals**

· PAC-1:		
110-19-0	isobutyl acetate	450 ppm
141-78-6	ethyl acetate	1,200 ppm
123-86-4	n-butyl acetate	5 ppm
67-64-1	acetone	200 ppm
67-63-0	propan-2-ol	400 ppm
78-83-1	2-methylpropan-1-ol	150 ppm
71-36-3	butan-1-ol	60 ppm

· PAC-2:		
110-19-0	isobutyl acetate	1300* ppm
141-78-6	ethyl acetate	1,700 ppm
123-86-4	n-butyl acetate	200 ppm
67-64-1	acetone	3200* ppm
67-63-0	propan-2-ol	2000* ppm
78-83-1	2-methylpropan-1-ol	1,300 ppm
71-36-3	butan-1-ol	800 ppm

· PAC-3:		
110-19-0	isobutyl acetate	7500** ppm
141-78-6	ethyl acetate	10000** ppm
123-86-4	n-butyl acetate	3000* ppm
67-64-1	acetone	5700* ppm
67-63-0	propan-2-ol	12000** ppm
78-83-1	2-methylpropan-1-ol	8000* ppm
71-36-3	butan-1-ol	8000** ppm

7 Handling and storage

- **Handling:**
 - **Precautions for safe handling**
*Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
Protect against electrostatic charges.
Use explosion-proof apparatus / fittings and spark-proof tools.*
 - **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.

(Contd. on page 5)

Product number TS1170**Trade name: UR CLEAR PRECAT SELF-S 80SH**

(Contd. of page 4)

Protect against electrostatic charges.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

- Store in a cool, well-ventilated area, away from heat and sources of ignition

- Provide solvent resistant, sealed floor.

- Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

- In cases where there is no reported expiration date, it means that the product must be used within 8 months.

- **Information about storage in one common storage facility: Not required.**

- **Further information about storage conditions:**

- Keep receptacle tightly sealed.

- Store in cool, dry conditions in well sealed receptacles.

- **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

110-19-0 isobutyl acetate

PEL	Long-term value: 700 mg/m , 150 ppm
REL	Long-term value: 700 mg/m , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

141-78-6 ethyl acetate

PEL	Long-term value: 1400 mg/m , 400 ppm
REL	Long-term value: 1400 mg/m , 400 ppm
TLV	Long-term value: 400 ppm

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m , 150 ppm
REL	Short-term value: 950 mg/m , 200 ppm Long-term value: 710 mg/m , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

67-64-1 acetone

PEL	Long-term value: 2400 mg/m , 1000 ppm
REL	Long-term value: 590 mg/m , 250 ppm
TLV	Short-term value: 500 ppm Long-term value: 250 ppm A4, BEI

67-63-0 propan-2-ol

PEL	Long-term value: 980 mg/m , 400 ppm
REL	Short-term value: 1225 mg/m , 500 ppm Long-term value: 980 mg/m , 400 ppm
TLV	Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4

(Contd. on page 6)

Product number TS1170**Trade name: UR CLEAR PRECAT SELF-S 80SH**

(Contd. of page 5)

78-83-1 2-methylpropan-1-ol

PEL Long-term value: 300 mg/m , 100 ppm

REL Long-term value: 150 mg/m , 50 ppm

TLV Long-term value: 50 ppm

71-36-3 butan-1-ol

PEL Long-term value: 300 mg/m , 100 ppm

REL Ceiling limit value: 150 mg/m , 50 ppm
Skin

TLV Long-term value: 20 ppm

95-47-6 o-xylene

PEL Long-term value: 435 mg/m , 100 ppm

REL Short-term value: 655 mg/m , 150 ppm
Long-term value: 435 mg/m , 100 ppmTLV Short-term value: (150) ppm
Long-term value: (100) NIC-20 ppm
BEI, A4**50-00-0 formaldehyde**PEL Short-term value: 2 ppm
Long-term value: 0.75 ppm
see 29 CFR 1910.1048(c)REL Long-term value: 0.016 ppm
Ceiling limit value: 0.1* ppm
*15-min; See Pocket Guide App. ATLV Short-term value: 0.3 ppm
Long-term value: 0.1 ppm
DSEN; RSEN, A1**· Ingredients with biological limit values:****67-64-1 acetone**BEI 25 mg/L
Medium: urine
Time: end of shift
Parameter: Acetone (nonspecific)**67-63-0 propan-2-ol**BEI 40 mg/L
Medium: urine
Time: end of shift at end of workweek
Parameter: Acetone (background, nonspecific)**95-47-6 o-xylene**BEI 1.5 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids**· Additional information:** The lists that were valid during the creation were used as basis.**· Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.

(Contd. on page 7)

Product number TS1170
Trade name: UR CLEAR PRECAT SELF-S 80SH

(Contd. of page 6)

Avoid contact with the eyes and skin.

- **Breathing equipment:**
Short term filter device:
Filter AX



Suitable respiratory protective device recommended.

- **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

· **Form:**

Fluid

· **Color:**

According to product specification

· **Odor:**

Characteristic

· **Odor threshold:**

Not determined.

· **pH-value:**

Mixture is non-polar/aprotic.

· Change in condition

· **Melting point/Melting range:**

Undetermined.

· **Boiling point/Boiling range:**

56 °C (132.8 °F)

· **Flash point:**

-4 °C (24.8 °F)

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

340 °C (644 °F)

· **Decomposition temperature:**

Not determined.

(Contd. on page 8)

Product number TS1170**Trade name: UR CLEAR PRECAT SELF-S 80SH**

(Contd. of page 7)

· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.	
· Explosion limits:		
· Lower:	1.2 Vol %	
· Upper:	13 Vol %	
· Vapor pressure at 20 °C (68 °F):	233 hPa (174.8 mm Hg)	
· Density (+/- 0,03) at 20 °C (68 °F):	0.955 g/cm (7.969 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water):	Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
· Kinematic at 20 °C (68 °F):	25 s (ISO 6 mm)	
· Oxidising properties:	N.A.	
· Solvent content:		
· VOC content:	64.46 % 615.6 g/l / 5.14 lb/gal	
· Solids content:	25.5 %	
· Other information (HAPS)		
95-47-6	o-xylene	<0.5%
50-00-0	formaldehyde	<0.1%
· Other information	No further relevant information available.	

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:**

in case of possible formation of combustion:
Carbon monoxide and carbon dioxide

US

(Contd. on page 9)

Product number TS1170
Trade name: UR CLEAR PRECAT SELF-S 80SH

(Contd. of page 8)

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral	LD50	47,403 mg/kg
------	------	--------------

110-19-0 isobutyl acetate

Oral	LD50	13,400 mg/kg (mouse)
Dermal	LD50	17,401 mg/kg (rabbit)
Inhalative	LC50/4 h	31 mg/l (mouse)

141-78-6 ethyl acetate

Oral	LD50	4,934 mg/kg (rabbit)
Dermal	LD50	20,001 mg/kg (rabbit)
Inhalative	LC50/4 h	1,600 mg/l (mouse)
	LC0	22.6 ppm (mouse)

123-86-4 n-butyl acetate

Oral	LD50	10,760 mg/kg (mouse)
Dermal	LD50	14,000 mg/kg (rabbit)
Inhalative	LC50/4 h	21.1 mg/l (mouse)

67-64-1 acetone

Oral	LD50	5,800 mg/kg (mouse)
Dermal	LD50	20,000 mg/kg (rabbit)
Inhalative	LC50/4 h	76 mg/l (mouse)

67-63-0 propan-2-ol

Oral	LD50	4,710 mg/kg (mouse)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	72.6 mg/l (mouse)

78-83-1 2-methylpropan-1-ol

Oral	LD50	2,460 mg/kg (mouse)
Dermal	LD50	3,400 mg/kg (rabbit)
Inhalative	LC50/4h.	19.2 mg/l (mouse)

71-36-3 butan-1-ol

Oral	LD50	790 mg/kg (mouse)
Dermal	LD50	3,400 mg/kg (rabbit)
Inhalative	LC50/4 h	8,000 mg/l (mouse)

50-00-0 formaldehyde

Oral	LD50	100 mg/kg (mouse)
Dermal	LD50	270 mg/kg (rabbit)

· Primary irritant effect:

· on the skin: No irritant effect.

· on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

· Sensitization: No sensitizing effects known.

(Contd. on page 10)

Product number TS1170**Trade name: UR CLEAR PRECAT SELF-S 80SH**

(Contd. of page 9)

 · **Additional toxicological information:**

Irritant

Causes serious eye damage.

May cause drowsiness or dizziness.

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

 · **Carcinogenic categories**

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)		
50-00-0	formaldehyde	1
· NTP (National Toxicology Program)		
50-00-0	formaldehyde	<0.1%
· OSHA-Ca (Occupational Safety & Health Administration)		
50-00-0	formaldehyde	<0.1%

12 Ecological information

 · **Toxicity**

· Aquatic toxicity:	
110-19-0 isobutyl acetate	
EC50	370 mg/l (algae) (72 h) 25 mg/l (daphnia)
LC50 (96h)	17 mg/l (Fish)
141-78-6 ethyl acetate	
EC50	165 mg/l (daphnia) (48 h)
LC50 (96h)	230 mg/l (Fish)
123-86-4 n-butyl acetate	
EC50	397 mg/l (algae) (72 h) 44 mg/l (daphnia) (48 h)
LC50 (96h)	18 mg/l (Fish)
67-64-1 acetone	
EC50	8,800 mg/l (daphnia)
LC50 (96h)	5,540 mg/l (Fish)
67-63-0 propan-2-ol	
EC50	1,001 mg/l (algae) (72 h) 10,000 mg/l (daphnia) (24 h)
LC50 (96h)	9,640 mg/l (Fish)
78-83-1 2-methylpropan-1-ol	
EC50	1,799 mg/l (algae) (72 h) 1,100 mg/l (daphnia) (48 h)
LC50 (96h)	1,430 mg/l (Fish)
50-00-0 formaldehyde	
EC50	4.89 mg/l (algae) (72 h) 5.8 mg/l (daphnia) (48 h)
LC50 (96h)	6.7 mg/l (Fish)

 · **Persistence and degradability** No further relevant information available.

(Contd. on page 11)

Product number TS1170**Trade name: UR CLEAR PRECAT SELF-S 80SH**

(Contd. of page 10)

· Substances Easily biodegradable

110-19-0	isobutyl acetate	.
141-78-6	ethyl acetate	.
123-86-4	n-butyl acetate	.
67-64-1	acetone	.
67-63-0	propan-2-ol	.
78-83-1	2-methylpropan-1-ol	.

· Behavior in environmental systems:

- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

· Additional ecological information:
· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

· Waste treatment methods
· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· Uncleaned packagings:

- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number

· DOT, IMDG, IATA

UN1263

· Note

Check viscosity and flash point at section 9

· UN proper shipping name

· DOT

Paint

· IMDG, IATA

PAINT

· Transport hazard class(es)

· DOT



· Class

3 Flammable liquids

· Label

3


· Class

3 Flammable liquids

(Contd. on page 12)

Product number TS1170
Trade name: UR CLEAR PRECAT SELF-S 80SH

(Contd. of page 11)

· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	II
· DOT, IMDG, IATA	
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	33
· EMS Number:	F-E, S-E
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Various regulations**
- **SARA**

· Section 355 (extremely hazardous substances):		
50-00-0	formaldehyde	<0.1%
· Section 313 (Specific toxic chemical listings) :		
67-63-0	propan-2-ol	5-9.99%
71-36-3	butan-1-ol	1-2.49%
95-47-6	o-xylene	<0.5%
50-00-0	formaldehyde	<0.1%
110-82-7	cyclohexane	≥0.025-<0.1%
· TSCA (Toxic Substances Control Act):		
All components have the value ACTIVE.		

(Contd. on page 13)

Product number TS1170
Trade name: UR CLEAR PRECAT SELF-S 80SH

(Contd. of page 12)

<i>· Hazardous Air Pollutants</i>			
95-47-6	o-xylene		
50-00-0	formaldehyde		
<i>· Proposition 65</i>			
<i>· Chemicals known to cause cancer:</i>			
50-00-0	formaldehyde	*	<0.1%
<i>· Chemicals known to cause reproductive toxicity for females:</i>			
None of the ingredients is listed.			
<i>· Chemicals known to cause reproductive toxicity for males:</i>			
None of the ingredients is listed.			
<i>· Chemicals known to cause developmental toxicity:</i>			
None of the ingredients is listed.			
<i>· Carcinogenic categories</i>			
<i>· EPA (Environmental Protection Agency)</i>			
67-64-1	acetone	I	10-12.49%
71-36-3	butan-1-ol	D	1-2.49%
95-47-6	o-xylene	I	<0.5%
50-00-0	formaldehyde	B1	<0.1%
110-82-7	cyclohexane	I	≥0.025-<0.1%
<i>· TLV (Threshold Limit Value)</i>			
67-64-1	acetone		A4
67-63-0	propan-2-ol		A4
95-47-6	o-xylene		A4
50-00-0	formaldehyde		A2
<i>· NIOSH-Ca (National Institute for Occupational Safety and Health)</i>			
50-00-0	formaldehyde		<0.1%

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS:** IVM Chemicals Srl
- Contact:** See emergency phone
 - Date of preparation / last revision** 09/07/2022 / 9
- Abbreviations and acronyms:**
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - NFPA: National Fire Protection Association (USA)
 - HMIS: Hazardous Materials Identification System (USA)
 - VOC: Volatile Organic Compounds (USA, EU)
 - LC50: Lethal concentration, 50 percent

(Contd. on page 14)

Product number TS1170
Trade name: UR CLEAR PRECAT SELF-S 80SH

(Contd. of page 13)

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids . Category 2

Flammable Liquids 3: Flammable liquids . Category 3

Flammable Liquids 4: Flammable liquids . Category 4

Acute Toxicity - Oral 3: Acute toxicity . Category 3

Acute Toxicity - Oral 4: Acute toxicity . Category 4

Skin Corrosion 1B: Skin corrosion/irritation . Category 1B

Skin Irritation 2: Skin corrosion/irritation . Category 2

Eye Damage 1: Serious eye damage/eye irritation . Category 1

Eye Irritation 2A: Serious eye damage/eye irritation . Category 2A

Sensitization - Skin 1A: Skin sensitisation . Category 1A

Germ Cell Mutagenicity 2: Germ cell mutagenicity . Category 2

Carcinogenicity 1B: Carcinogenicity . Category 1B

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) . Category 3

Aspiration Hazard 1: Aspiration hazard . Category 1

- **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

- * Data compared to the previous version altered.