


## 1 Identification

- **Product identifier**
  - *Product number* WUM5A06E
  - *Trade name:* **SELF SEALER WB UV WHITE 45GL**
    - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
  - *Manufacturer/Supplier:*  
IVM Chemicals Srl  
Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
  - *Information department:*  
Environmental Health and safety office  
hseoffice@ivmchemicals.com
  - *Emergency telephone number:*  
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.


## 2 Hazard(s) identification

- **Classification of the substance or mixture**


Sensitization - Skin 1 H317 May cause an allergic skin reaction.  
 Carcinogenicity 2 H351 Suspected of causing cancer.  
 Aquatic Acute 2 H401 Toxic to aquatic life.  
 Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.
- **Label elements**
  - *GHS label elements*  
The product is classified and labeled according to the Globally Harmonized System (GHS).
  - *Hazard pictograms*



GHS07



GHS08



GHS09
  - *Signal word* Warning
  - *Hazard-determining components of labeling:*  
2,2-bis(acryloyloxymethyl)butyl acrylate  
2-methyl-2H-isothiazol-3-one  
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide
  - *Hazard statements*  
H317 May cause an allergic skin reaction.  
H351 Suspected of causing cancer.  
H401 Toxic to aquatic life.  
H411 Toxic to aquatic life with long lasting effects.
  - *Precautionary statements*  
P261 Avoid breathing dust/fume/gas/mist/vapors/spray  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P363 Wash contaminated clothing before reuse.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

US

**Product number WUM5A06E**  
**Trade name: SELF SEALER WB UV WHITE 45GL**

(Contd. of page 1)

**Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



**3 Composition/information on ingredients**

**Chemical characterization: Mixtures**

· **Description:** Mixture: consisting of the following components.

· **Dangerous components:**

15625-89-5	2,2-bis(acryloyloxymethyl)butyl acrylate ⚠ Carcinogenicity 2, H351 ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410 ⚠ Skin Irritation 2, H315; Eye Irritation 2A, H319; Sensitization - Skin 1, H317	5-9.99%
7473-98-5	2-hydroxy-2-methylpropiophenone ⚠ Acute Toxicity - Oral 4, H302 Aquatic Acute 3, H402; Aquatic Chronic 3, H412	<2.5%
5131-66-8	3-butoxypropan-2-ol ⚠ Skin Irritation 2, H315; Eye Irritation 2A, H319 Flammable Liquids 4, H227	1-2.49%
111-90-0	Diethylene glycol monoethyl ether Flammable Liquids 4, H227	0.5-1%
112-34-5	2-(2-butoxyethoxy)ethanol ⚠ Eye Irritation 2A, H319	0.5-1%
162881-26-7	phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide ⚠ Sensitization - Skin 1A, H317 Aquatic Chronic 4, H413	≥0.1-<0.5%
2682-20-4	2-methyl-2H-isothiazol-3-one ⚠ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331 ⚠ Skin Corrosion 1B, H314; Eye Damage 1, H318 ⚠ Sensitization - Skin 1, H317	≥0.0015-<0.01%
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1) ⚠ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 2, H310; Acute Toxicity - Inhalation 2, H330 ⚠ Skin Corrosion 1B, H314; Eye Damage 1, H318 ⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100) ⚠ Sensitization - Skin 1A, H317	≥0.00025-<0.0015%

US

(Contd. on page 3)

**Product number WUM5A06E**  
**Trade name: SELF SEALER WB UV WHITE 45GL**

(Contd. of page 2)

#### 4 First-aid measures

· **Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

#### 5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:**

Do not use a jet water stream as it may scatter and spread fire.

· **Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Nitrogen oxides (NO<sub>x</sub>)

Carbon monoxide (CO)

· **Advice for firefighters**

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· **Protective equipment:**

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

#### 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Keep away from ignition sources

· **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

(Contd. on page 4)

**Product number WUM5A06E****Trade name: SELF SEALER WB UV WHITE 45GL**

(Contd. of page 3)

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

· PAC-1:		
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	30 mg/m
111-90-0	Diethylene glycol monoethyl ether	75 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm
68439-49-6	c16-18 alcohols ethoxylated	3.8 mg/m
7631-86-9	silicon dioxide, chemically prepared	18 mg/m
25322-69-4	Propane-1,2-diol, propoxylated	30 mg/m
· PAC-2:		
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	330 mg/m
111-90-0	Diethylene glycol monoethyl ether	100 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm
68439-49-6	c16-18 alcohols ethoxylated	42 mg/m
7631-86-9	silicon dioxide, chemically prepared	740 mg/m
25322-69-4	Propane-1,2-diol, propoxylated	330 mg/m
· PAC-3:		
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2,000 mg/m
111-90-0	Diethylene glycol monoethyl ether	450 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm
68439-49-6	c16-18 alcohols ethoxylated	250 mg/m
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m
25322-69-4	Propane-1,2-diol, propoxylated	2,000 mg/m

## 7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Keep respiratory protective device available.

- **Information about protection against explosions and fires:**

Keep respiratory protective device available.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

- **Information about storage in one common storage facility: Not required.**

- **Further information about storage conditions: Keep receptacle tightly sealed.**

(Contd. on page 5)

**Product number WUM5A06E**
**Trade name: SELF SEALER WB UV WHITE 45GL**

(Contd. of page 4)

- **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

15625-89-5 2,2-bis(acryloyloxymethyl)butyl acrylate	
WEEL	Long-term value: 1 mg/m Skin
111-90-0 Diethylene glycol monoethyl ether	
WEEL	Long-term value: 25 ppm
112-34-5 2-(2-butoxyethoxy)ethanol	
TLV	Long-term value: 10* ppm *Inhalable fraction and vapor

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

- **Breathing equipment:**

Not required.

Short term filter device:



Suitable respiratory protective device recommended.

Filter A

- **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

**Product number WUM5A06E**
**Trade name: SELF SEALER WB UV WHITE 45GL**

(Contd. of page 5)

- *Penetration time of glove material*  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- *Eye protection:* Goggles recommended during refilling.

## 9 Physical and chemical properties

### · Information on basic physical and chemical properties

#### · General Information

##### · Appearance:

##### · Form:

Fluid

##### · Color:

According to product specification

##### · Odor:

Characteristic

##### · Odor threshold:

Not determined.

##### · pH-value:

Mixture is non-polar/aprotic.  
Range: 7 - 9

#### · Change in condition

##### · Melting point/Melting range:

Undetermined.

##### · Boiling point/Boiling range:

100 °C (212 °F)

##### · Flash point:

95 °C (203 °F)

##### · Flammability (solid, gaseous):

Not applicable.

##### · Ignition temperature:

190 °C (374 °F)

##### · Decomposition temperature:

Not determined.

##### · Auto igniting:

Product is not selfigniting.

##### · Danger of explosion:

Product does not present an explosion hazard.

#### · Explosion limits:

##### · Lower:

1.1 Vol %

##### · Upper:

8.4 Vol %

##### · Vapor pressure at 20 °C (68 °F):

1.3 hPa (1 mm Hg)

##### · Density (+/- 0,03) at 20 °C (68 °F):

1.139 g/cm (9.505 lbs/gal)

##### · Relative density

Not determined.

##### · Vapor density

Not determined.

##### · Evaporation rate

Not determined.

#### · Solubility in / Miscibility with

##### · Water:

Fully miscible.

##### · Partition coefficient (n-octanol/water): Not determined.

#### · Viscosity:

##### · Dynamic:

Not determined.

##### · Kinematic at 20 °C (68 °F):

60 s (ISO 6 mm)

##### · Oxidising properties:

N.A.

#### · Solvent content:

##### · Water:

51.0 %

##### · VOC content:

3.19 %

36.4 g/l / 0.30 lb/gal

##### · Solids content:

45.8 %

(Contd. on page 7)



**Product number WUM5A06E**
**Trade name: SELF SEALER WB UV WHITE 45GL**

(Contd. of page 6)

**· Other information (HAPS)**

111-90-0	Diethylene glycol monoethyl ether	0.5-1%
112-34-5	2-(2-butoxyethoxy)ethanol	0.5-1%
121-44-8	triethylamine	<0.1%
110-80-5	2-ethoxyethanol	<0.01%
<b>· Other information</b>		No further relevant information available.

**10 Stability and reactivity**

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
  - **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:** No dangerous decomposition products known.

**11 Toxicological information**
**· Information on toxicological effects**
**· Acute toxicity:**
**· LD/LC50 values that are relevant for classification:**
**ATE (Acute Toxicity Estimate)**

Oral	LD50	106,207 mg/kg (mouse)
<b>15625-89-5 2,2-bis(acryloyloxymethyl)butyl acrylate</b>		
Oral	LD50	5,001 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (mouse)
<b>7473-98-5 2-hydroxy-2-methylpropiophenone</b>		
Oral	LD50	1,694 mg/kg (mouse)
Dermal	LD50	6,929 mg/kg (mouse)
<b>5131-66-8 3-butoxypropan-2-ol</b>		
Oral	LD50	3,300 mg/kg (mouse)
Dermal	LD50	8,001 mg/kg (mouse)
<b>111-90-0 Diethylene glycol monoethyl ether</b>		
Oral	LD50	6,031 mg/kg (mouse)
Dermal	LD50	9,143 mg/kg (rabbit)
<b>112-34-5 2-(2-butoxyethoxy)ethanol</b>		
Oral	LD50	6,600 mg/kg (mouse)
Dermal	LD50	2,764 mg/kg (rabbit)
<b>162881-26-7 phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide</b>		
Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (mouse)

(Contd. on page 8)

**Product number WUM5A06E**
**Trade name: SELF SEALER WB UV WHITE 45GL**

(Contd. of page 7)

**2682-20-4 2-methyl-2H-isothiazol-3-one**

Oral	LD50	200 mg/kg (mouse)
Dermal	LD50	400 mg/kg (mouse)
Inhalative	LC50/4 h	0.53 mg/l (mouse)

 · **Primary irritant effect:**

- *on the skin:* No irritant effect.
- *on the eye:* No irritating effect.

- **Sensitization:** Sensitization possible through skin contact.

 · **Additional toxicological information:**
**Irritant**

May cause an allergic skin reaction.

Suspected of causing cancer.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

 · **Carcinogenic categories**
**Titanium dioxide**

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

 · **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2B - DUST
15625-89-5	2,2-bis(acryloyloxymethyl)butyl acrylate	2B

 · **NTP (National Toxicology Program)**

None of the ingredients is listed.

 · **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**12 Ecological information**

- **Toxicity** Toxic to aquatic life with long lasting effects.

 · **Aquatic toxicity:**
**15625-89-5 2,2-bis(acryloyloxymethyl)butyl acrylate**

EC50	4.9 mg/l (algae) (72 h)
	19.9 mg/l (daphnia) (48 h)
LC50 (96h)	2.1 mg/l (Fish)

**7473-98-5 2-hydroxy-2-methylpropiophenone**

EC50	119 mg/l (daphnia) (48h)
LC50 (96h)	160 mg/l (Fish)

**5131-66-8 3-butoxypropan-2-ol**

EC50	1,001 mg/l (algae) (96 h)
	1,001 mg/l (daphnia) (48 h)
LC50 (96h)	1,000 mg/l (Fish)

**111-90-0 Diethylene glycol monoethyl ether**

LC50 48h	1,982 mg/l (daphnia)
----------	----------------------

(Contd. on page 9)



**Product number** WUM5A06E  
**Trade name:** SELF SEALER WB UV WHITE 45GL

(Contd. of page 8)

LC50 (96h)	101 mg/l (Fish)
<b>112-34-5 2-(2-butoxyethoxy)ethanol</b>	
EC50	1,001 mg/l (daphnia) (48 h)
LC50 (96h)	1,300 mg/l (Leuciscus idus melanotus)
<b>162881-26-7 phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide</b>	
EC50	1,175 mg/l (daphnia) 48h
<b>55965-84-9 a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)</b>	
EC50	0.027 mg/l (algae) (72 h) 0.16 mg/l (daphnia) (48 h)
LC50 (96h)	0.19 mg/l (Fish)

· **Persistence and degradability** No further relevant information available.

· **Substances Easily biodegradable**

15625-89-5	2,2-bis(acryloyloxymethyl)butyl acrylate	.
5131-66-8	3-butoxypropan-2-ol	.
111-90-0	Diethylene glycol monoethyl ether	.
112-34-5	2-(2-butoxyethoxy)ethanol	.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Ecotoxicological effects:**

· **Remark:** Toxic for fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

· **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

· **Recommended cleansing agent:** Water, if necessary with cleansing agents.



US

(Contd. on page 10)

**Product number** WUM5A06E  
**Trade name:** SELF SEALER WB UV WHITE 45GL

(Contd. of page 9)

## 14 Transport information

<ul style="list-style-type: none"> <li>· <b>UN-Number</b></li> <li>· DOT, IMDG, IATA</li> <li>· Note</li> </ul>	UN3082  Check viscosity and flash point at section 9
<ul style="list-style-type: none"> <li>· <b>UN proper shipping name</b></li> <li>· DOT</li> <li>· IMDG</li> <li>· IATA</li> </ul>	Environmentally hazardous substance, liquid, n.o.s. ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2-bis(acryloyloxymethyl)butyl acrylate), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2-bis(acryloyloxymethyl)butyl acrylate)
<ul style="list-style-type: none"> <li>· <b>Transport hazard class(es)</b></li> <li>· DOT, IMDG, IATA</li> </ul> <div style="display: flex; align-items: center; gap: 10px;">   </div> <ul style="list-style-type: none"> <li>· Class</li> <li>· Label</li> <li>· Class</li> <li>· Label</li> </ul>	9 Miscellaneous dangerous substances and articles 9 9 Miscellaneous dangerous substances and articles 9
<ul style="list-style-type: none"> <li>· <b>Packing group</b></li> <li>· DOT, IMDG, IATA</li> </ul>	III
<ul style="list-style-type: none"> <li>· <b>Environmental hazards:</b></li> <li>· Marine pollutant:</li> <li>· Special marking (IATA):</li> </ul>	Product contains environmentally hazardous substances: Yes Symbol (fish and tree) Symbol (fish and tree)
<ul style="list-style-type: none"> <li>· <b>Special precautions for user</b></li> <li>· Hazard identification number (Kemler code):</li> <li>· EMS Number:</li> <li>· Stowage Category</li> </ul>	Warning: Miscellaneous dangerous substances and articles 90 F-A,S-F A
<ul style="list-style-type: none"> <li>· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b></li> </ul>	Not applicable.
<ul style="list-style-type: none"> <li>· <b>Transport/Additional information:</b></li> <li>· DOT</li> <li>· Remarks:</li> </ul>	Special marking with the symbol (fish and tree).
<ul style="list-style-type: none"> <li>· <b>IMDG</b></li> <li>· Limited quantities (LQ)</li> <li>· Excepted quantities (EQ)</li> </ul>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml

(Contd. on page 11)

**Product number** WUM5A06E  
**Trade name:** SELF SEALER WB UV WHITE 45GL

(Contd. of page 10)

Maximum net quantity per outer packaging:  
1000 ml

· **UN "Model Regulation":** UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2-BIS(ACRYLOYLOXYMETHYL)BUTYL ACRYLATE), 9, III

## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Various regulations
- SARA

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings) :**

111-90-0	Diethylene glycol monoethyl ether	0.5-1%
112-34-5	2-(2-butoxyethoxy)ethanol	0.5-1%
121-44-8	triethylamine	<0.1%
110-80-5	2-ethoxyethanol	<0.01%

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

121-44-8	triethylamine
----------	---------------

· **Proposition 65**

· **Chemicals known to cause cancer:**

Titanium dioxide only in bound form

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	only for Dust	10-12.49%
15625-89-5	2,2-bis(acryloyloxymethyl)butyl acrylate	*	5-9.99%

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

110-80-5	2-ethoxyethanol	<0.01%
----------	-----------------	--------

· **Chemicals known to cause developmental toxicity:**

110-80-5	2-ethoxyethanol	<0.01%
----------	-----------------	--------

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	A4
121-44-8	triethylamine	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	10-12.49%
------------	---	-----------

(Contd. on page 12)

**Product number** WUM5A06E  
**Trade name:** SELF SEALER WB UV WHITE 45GL

(Contd. of page 11)

- **National regulations:**  
 The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl
- **Contact:** See emergency phone
  - **Date of preparation / last revision** 09/14/2022 / 5
  - **Abbreviations and acronyms:**  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 NIOSH: National Institute for Occupational Safety  
 OSHA: Occupational Safety & Health  
 TLV: Threshold Limit Value  
 PEL: Permissible Exposure Limit  
 REL: Recommended Exposure Limit  
 Flammable Liquids 4: Flammable liquids . Category 4  
 Acute Toxicity - Oral 3: Acute toxicity . Category 3  
 Acute Toxicity - Oral 4: Acute toxicity . Category 4  
 Acute Toxicity - Dermal 2: Acute toxicity . Category 2  
 Skin Corrosion 1B: Skin corrosion/irritation . Category 1B  
 Skin Irritation 2: Skin corrosion/irritation . Category 2  
 Eye Damage 1: Serious eye damage/eye irritation . Category 1  
 Eye Irritation 2A: Serious eye damage/eye irritation . Category 2A  
 Sensitization - Skin 1: Skin sensitisation . Category 1  
 Sensitization - Skin 1A: Skin sensitisation . Category 1A  
 Carcinogenicity 2: Carcinogenicity . Category 2  
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard . Category 1  
 Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard . Category 2  
 Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard . Category 3  
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard . Category 1  
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard . Category 2  
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3  
 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard . Category 4
- **Sources**  
 REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments  
  
 Agency ECHA web site  
 INRS Fiche Toxicologique  
 IARC International agency for research on cancer
- **\* Data compared to the previous version altered.**