ILVA TECHNICAL DATA SHEET

PZ3.../COLOR SERIES PRODUCT CODE:

POLYURETHANE PIGMENTED TINT PASTE **DESCRIPTION:**

Tinting colors for Polyurethane Products. In general they may be used in all polyurethane systems at a USES:

> level of 20-30% maximum combined color level with no effect on film properties, only gloss levels at the maximum level of tint paste. If used in Acrylic Urethane maximum level is 10%

AVAILABLE COLORS: PZ330 White

PZ331 Vivid Yellow PZ332 Gold Yellow PZ333 Yellow Oxide PZ335 Wisteria Red PZ336 Red Oxide PZ337 Bordeaux PZ338 Blue PZ339 Black PZ340 Green PZ341 Lemon Yellow PZ344 Vivid Red PZ347 Violet

PZ355 Red Concentrate

PZ361 Yellow PZ364 Orange

CODE Density (Kg/I Density (lb/US gal) Solid content % CHEMICAL/PHYSICAL **PROPERTIES**

PZ330	1.877 +/- 0.030	15.7 +/-	0.3	74.0 +/- 2
PZ331	0.987 +/- 0.030	8.2 +/-	0.3	48.0 +/- 2
PZ332	1.081 +/- 0.030	9.0 +/-	0.3	49.0 +/- 2
PZ333	1.550 +/- 0.030	12.9 +/-	0.3	54.0 +/- 2
PZ335	0.995 +/- 0.030	8.3 +/-	0.3	35.0 +/- 2
PZ336	1.608 +/- 0.030	13.4 +/-	0.3	39.0 +/- 2
PZ337	1.056 +/- 0.030	8.8 +/-	0.3	54.0 +/- 2
PZ338	1.071 +/- 0.030	8.9 +/-	0.3	32.0 +/- 2
PZ339	1.040 +/- 0.030	8.7 +/-	0.3	44.0 +/- 2
PZ340	1.074 +/- 0.030	9.0 +/-	0.3	46.0 +/- 2
PZ341	1.590 +/- 0.030	13.3 +/-	0.3	68.0 +/- 2
PZ344	1.028 +/- 0.030	8.6 +/-	0.3	39.0 +/- 2
PZ347	1.038 +/- 0.030	8.7 +/-	0.3	38.0 +/- 2
PZ355	1.081 +/- 0.030	9.0 +/-	0.3	56.0 +/- 2
PZ361	1.091 +/- 0.030	9.1 +/-	0.3	48.0 +/- 2
PZ364	1.102 +/- 0.030	9.2 +/-	0.3	43.0 +/- 2

USAGE INDICATIONS: Must thoroughly mix paste before use. It is advisable to add pastes under mechanical mixing.

Quantities must be weighed with high precision balances.

One Year SHELF LIFE:

Store in a tightly closed container at room temperature 18-25°C, 64-75°F and protect from moisture and STORAGE:

foreign material.

DATE OF ISSUANCE: 12-16

IC & S, P.O. BOX 10845, LANCASTER, PA 17605 (800) 220-4035